

CLEANING SOLUTIONS

GENERAL CATALOGUE 2024

**HIGH PRESSURE WASHERS
STEAM GENERATORS
PURE WATER CLEANING SYSTEM
ELECTRIC VEHICLES**



IPC

BY TENNANT COMPANY

IPC GROUP SUMMARY

#3 EUROPEAN MANUFACTURER OF PROFESSIONAL CLEANING EQUIPMENT

IPC knows every detail of cleaning equipment, with five reknown and dedicated production sites, it is the undisputed Italian leader.

INNOVATIONS

INNOVATION THAT DELIVERS PRODUCTIVITY

IPC's large R&D team works as a group of experts in cleaning innovation to deliver tangible productivity benefits at a fast pace.

KEY VALUES

CLIENT-CENTRIC

IPC's tremendous depth of expertise and know-how are focused on delivering to customers specific solutions, addressing effectively emerging cleaning needs together.

KEY VALUES

COMMITTED TO SUSTAINABILITY

IPC's sustainable technologies contribute every year to improve energy, water savings and recycling of materials.

NETWORK

GLOBAL DISTRIBUTION

IPC has a global commercial network active in over 120 countries, with pervasive and complete service in reference markets.

PRODUCTS

COMPLETE PORTFOLIO


IPC provides a complete range of professional equipment including scrubber dryers, professional vacuum cleaners, high pressure washers and manual equipment.



IPC

BY TENNANT COMPANY

MORE THAN 1.000 SPECIALISTS DEDICATED TO "CLEAN ON"



HIGH PRESSURE WASHER DIVISION

50.000 pieces of hp
cleaners a year
and a **4.500 sq/m** of
warehouses.

Number of patents: 12

Certificates:

UNI EN ISO 9001:2015
UNI EN ISO 14001:2015
UNI ISO 45001:2018
UNI EN ISO 14067:2018




FLOORCARE DIVISION

40.000 pieces of
floorcare machines a
year and a **7.000 sq/m** of
warehouses.

Number of patents: 45

Certificates:

UNI EN ISO 9001:2015
UNI ISO 45001:2018
UNI EN ISO 14067:2018



VACUUM CLEANER DIVISION

200.000 pieces of
vacuums a year
and a **1.800 sq/m** of
warehouses.

Number of patents: 9

Certificates:

UNI EN ISO 9001:2015
UNI EN ISO 14001:2015
UNI ISO 45001:2018
UNI EN ISO 14067:2018



MANUAL TOOLS DIVISION


7 million pieces of
cleaning equipments a
year and **11.000 sq/m** of
warehouses.

Number of patents: 23

Certificates:

UNI EN ISO 9001:2015
UNI EN ISO 14067:2018

IPC IS ALWAYS WITH YOU ON PC, TABLET & SMARTPHONE



IPC

BY TENNANT COMPANY

**DOWNLOAD OUR
IPC CATALOGUES APP**
**DISCOVER OUR OFFICIAL WEBSITE
IPCWORLDWIDE.COM**



VISIT OUR OFFICIAL WEBSITE IPCWORLDWIDE.COM

Easy access to product leaflets, pictures and videos from any device.



DOWNLOAD OUR IPC CATALOGUES APP

Once downloaded, catalogues are always available, even offline.



REGISTER TO IPC BUSINESS AREA

You will have access to all IPC technical and commercial documents.



SIGN UP ON WEBSITE TO RECEIVE OUR NEWSLETTER

Keep updated on our latest news including new IPC products and events.

FOLLOW US



KEEP IN TOUCH WITH US

info@ipcworldwide.com





IPC

BY TENNANT COMPANY

HIGH PRESSURE WASHERS - COLD WATER



PW-C09

P. 32



PW-C22/PW-C22 P

P. 34



PW-C23 P

P. 36



PW-C21

P. 38



PW-C25

P. 40



PW-C25 PLUS

P. 42



PW-C40
BY-PASS

P. 44

PW-C40
DELAYED TOTAL STOP

P. 46

PW-C40
SPECIAL MODEL

P. 48



PW-C45 VALUE

P. 50

PW-C45 PREMIUM

P. 52



PW-C45

P. 54

PAINTED
STEEL
STRUCTURE



PW-C50

P. 56



PW-C55 VALUE

P. 58

PW-C55 PREMIUM

P. 60



PW-C55

P. 62

PAINTED
STEEL
STRUCTURE



IPC

BY TENNANT COMPANY

HIGH PRESSURE WASHERS - COLD WATER



PW-C85

P. 64



ABSOLUTE-C

P. 66



BENZ-C



P. 68



DIESEL-C

P. 70



FIRE BOX

P. 72



IPC

BY TENNANT COMPANY

HIGH PRESSURE WASHERS - HOT WATER



PW-H10

P. 78



PW-H28

P. 80



**STAINLESS
STEEL
SERIES**

PW-H28/4

P. 82



PW-H31 VALUE

P. 84



PW-H61 VALUE

P. 86

PW-H61 PREMIUM

P. 88



PW-H90

P. 90



PW-H101 VALUE

P. 92

PW-H101 PREMIUM

P. 94



PW-H101 HTM

P. 96



PW-H101 AUTOMATIC

P. 98



**STAINLESS
STEEL
SERIES**

PW-H100 P

P. 100



SKID FUEGO

P. 102



IPC

BY TENNANT COMPANY

HIGH PRESSURE WASHERS - COLD STATIONARY



MLC-C

P. 108



ML CMP

P. 110



ML-C

P. 112



SML-C

P. 114

HIGH PRESSURE WASHERS - HOT STATIONARY



IWD-H

P. 116

HIGH PRESSURE WASHERS - ELECTRICALLY HEATED BOILER



PW-E101
HIGH TEMPERATURE

P. 122

PW-E101

P. 124

**STAINLESS
STEEL
SERIES**



PW-E100

P. 126

**STAINLESS
STEEL
SERIES**



IWD-E

P. 128



IPC

BY TENNANT COMPANY

WEED REMOVAL SYSTEM - HOT WATER



GREEN JET 7006

P. 132



GREEN JET 1010

P. 134



GREEN JET 7510

P. 136

STEAM GENERATORS



SG-08/SG-10

P. 144



SG-20/SG-30

P. 146



SG-45

P. 148

**SOFT
TOUCH
PANEL**



SG-48

P. 150



SG-50

P. 152



SG-55

P. 154



SG-10 + PT 04

P. 156



IPC

BY TENNANT COMPANY

PURE WATER CLEANING SYSTEM - **GREEN TUBE** - HIGH PURE



HPB HIGH PURE

P. 165



HPE HIGH PURE

P. 166



HPG HIGH PURE

P. 167

ELECTRIC VEHICLES



TIGER 250/TIGER 250 BC

P. 172



TIGER 500

P. 173



HIGH-PRESSURE WASHERS

INNOVATIONS	12
SUGGESTED SECTORS	25
COLD WATER	29
HOT WATER	75
STATIONARY	113
ELECTRICALLY HEATED BOILER	119
HOT WATER WEED REMOVAL SYSTEM	130

IPC pressure washers nomenclature allows an easy and fast identification of the main technical features of each model. Following an example on PW-H50 D1310P4 M pressure washer:

PRESSURE
WASHERS

PW

-

H

H = HOT WATER
PRESSURE WASHER
C = COLD WATER
PRESSURE WASHER

PLATFORM

61

D

CONTROL SYSTEM:
- = BY PASS
I = IMMEDIATE TOTAL STOP
D = DELAYED TOTAL STOP
S = SAFETY STOP

MPA PRESSURE

18

FLOW RATE
l/min

13

PUMP TYPE

P = PLUNGER PUMP
A = AXIAL PUMP

P

POWER
M = SINGLE-PHASE
T = THREE-PHASE

T



AMSC™ ADVANCED MULTIFUNCTION SAFETY CONTROLS

FULL CONTROL OVER YOUR MACHINE.

The innovation Advanced Multifunction Safety Control is a high-tech system that provides the maximum machine safeguarding and the improvement of the operator safety at work.



- **IPSF** Intelligent Proportional Switching Off
- **DTS** Exclusive Delayed Total Stop
- **MLC** Micro Leakage Control
- **NCC** Nozzle Clogged Control
- **WHC** Working Hours Counter
- **FPS** Flooding Prevention System
- **IASF** Intelligent Automatic Switch Off
- **DRP** Dry Running Protection
- **IBD** Ignition Boiler Delay
- **FCS** Infrared Flame Control System
- **MCL** Maintenance Check Led
- **FLC** Fuel Level Control
- **HBLs** High Brightness Led Signals
- **DTSC** Digital temperature stabilizer control
- **LCPU** Limescale Corrosion Protection Unit

MSC™ MULTIFUNCTION SAFETY CONTROLS

The innovation MSC™ includes the functions: **IPSF, DTS, MLC, NCC, WHC, FPS, IASF, DRP, IBD, FCS, MCL, FLC, HBLs**
The machines provided with these technology are: **SML-C, IWD-H, PW-E100, IWD-E, GREEN JET 1010, GREEN JET 7510**

BENEFITS

- 01 Optimized cleaning operations in total safety.
- 02 Reduced energy consumption.
- 03 Reduced maintenance costs and prevented failures through the innovative self-diagnosis system.
- 04 No floods from leaks in the hydraulic circuit.



DIAD DIRECT INJECTION DETERGENT AND ANTI-SCALE

EXCELLENT RESULTS WHILE SAVING MONEY.

The direct injection anti-scale and detergent controls guarantee the desired and precise products mixing, by reducing detergent expense, mechanical vibrations and noise related to traditional system.

+Productivity

+
detergent
reduction

+
mechanical
vibration
reduction

+
noise
reduction



BENEFITS


- 01 Reduction of detergent expense, mechanical vibrations and noise due to traditional systems.
- 02 Operator productivity increase.
- 03 Pump life extension.



DTSC DIGITAL TEMPERATURE STABILIZER CONTROL

CONSTANT TEMPERATURE FOR INCREASED SAVINGS.

The system provides a high precise temperature control of the outlet water, by stabilizing the pre-set temperature and preventing high thermal variations



BENEFITS


- 01 Lower fuel consumption.
- 02 Lower maintenance costs.



ECO SYSTEM

REDUCED DIESEL CONSUMPTION, MAXIMIZED THE CLEANING.

This function leads to diesel consumption and emissions reduction up to 25% by setting the water temperature at 60° C automatically.



BENEFITS

- 01 Reduction of diesel consumption and emissions up to 25%.
- 02 Run time increase.
- 03 Maximization of detergents cleaning effect.



CIRCULAR DESIGN & OPERATION

ADDRESSING THE SUSTAINABILITY CHALLENGE.

The great commitment to the Environment is accomplished by recycled plastic, recyclable components and the reduction of diesel, energy and detergent consumptions.



BENEFITS

- 01 Direct injection against excessive detergent application.
- 02 Use of recycled plastic and more than 90% of recyclable components.
- 03 High serviceability for an increased product's lifespan.
- 04 High-quality, robust and durable materials.
- 05 FPS (Flooding Prevention System) which shuts the machine in case of hydraulic damages.



DIGITAL DISPLAY DD

USER-MACHINE INTUITIVE INTERACTION.

The digital display informs the operator on alerts and fault codes, saving time troubleshooting and bringing operators back to work. It can also confirm machine readiness prior to operation so employees know they are cleaning as intended.

Digital display - informs the operator on alerts and fault codes, saving time troubleshooting and getting operators back to work.

Digital display - confirms machine readiness prior to operation so employees know they are cleaning as intended.



**PLUS
VERSION
HTM
AUTOMATIC
PW-E101**



**VALUE
VERSION**

Warning Signal Lamps
Value versions are equipped with signal lamps to keep everything under control.

BENEFITS


- 01 Improvement of the user – machine interface for a more intuitive use.
- 02 Easy selection of the most appropriate cleaning solution according to the cleaning activity.



AUTOMATIC PRESSURE WASHER

AUTOMATIC VERSION FOR AN EASIER CLEANING.

The AUTOMATIC version allows to set the machine's programs automatically according to the cleaning, degreasing and sanitizing tasks.



BENEFITS


- 01 Machine's performances are adjusted according to specific cleaning needs.
- 02 Through High Temperature Master system (HTM), sanitizing and degreasing are performed at a stable temperature of 100°C., by automatically adjusting flow and pressure.



G6000™ CERAMIC HIGH-TECH GUN

LONG-LASTING HIGH PERFORMANCES.

The Low Activation Trigger and the comfortable grip are designed to ensure a more comfortable use to the operator.



BENEFITS

- 01 Best category technical features: 350bar - 45l/min - 160°C.
- 02 Long-lasting gun through the ceramic ball it is provided with. It ensures excellent resistance to wear, corrosion, soap, acids and chlorine.
- 03 Trigger lock to prevent accidental activation.
- 04 Provided with a brass swivel fitting, it prevents twisting of the high-pressure hose.



ALL TERRAIN

EASE OF MOVEMENT.

This is an exclusive feature of IPC: all the models are available in 3 or 4-wheel versions. The machines move easily on any type of floor.

Industrial surface

Rough terrain



BENEFITS

- 01 The 3-wheel version can be perfectly handled on all industrial surfaces.
- 02 The 4-wheel version can be easily used on several types of surfaces, such as concrete, rough terrain and gravel.



MODERN MODULAR BUILD UP

REDUCED MAINTENANCE COSTS.

Whatever the need (maintenance and/or fixing action), the new machines' layout allows the operator to easily access the internal components, by removing the cover.



BENEFITS

- 01 User friendly access to internal components, adjustments and refilling for maintenance and / or fixing operations.
- 02 Pump, valve and motor can be easily reached for easy and fast maintenance and/or fixing operations.
- 03 Sturdy structure, high resistant to thermal shocks, weather conditions, and corrosion from chemicals.



IPC'S EXCLUSIVE BOILER

A LONG WORKING LIFE GUARANTEED BY IPC.

The IPC boilers offer the best heating capacity in any working condition.
The structure and internal components are in stainless steel that ensures a longer lifetime.



- Ignition unit by IPC.
- Removable top cover.
- Stainless steel structure.
- Double stainless steel heating coil.
- Fire-resistant and non-toxic bottom.
- O-rings couplings

BENEFITS

- 01 High-performance combustion.
- 02 Stainless steel external structure designed by IPC.
- 03 Water inlet and outlet at the bottom of the boiler avoiding stagnant water in the heating coils.



IPC
PUMP

RELIABLE AND EFFICIENT.

The exclusive and highly reliable IPC's plunger pump has been tested for more than 2000 working hours, to allow a daily use for more than 8 hours / day.

Reinforced connecting rod
in a special alloy or bronze (depending on the model)

High- and low-pressure water seals
with high durability due to its exclusive IPC design

Brass head
with high mechanical strength
for a long working life

Large oil warning light
to keep the oil level under control.

High-quality long-lasting bearings.

High-efficiency intake valves
stainless steel made

Extra thick and high strength ceramic pistons
highly resistant to wear and thermal shocks.



BENEFITS

- 01 Oversized components to withstand the hardest use.
- 02 Brass head for a long working life.
- 03 The double seals (high and low- pressure) and the intermediate chamber keep the system cool and recirculate the liquid leaked from worn seals too.



M421 ANTI-SCALE

PREVENTS DAMAGE CAUSED BY HARD WATER.

The daily use of the IPC anti-scaling compound reduces maintenance operations on the machine's hydraulic circuit, thus preserving heating performance.

+30%

**MORE EFFICIENT
MORE CONCENTRATED**

**PREVENTS DAMAGES
CAUSED BY HARDWATER**



BENEFITS

- 01** It provides protection from corrosion to components in contact with water.
- 02** It reduces maintenance costs due to overpressure on coil pipes with limescale build-up.
- 03** It prevents limescale from formation inside the hot water pressure washer coil, thus reducing fuel costs caused by heat loss.

AUTOMOTIVE



CAR WASHING

- ▶ DEGREASING AND DEWAXING
- ▶ HEAVY DIRT REMOVAL
- ▶ PRE-WASH OPERATIONS

GARAGES/BODY REPAIR SHOPS AND TYRE CENTRES

- ▶ PARTS CLEANING
- ▶ RIM CLEANING
- ▶ PRE-PAINTING OPERATIONS

CAR-HIRE AGENCIES/CAR DEALERS

- ▶ VEHICLE CLEANING
- ▶ PRE-WASH OPERATIONS
- ▶ SECOND HAND CARS RENOVATION

AGRICULTURE



FARMING

- ▶ ANIMAL PEN CLEANING
- ▶ LIVESTOCK TRUCK CLEANING
- ▶ DAIRY BARN AND LABORATORY CLEANING

VITICULTURE

- ▶ CELLAR FLOOR CLEANING
- ▶ CLEANING OF BOTTLING AND AGEING AREAS
- ▶ WINE SHOP CLEANING

CEREAL FARMING AND STORAGE

- ▶ GRAIN STORAGE SILOS
- ▶ GRAIN TRUCKS CLEANING
- ▶ GRAIN EQUIPMENTS CLEANING

CONSTRUCTION AND BUILDING



RENOVATIONS

- ▶ CONCRETE REMOVAL
- ▶ FACADE CLEANING
- ▶ DEBRIS REMOVAL

BUILDINGS

- ▶ EQUIPMENT CLEANING
- ▶ TRUCK CLEANING
- ▶ STORAGE AREA CLEANING

CONCRETE INDUSTRY

- ▶ EQUIPMENT CLEANING
- ▶ TRUCK CLEANING
- ▶ PARKING AND STORAGE AREA CLEANING

MUNICIPALITIES



ROAD MAINTENANCE

- ▶ TUNNEL CLEANING
- ▶ ROAD SURFACE AND PAVEMENT CLEANING
- ▶ MANHOLE AND STREET DRAIN CLEANING

BUILDING MAINTENANCE

- ▶ FACADE CLEANING
- ▶ GRAFFITI REMOVAL
- ▶ CLEANING OF PUBLIC SPACES AND GREEN AREAS

WASTE COLLECTION

- ▶ REFUSE TRUCK CLEANING
- ▶ LANDFILL SITE CLEANING
- ▶ CLEANING OF WASTE CONTAINERS AND BINS

DIY AND GARDENING



OUTDOOR CLEANING

- ▶ PATIO CLEANING
- ▶ MOSS REMOVAL
- ▶ PIPE AND GUTTER CLEANING

GARDENING

- ▶ CLEANING OF LAWNMOWERS AND TRIMMERS
- ▶ OUTDOOR FURNITURE CLEANING
- ▶ CLEANING OF WALLS, PAVEMENTS AND FENCES

CAR AND EQUIPMENT CARE

- ▶ CAR CLEANING
- ▶ UNDERBODY AND RIM CLEANING
- ▶ DIY TOOL CLEANING

HEAVY INDUSTRY



FOOD FACTORIES

- ▶ CONVEYOR BELT CLEANING
- ▶ SANITIZING FILTERS AND GRILLES
- ▶ CLEANING AND DEGREASING OF WORKBENCHES, WALLS AND CEILINGS

OIL AND GAS COMPANIES

- ▶ REMOVAL OF GREASE AND ENCRUSTATIONS FROM STRUCTURES AND STAIRS
- ▶ TANK AND CONTAINER CLEANING
- ▶ PIPE AND EQUIPMENT CLEANING

HEAVY INDUSTRIES

- ▶ GREASE ENCRUSTATIONS REMOVAL
- ▶ PRE-PAINTED PARTS CLEANING
- ▶ HARD FLOOR CLEANING



COLD WATER

EXCLUSIVE TECHNOLOGIES 30

PW-C09	32
--------	----

PW-C22/PW-C22 P	34
-----------------	----

PW-C23 P	36
----------	----

PW-C21	38
--------	----

PW-C25	40
--------	----

PW-C25 PLUS	42
-------------	----

PW-C40 BY-PASS	44
----------------	----

PW-C40 DELAYED TOTAL STOP	46
---------------------------	----

PW-C40 SPECIAL MODEL	48
----------------------	----

PW-C45 VALUE	50
--------------	----

PW-C45 PREMIUM	52
----------------	----

PW-C45 PAINTED STEEL STRUCTURE	54
--------------------------------	----

PW-C50	56
--------	----

PW-C55 VALUE	58
--------------	----

PW-C55 PREMIUM	60
----------------	----

PW-C55 PAINTED STEEL STRUCTURE	62
--------------------------------	----

PW-C85	64
--------	----

ABSOLUTE-C	66
------------	----

BENZ-C	68
--------	----

DIESEL-C	70
----------	----

FIRE BOX	72
----------	----



IPC

BY TENNANT COMPANY

EXCLUSIVE TECHNOLOGIES

REMOTE CONTROLS

BY-PASS (BYP)

This system activates the machine's water recycling function when the trigger is released

IMMEDIATE TOTAL STOP (ITS)

Instantly stops the machine when the trigger is released

DELAYED TOTAL STOP (DTS)

Stops the machine 30 seconds after its last use

REMOTE CONTROLLED SAFETY STOP (ST)

The Safety Stop remote control stops the machine 3 minutes after the By-pass system has been started. The machine needs to be reset to work again. This system prevents pump gaskets from overheating due to prolonged By-pass system operation.

ENGINE THROTTLE CONTROL (RS)

Reduced engine revolutions when the machine is in By-pass stage. It ensures long life and reduces fuel consumption

SAFETY DEVICES

INTELLIGENT PROPORTIONAL SWITCH OFF (IPSF)

Automatic total stop of the machine after a period of inactivity, which varies according to how long the machine has been used

MICRO LEAKAGE CONTROL (MLC)

The machine stops in case of dangerous leakage in the high-pressure hydraulic circuit

DRY RUNNING PROTECTION (DRP)

Stops the machine in case of lack of water

THERMOSTATIC VALVE (TSV)

In case of prolonged By-pass system operation, this system prevents water from overheating inside the high-pressure pump

LANCE NOZZLE CLOGGED CONTROL (NCC)

Stops the machine when the nozzle is clogged

IGNITION BOILER DELAY (IBD)

Ensures low fume emission levels when the boiler is started

WORKING HOURS COUNTER (WHC)

An electronic hour counter that shows the working hours of the machine

CONTROLS

FLOODING PREVENTION SYSTEM (FPS)

This system stops the machine after 60 minutes of continuous activity

EXCLUSIVE TECHNOLOGIES

PW-C09 PW-C22 PW-C23 PW-C21	PW-C40 (BYP) PW-C50 (BYP)	PW-C25 (ITS)	PW-C45 (VALUE) PW-C55 (VALUE) PW-C45 (PAINTED) PW-C55 (PAINTED)	PW-C40 (DTS) PW-C45 (PREM) PW-C55 (PREM)	PW-C50 (DTS) PW-C85 (DTS)	ABSOLUTE-C	BENZ-C DIESEL-C	FIRE BOX
	•						•	
•		•						
			•	•	•			
						•		
							•	
				•	•			
				•	•			
				•	•	•		
	•					•	•	
				•	•			
								•
				•	•			
				•	•			



IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - COLD WATER

PW-C09

PRESSURE

120 bar

FLOW RATE

380 l/h

ABSORBED POWER

1,8 kW



EXCLUSIVE CHARACTERISTICS

► IMMEDIATE TOTAL STOP - ITS

MOST FREQUENTLY USE

DIY AND GARDENING



SPECS



ACCESSORIES "PRO" WITH METAL QUICK CONNECTION



ACCESSORIES HOLDER




ERGONOMIC HANDLE

TECHNICAL DATA


Code		PW-C09 I1207A M
PERFORMANCE		IDAF94300
Operating pressure	bar/Mpa	120/12
Flow rate	l/h	380
Max inlet water temperature	°C	50
Power supply	Ph-V-Hz/A	1-230-50/8,2
Absorbed power	kW	1,8
Motor pole/rpm		universal
Remote control		ITS
Pump/head/pistons		Axial/aluminium/inox
Detergent tank	l	foamer (0,5l)
Detergent delivery		low pressure
Dimension (LxWxH)	cm	25,5x25x78
Weight	kg	10

STANDARD EQUIPMENT


CODE: IPPR40021
HANDGRIP 1/4M
-BAYONET




CODE: LCPR40124
LANCE F-BAYONET D. 0,97




CODE: LCPR40129
TURBO LANCE
F-BAYOPNET D.1,15 (0)




CODE: TBAP40179
HIGH PRESSURE HOSE 6 m



CODE: KTRI40331
FOAMER 0,5 l



CODE: KTRI40330
FIXED BRUSH



OPTIONAL ACCESSORIES (BLISTER PACKAGING)

CODE: KTRI40329
ROTATING WATER BRUSH
(BLISTER)



CODE: KTRI40330
FIXED WATER BRUSH
(BLISTER)



CODE: KTRI40331
FOAMER 0,5 l (BLISTER)



CODE: KTRI40325
SURFACE CLEANING
(BLISTER)



CODE: KTRI40324
FLOOR CLEANING
(BLISTER)



CODE: KTRI40327
PIPE CLEANING SET
(BLISTER)



CODE: KTRI40328
SANDBLASTING SET
(BLISTER)





IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - COLD WATER

PW-C22/PW-C22 P

PRESSURE

120÷160

bar

FLOW RATE

380÷540

l/h

ABSORBED POWER

1,6÷3

kW



PW-C22



PW-C22P

EXCLUSIVE CHARACTERISTICS

► IMMEDIATE TOTAL STOP - ITS

MOST FREQUENTLY USE

DIY AND GARDENING



SPECS



ALL ACCESSORIES AND POWER CORD CAN BE STORED ON THE UNIT



4 LITRES DETERGENT TANK FOR A LOW-PRESSURE DETERGENT DELIVERY



ERGONOMIC HANDLE

TECHNICAL DATA

Code	WITHOUT HOSE REEL		NEW 3000W		
	PW-C22 I1207A M		PW-C22P I1307A M	PW-C22P I1508A M	PW-C22P I1609AO M
	IDAF94301		IDAF94303	IDAF94304	IDAF94339
PERFORMANCE					
Operating pressure	bar/Mpa	120/12	130/13	150/15	160/16
Flow rate	l/h	380	420	500	540
Max inlet water temperature	°C	50	50	50	50
Power supply	Ph-V-Hz/A	1-230-50/9	1-230-50/9	1-230-50/11	1-230-50/11,2
Absorbed power	kW	1,6	2	2,5	3
Motor pole/rpm		2-2800	2-2800	2-2800	2-2800
Remote control		ITS	ITS	ITS	ITS
Pump/head/pistons		Axial/aluminium/inox	Axial/aluminium/inox	Axial/aluminium/inox	Axial/brass/inox
Detergent tank	l	4	4	4	4
Detergent delivery		low pressure	low pressure	low pressure	low pressure
Dimension (LxWxH)	cm	34,5x29,5x78	34,5x33x86,5	34,5x33x86,5	34,5x33x86,5
Weight	kg	18	21	20	25

STANDARD EQUIPMENT

CODE: IPPR40019
HANDGRIP 1/4M M22



CODE: LCPR40120
LANCE M22 D. 0,95
(FOR 1207)



CODE: LCPR40121
LANCE M22 D. 0,90
(FOR 1307)



CODE: LCPR40116
LANCE M22 D. 0,91
(FOR 1508)



CODE: LCPR40146
LANCE M22 D. 1,00
(FOR 1609)



CODE: LCPR40125
TURBO LANCE D.1,15(0)
(FOR 1207)



CODE: LCPR40126
TURBO LANCE D.1,15(1)
(FOR 1307)



CODE: LCPR40117
TURBO LANCE D.1,15(2)
(FOR 1508)



CODE: LCPR40147
TURBO LANCE D.1,30(0)
(FOR 1609)



CODE: TBAP40180
HIGH PRESSURE HOSE 6 m
(FOR 1207)



CODE: TBAP40182
HIGH PRESSURE HOSE 8 m
(FOR 1307)



CODE: TBAP40171
HIGH PRESSURE HOSE 8 m
(FOR 1508/1609)



OPTIONAL ACCESSORIES (BLISTER PACKAGING)

CODE: KTRI40329
ROTATING WATER BRUSH
(BLISTER)



CODE: KTRI40330
FIXED WATER BRUSH
(BLISTER)



CODE: KTRI40331
FOAMER 0,5 l (BLISTER)



CODE: KTRI40325
SURFACE CLEANING
(BLISTER)



CODE: KTRI40324
FLOOR CLEANING
(BLISTER)



CODE: KTRI40327
PIPE CLEANING SET
(BLISTER)



CODE: KTRI40328
SANDBLASTING SET
(BLISTER)



CODE: KTRI40543
MAINTENANCE KIT
(FOR 1207)



CODE: KTRI40544
MAINTENANCE KIT
(FOR 1307)



CODE: KTRI40545
MAINTENANCE KIT
(FOR 1508)



CODE: KTRI40546
MAINTENANCE KIT
(FOR 1609)





IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - COLD WATER

PW-C23 P

PRESSURE

140÷160
bar

FLOW RATE

460÷600
l/h

ABSORBED POWER

2,3÷3
kW



EXCLUSIVE CHARACTERISTICS

► IMMEDIATE TOTAL STOP - ITS

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



DIY AND GARDENING



SPECS



ROBUST AND ERGONOMIC
HANDLE



PROFESSIONAL HOSE REEL



PROFESSIONAL GAUGE
(only for I1508 A0-M - I1610 A0-M)

TECHNICAL DATA

		WITH HOSE REEL			
		PW-C23P I1408A M IDAF94223	PW-C23P I1610A M IDAF94227	PW-C23P I1508AO M IDAF94229	PW-C23P I1610AO M IDAF94231
Code					
PERFORMANCE					
Operating pressure	bar/Mpa	140/14	160/16	150/15	160/16
Flow rate	l/h	460	600	500	600
Max inlet watertemperature	°C	50	50	50	50
Power supply	Ph-V-Hz/A	1-230-50/10,9	1-230-50/11,5	1-230-50/14,2	1-230-50/14,2
Absorbed power	kW	2,3	2,5	3	3
Motor pole/rpm		2-2800	2-2800	2-2800	2-2800
Remote control		ITS	ITS	ITS	ITS
Pump/head/pistons		axial/aluminium/inox	axial/aluminium/inox	axial/brass/inox	axial/brass/inox
Detergent tank	l	2 x 0,6 l	2 x 0,6 l	2 x 0,6 l	2 x 0,6 l
Detergent delivery		low pressure	low pressure	low pressure	low pressure
Dimension (LxWxH)	cm	38x33x84	38x33x84	38x33x84	38x33x84
Weight	kg	20,5	23,5	24	25

STANDARD EQUIPMENT

CODE: IPPR40012
HANDGRIP P270 + M22



CODE: LCPR40075
LANCE P350 + M22 D.1,08 (FOR 1408)



CODE: LCPR40076
LANCE P440 + M22 D.1,03NE (FOR 1508)



CODE: LCPR40074
LANCE P440 + M22 D.1,07GR (FOR 1610)



CODE: LCPR40078
TURBO LANCE P440 + M22 D.1.2B (FOR 1408)



CODE: LCPR40080
TURBO LANCE P440 + M22 D.1.03NE (FOR 1508)



CODE: LCPR40079
TURBO LANCE P440 + M22 D.1.07GRI (FOR 1610)



CODE: TBAP40108
HIGH PRESSURE HOSE 12 m



OPTIONAL ACCESSORIES

CODE: SPID40010
FIXED BRUSH + M22



CODE: SPID40011
ROTOBRUSH + M22



CODE: LCLC40010
LANCE FOR WASHING FLOORS + M22



CODE: TBAP40111
DRAIN KIT 8 m



CODE: TBAP40112
HOSE EXTENSION 8 m



CODE: KTRI29366
PLUNGER EJECTOR DEVICE



CODE: KTRI40239
SANDBLASTER KIT



CODE: LCPR29360
MUDGUARD LANCE





IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - COLD WATER

PW-C21

PRESSURE

130÷160
bar

FLOW RATE

480÷600
l/h

ABSORBED POWER

2,5÷3
kW



EXCLUSIVE CHARACTERISTICS

- IMMEDIATE TOTAL STOP - ITS

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



DIY AND GARDENING



SPECS



PLUNGER PUMP WITH BRASS
HEAD AND CERAMIC PISTONS



ADJUSTABLE PRESSURE



PROFESSIONAL
PRESSURE GAUGE

TECHNICAL DATA

		PW-C21 I1310P M	PW-C21 I1508P M	PW-C21 I1609P M
Code		IDAF94361	IDAF94359	IDAF94360
PERFORMANCE				
Operating pressure	bar/Mpa	130/13	150/15	160/16
Flow rate	l/h	600	480	540
Max inlet water temperature	°C	50	50	50
Power supply	Ph-V-Hz/A	1-230-50	1-230-50	1-230-50
Absorbed power	kW	2,9	2,5	2,9
Motor pole/rpm		2-2800	2-2800	2-2800
Remote control		ITS	ITS	ITS
Pump/head/pistons		plunger/brass/ceramic	plunger/brass/ceramic	plunger/brass/ceramic
Detergent tank	l	-	-	-
Deterget delivery		low pressure	low pressure	low pressure
Dimension (LxWxH)	cm	46x28x26	46x28x26	46x28x26
Weight	kg	18,4	16,8	18,4

STANDARD EQUIPMENT

CODE: IPIP40009
HANDGRIP 1/4 M M22



CODE: LCPR40162
LANCE P400 M22 1,21BI
(FOR 1310)



CODE: LCPR40152
LANCE P400 M22 1,05NE
(FOR 1508)



CODE: LCPR40154
LANCE P400 M22 1,00RS
(FOR 1609)



CODE: TBAP40210
HIGH PRESSURE HOSE
1/4 8 m



OPTIONAL ACCESSORIES

CODE: KTRI40417
TROLLEY KIT



CODE: KTRI40419
HOSE REEL KIT FOR
TROLLEY



CODE: KTRI40418
WALL SUPPORT KIT + HOSE
REEL (WITHOUT HOSE)



CODE: KTRI40443
WALL SUPPORT KIT +
HOSE REEL + HOSE 15 m



CODE: LCPR40151
TURBO LANCE TPR-20 +
M22 D.1,30 (FOR 1310)



CODE: LCPR40150
TURBO LANCE TTR-16 +
M22 D.1,25 (FOR 1508)



CODE: LCPR40155
TURBO LANCE TTR-16 +
M22 D.1,15 (FOR 1609)





IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - COLD WATER

PW-C25

IMMEDIATE TOTAL STOP MODELS

PRESSURE

150÷180
bar

FLOW RATE

540÷800
l/h

ABSORBED POWER

2,7÷4,7
kW



EXCLUSIVE CHARACTERISTICS

► IMMEDIATE TOTAL STOP - ITS

WITHOUT HOSE REEL

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



DIY AND GARDENING



HEAVY INDUSTRY



INNOVATIONS



G6000™
CERAMIC
HIGH-TECH GUN



IPC
PUMP

SPECS



DESIGNED FOR AN EASY AND RAPID MAINTENANCE



STANDARD SUPPORTS FOR ACCESSORIES TO HAVE THEM READY TO BE USED



LANCE SUPPORT

TECHNICAL DATA

		PW-C25 I1509P M	PW-C25 I813P T
Code		IDAF94166	IDAF94169
PERFORMANCE			
Operating pressure	bar/Mpa	30-150/3-15	30-180/3-18
Flow rate	l/h	540	800
Max inlet water temperature	°C	50	50
Power supply	Ph-V-Hz/A	1-230-50/12	3-400-50/8,6
Absorbed power	kW	2,8	4,7
Motor pole/rpm		2-2800	2-2800
Remote control		ITS	ITS
Pump/head/pistons		IPC plunger/brass/ceramic	IPC plunger/brass/ceramic
Detergent tank	l	3	3
Detergent delivery		low pressure	low pressure
Dimension (LxWxH)	cm	49x40x93	49x40x93
Weight	kg	30	35

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000 +
EXTENSION P330+M22



CODE: LCPR40057
EXTENSION P580
Ø 1,20GL (FOR 1509)



CODE: LCPR40046
EXTENSION P580 Ø
1,50AZZ (FOR 1813)



CODE: TBAP28305
HIGH PRESSURE HOSE 8 m



OPTIONAL ACCESSORIES

CODE: LCPR29360
MUDGUARD LANCE P90



CODE: TBAP23853
DRAIN KIT 10 m



CODE: LCLC49492
LANCE FOR WASHING
FLOORS (FOR 1509)




CODE: LCLC49493
LANCE FOR WASHING
FLOORS (FOR 1813)




CODE: LCPR40040
FOAMER KIT



CODE: LCPR14858
SANDBLASTER KIT Ø 1,4
(FOR 1813)



CODE: LCPR24943
SANDBLASTER KIT Ø 1,3
(FOR 1509)



CODE: PRCH40041
SAND BAG 25 Kg



CODE: SPID24939
FIXED HYDROBRUSH
LANCE



CODE: LCPR93177
TURBO LANCE TTR-16 M22
1,30 - (FOR 1509/1813)



CODE: KTRI40318
MAINTENANCE KIT 500H
(FOR 1509/1813)



CODE: KTRI40478
KIT FOR HOT WATER
FEEDING VERSION
(FOR 1509/1813)





IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - COLD WATER

PW-C25 PLUS

IMMEDIATE TOTAL STOP MODELS

PRESSURE

130÷180
bar

FLOW RATE

540÷800
l/h

ABSORBED POWER

2,7÷4,7
kW



EXCLUSIVE CHARACTERISTICS

► IMMEDIATE TOTAL STOP - ITS

WITH HOSE REEL

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



DIY AND GARDENING



HEAVY INDUSTRY



INNOVATIONS



G6000™
CERAMIC
HIGH-TECH GUN



IPC
PUMP

SPECS



SOLID STRUCTURE:
RESISTANT TO SHOCKS,
ATMOSPHERIC AGENTS AND
CHEMICAL CORROSION



IPC PUMP WITH SEPARATE
BY-PASS, AND ADJUSTABLE
PRESSURE



PROFESSIONAL HOSE REEL

TECHNICAL DATA

		PW-C25P I1310P4 M IDAF94187	PW-C25P I1509P M IDAF94170	PW-C25P I1813P T IDAF94174
Code				
PERFORMANCE				
Operating pressure	bar/Mpa	30-130/3-13	30-150/3-15	30-180/3-18
Flow rate	l/h	600	540	800
Max inlet water temperature	°C	50	50	50
Power supply	Ph-V-Hz/A	1-230-50/13,3	1-230-50/12	3-400-50/8,6
Absorbed power	kW	2,7	2,8	4,7
Motor pole/rpm		4-1400	2-2800	2-2800
Remote control		ITS	ITS	ITS
Pump/head/pistons		IPC plunger/brass/ceramic	IPC plunger/brass/ceramic	IPC plunger/brass/ceramic
Detergent tank	l	3	3	3
Detergent delivery		low pressure	low pressure	low pressure
Dimension (LxWxH)	cm	49x40x93	49x40x93	49x40x93
Weight	kg	35	32,4	37,8

STANDARD EQUIPMENT

CODE: IPPR40025
**HANDGRIP G6000 +
EXTENSION P330+M22**



CODE: LCPR40049
**EXTENSION P580
Ø 1,40BEI (FOR 1310)**



CODE: LCPR40057
**EXTENSION P580
Ø 1,20GL (FOR 1509)**



CODE: LCPR40046
**EXTENSION P580
Ø 1,50AZZ (FOR 1813)**



CODE: LCPR40016
**TURBO LANCE TTR-16 M22
1,40 (FOR 1310)**



CODE: LCPR93177
**TURBO LANCE TTR-16 M22
1,30 (FOR 1509 /1813)**



CODE: TBAP93827
HIGH PRESSURE HOSE 12 m



OPTIONAL ACCESSORIES

CODE: LCPR29360
MUDGUARD LANCE P90



CODE: TBAP23853
DRAIN KIT 10 m



CODE: LCLC49492
**LANCE FOR WASHING
FLOORS (FOR 1509)**



CODE: LCLC49493
**LANCE FOR WASHING
FLOORS (FOR 1310/1813)**



CODE: LCPR40040
FOAMER KIT



CODE: LCPR14858
**SANDBLASTER KIT
Ø 1,4 mm (FOR 1310/1813)**



CODE: LCPR24943
**SANDBLASTER KIT
Ø 1,3 mm (FOR 1509)**



CODE: PRCH40041
SAND BAG 25 Kg



CODE: SPID24939
**FIXED HYDROBRUSH
LANCE**



CODE: KTRI40312
**MAINTENANCE KIT 500H -
(FOR 1310)**



CODE: KTRI40318
**MAINTENANCE KIT 500H
(FOR 1509/1813)**



CODE: KTRI40479
**KIT FOR HOT WATER
FEEDING VERSION
(FOR 1310)**



CODE: KTRI40478
**KIT FOR HOT WATER
FEEDING VERSION
(FOR 1509/1813)**





IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - COLD WATER

PW-C40 BY-PASS

PRESSURE

130÷190
bar

FLOW RATE

600÷900
l/h

ABSORBED POWER

3÷5,1
kW



EXCLUSIVE CHARACTERISTICS

- BY-PASS - BYP
- THERMOSTATIC VALVE - TSV

WITHOUT HOSE REEL

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



DIY AND GARDENING



HEAVY INDUSTRY



INNOVATIONS



G6000™
CERAMIC
HIGH-TECH GUN



IPC
PUMP

SPECS



7,5 LITRES DETERGENT
TANK FOR A LOW-PRESSURE
DETERGENT DELIVERY



LARGE DIAMETER WHEELS
IN ORDER TO FACILITATE
MOVEMENTS



THERMOSTATIC VALVE TO
PROTECTING THE PUMP
FROM HIGH TEMPERATURES
IN BY-PASS PHASE

TECHNICAL DATA

		BY-PASS MODELS - 2 POLES	BY-PASS MODELS - 4 POLES
		PW-C40 1813P T	PW-C40 1310P4 M
		IDAF40237	IDAF40245
Code			
PERFORMANCE			
Operating pressure	bar/Mpa	30-180/3-18	30-130/3-13
Flow rate	l/h	800	600
Max inlet water temperature	°C	50	50
Power supply	Ph-V-Hz/A	3-400-50/8,6	1-230-50/14,5
Absorbed power	kW	4,7	3,1
Motor pole/rpm		2-2800	4-1400
Remote control		BYP	BYP
Pump/head/pistons		IPC plunger/brass/ceramic	IPC plunger/brass/ceramic
Detergent tank	l	7,5	7,5
Detergent delivery		low pressure	low pressure
Dimension (LxWxH)	cm	74x43x81	74x43x81
Weight	kg	44	47

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000 +
EXTENSION P330+M22



CODE: LCPR40046
EXTENSION P580 Ø
1,50AZZ - (FOR 1813)



CODE: LCPR40048
EXTENSION P580 Ø
1,35BLU - (FOR 1310)



CODE: TBAP40256
HIGH PRESSURE HOSE 10 m



OPTIONAL ACCESSORIES

CODE: LCPR29360
MUDGUARD LANCE P90



CODE: RCIN10810
HOSE COUPLINGS



CODE: TBAP23853
DRAIN KIT 10 m



CODE: LCLC49492
LANCE FOR WASHING
FLOORS 0,35
(FOR 1310/1813)



CODE: LCPR13557
SANDBLASTER KIT Ø 1,6 -
(FOR 1813)



CODE: LCPR14858
SANDBLASTER KIT Ø 1,4 -
(FOR 1310)



CODE: PRCH40041
SAND BAG 25 Kg



CODE: LCPR93178
TURBO LANCE TTR-16 M22
1,35 (FOR 1310)



CODE: LCPR40016
TURBO LANCE TTR-16 M22
1,40 - (FOR 1813)



CODE: KTRI40319
MAINTENANCE KIT 500H -
(FOR 1813)



CODE: KTRI40311
MAINTENANCE KIT 500H -
(FOR 1310)



CODE: KTRI40479
KIT FOR HOT WATER
FEEDING VERSION -
(FOR 1310)



CODE: KTRI40478
KIT FOR HOT WATER
FEEDING VERSION -
(FOR 1813)





IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - COLD WATER

PW-C40 DELAYED TOTAL STOP

PRESSURE

130÷190
bar

FLOW RATE

600÷900
l/h

ABSORBED POWER

3÷5,1
kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT PROPORTIONAL SWITCHING OFF - IPSF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ NOZZLE CLOGGED CONTROL - NCC
- ▶ WORKING HOURS COUNTER - WHC
- ▶ FLOODING PREVENTION SYSTEM - FPS
- ▶ DRY RUNNING PROTECTION - DRP (ONLY THREE PHASE MODELS WITH DELAYED TOTAL STOP)



WITHOUT HOSE REEL

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



DIY AND GARDENING



HEAVY INDUSTRY



INNOVATIONS



G6000™
CERAMIC
HIGH-TECH GUN



MSC™
MULTIFUNCTION
SAFETY
CONTROL



IPC
PUMP

SPECS



PRESSURE ADJUSTMENT
KNOB



LARGE FRONT FOOT FOR
GREATER STABILITY



ERGONOMIC HANDLE,
LANCE HOLDER AND HOSE
SUPPORTS

TECHNICAL DATA

DELAYED TOTAL STOP MODELS - 4 POLES

		PW-C40 D1310P4 M	PW-C40 D1915P4 T
Code		IDAF40246	IDAF40254
PERFORMANCE			
Operating pressure	bar/Mpa	30-130/3-13	30-190/3-19
Flow rate	l/h	600	900
Max inlet water temperature	°C	50	50
Power supply	Ph-V-Hz/A	1-230-50/14,5	3-400-50/9,4
Absorbed power	kW	3,1	5,1
Motor pole/rpm		4-1400	4-1400
Remote control		DTS	DTS
Pump/head/pistons		IPC plunger/brass/ceramic	IPC plunger/brass/ceramic
Detergent tank	l	7,5	7,5
Detergent delivery		low pressure	low pressure
Dimension (LxWxH)	cm	74x43x81	74x43x81
Weight	kg	47	52

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000 +
EXTENSION P330+M22



CODE: LCPR40048
EXTENSION P580 Ø
1,35BLU - (FOR 1310)



CODE: LCPR40047
EXTENSION P580 Ø
1,45GLO - (FOR 1915P4)



CODE: TBAP40256
HIGH PRESSURE HOSE
MT 10



OPTIONAL ACCESSORIES

CODE: LCPR29360
MUDGUARD LANCE P90



CODE: RCIN10810
HOSE COUPLINGS



CODE: TBAP23853
DRAIN KIT 10 m



CODE: LCLC49492
LANCE FOR WASHING
FLOORS 0,35 (FOR 1310)



CODE: LCLC49493
LANCE FOR WASHING
FLOORS 0,45 (FOR 1915)



CODE: LCPR13557
SANDBLASTER KIT Ø 1,6 -
(FOR 1915)



CODE: LCPR14858
SANDBLASTER KIT Ø 1,4 -
(FOR 1310)



CODE: PRCH40041
SAND BAG 25 Kg



CODE: LCPR93178
TURBO LANCE TTR-16 M22
1,35



CODE: KTRI40311
MAINTENANCE KIT 500H -
(FOR 1310)



CODE: KTRI40313
MAINTENANCE KIT 500H -
(FOR 1915)



CODE: KTRI40479
KIT FOR HOT WATER
FEEDING VERSION -
(FOR 1310P4/1915P4)





IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - COLD WATER

PW-C40 SPECIAL MODEL

PRESSURE

100 bar

FLOW RATE

300 l/h

ABSORBED POWER

1,3 kW



HIGHPURE - HPE
CODE: APTA40015

TECNOLOGIE ESCLUSIVE

- ▶ DELAYED TOTAL STOP - DTS
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ LANCE NOZZLE CLOGGED CONTROL - NCC
- ▶ WORKING HOURS COUNTER - WHC
- ▶ FLOODING PREVENTION SYSTEM - FPS

**TO BE USED ONLY IN COMBINATION
WITH APTA40015 -
HIGHPURE HPE
(SEE IMAGE ON THE RIGHT)**

MOST FREQUENTLY USE

CONSTRUCTION INDUSTRY



GREEN ENERGIES



NAUTICAL/AUTO/TRANSPORTS



GREENHOUSES/GLASSHOUSES/
TENSILE STRUCTURES



INNOVATIONS



G6000™
CERAMIC
HIGH-TECH GUN



MSC™
MULTIFUNCTION
SAFETY
CONTROL



IPC
PUMP

SPECS



IPC PUMP WITH SEPARATE
BY-PASS, PROVIDED WITH
PRESSURE ADJUSTMENT
KNOB



PROFESSIONAL HOSE REEL







INTEGRATED ERGONOMIC
HANDLE, LANCE HOLDER

TECHNICAL DATA

Code		PW-C40 D1005P4 M
PERFORMANCE		IDAF40884
Operating pressure max	bar/Mpa	100/10
Flow rate	l/h	300
Inlet water max. temperature	°C	50
Power supply	Ph-V-Hz/A	1-230-50/8,6
Absorbed power	kW	1,3
Motor pole/rpm		4-1400
Remote control		DTS
Pump/head/pistons		lpc plunger/brass/ceramic
Detergent tank	l	7,5
Detergent delivery		low pressure
Dimension (LxWxH)	cm	74x43x81
Weight	kg	47

STANDARD EQUIPMENT

CODE: IPPR40025 HANDGRIP G6000 + EXTENSION P330+M22	CODE: LCPR40013 EXTENSION P70 HY.JET	CODE: UGLN40038 H.P. NOZZLE 1/4 1502	CODE: TBAP40012 H.P. HOSE 1/4" 10 m
			

OPTIONAL ACCESSORIES

CODE: LCPR29360 MUDGUARD LANCE P90	CODE: RCIN10810 HOSE COUPLINGS	CODE: TBAP23853 DRAIN KIT 10 m	CODE: SPID24939 FIXED HYDROBRUSH LANCE	CODE: KTRI40478 KIT FOR HOT WATER FEEDING VERSION
				



IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - COLD WATER

PW-C45 VALUE

PRESSURE

110÷190
bar

FLOW RATE

500÷900
l/h

ABSORBED POWER

2,9÷4,9
kW



EXCLUSIVE CHARACTERISTICS

► DELAYED TOTAL STOP - DTS

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



DIY AND GARDENING



HEAVY INDUSTRY



INNOVATION



G6000™
CERAMIC
HIGH-TECH GUN



IPC
PUMP



MSC™
MULTIFUNCTION
SAFETY
CONTROL

SPECS



COLLAPSIBLE HANDLE FOR
COMPACT STORAGE AND EASY
TRANSPORT



NEW STORAGE SPACE FOR ALL
EQUIPMENT AND ACCESSORIES



REMOVABLE COVER, AND EASY OIL
FILL-EMPTY SYSTEM FOR A RAPID
MAINTENANCE

TECHNICAL DATA

		PW-C45 D1112P4M	PW-C45 D1310P4M	PW-C45 D1708P4M	PW-C45 D1813P T	PW-C45 D1814P4 T	PW-C45 D1915P4 T
CODE		IDAF40901	IDAF40902	IDAF40903	IDAF40904	IDAF40905	IDAF40906
PERFORMANCE							
Operating pressure	bar/Mpa	30-110/3-11	30-130/3-13	30-170/3-17	30-180/3-18	30-180/3-18	30-190/3-19
Flow rate	l/h	300-720	300-600	400-500	450-800	450-840	450-900
Max inlet water temperature	°C	50	50	50	50	50	50
Power supply	Ph-V-Hz/A	1-230-50/14,5	1-230-50/14,1	1-230-50/14,5	3-400-50/9,3	3-400-50/9,6	3-400-50/10,3
Absorbed power	kW	3	2,9	3	4,9	4,6	4,9
Motor pole/rpm		4-1400	4-1400	4-1400	2-2800	4-1400	4-1400
Remote control		DTS	DTS	DTS	DTS	DTS	DTS
Pump/head/pistons		lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic
Detergent tank	l	-	-	-	-	-	-
Detergent delivery		low pressure	low pressure	low pressure	low pressure	low pressure	low pressure
Dimension (LxWxH)	cm	67x42x95	67x42x95	67x42x95	67x42x95	67x42x95	67x42x95
Weight	kg	40,2	40,1	40,2	42,2	44	47,3

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000 +
EXTENSION P330+M22



CODE: LCPR40087
EXTENSION P70 - INOX



CODE: UGLN05200
H.P. NOZZLE 1/4 1505
(FOR 1112P4)



CODE: UGLN11196
H.P. NOZZLE 1/4 15035
(FOR 1310P4)



CODE: UGLN75421
H.P. NOZZLE 1/4 15025
(FOR 1708P4)



CODE: UGLN49987
H.P. NOZZLE LANCE
1/4 15045 - (FOR
1813P/1814P4/1915P4)



CODE: TBAP40229
H.P. HOSE 1/4" 10 m



OPTIONAL ACCESSORIES

CODE: KTRI40505
HOSE REEL KIT (WITHOUT
HOSE)



CODE: KTRI40506
HOSE REEL KIT (WITH 20 m
HOSE)



CODE: LCPR29360
MUDGUARD LANCE P90



CODE: RCIN10810
HOSE COUPLINGS M22



CODE: TBAP23853
DRAIN KIT 10 m - M22



CODE: LCLC49492
LANCE FOR WASHING
FLOORS 0,35 (FOR
1310P4/1708P4)



CODE: LCPR24943
SANDBLASTER KIT Ø 1,3 mm
(FOR 1310P4/1708P4)



CODE: PRCH40041
SAND BAG 25 Kg



CODE: SPID24939
FIXED HYDROBRUSH
LANCE



CODE: LCPR93178
TURBO LANCE TTR-16 +
M22 Ø1,35
(FOR 1310P4)



CODE: LCPR40011
TURBO LANCE
TTR-16 + M22 Ø 1,15
(FOR 1708P4)



CODE: LCPR40014
TURBO LANCE TPR-20 +
M22 Ø1,30
(FOR 1813P/1814P4)



CODE: KTRI40588
MAINTENANCE KIT 500H
(FOR 1814P4/1915P4)



CODE: KTRI40478
KIT FOR HOT WATER
FEEDING VERSION -
(FOR 1813P)



CODE: KTRI40479
KIT FOR HOT WATER FEEDING
VERSION (FOR 1112P4/1310P4
/1708P4/1814P4/1915P4)



ACCESSORIES TO DELIVERY CHEMICAL PRODUCT

OPTION [1]

OPTION [2]

CODE: LCPR40040
FOAMER KIT 1 I



CODE: KTRI40527
EJECTOR KIT + P70 HYJET



CODE: LCLC49493
LANCE FOR WASHING
FLOORS 0,45 (FOR 1112P4/
1813P/1814P4/1915P4)



CODE: LCPR14859
SANDBLASTERKIT Ø1,5mm
(FOR 1112P4/1813P/1814P4
/1915P4)



CODE: KTRI00038
INJECTOR KIT



CODE: LCPR40053
TURBO LANCE TPR-20
+ M22 Ø1,50 -
(FOR 1112P4/1915P4)



CODE: KTRI40587
MAINTENANCE KIT 500H
(FOR 1813P)



CODE: KTRI40586
MAINTENANCE KIT 500H
(FOR 1112P4/1310P4/
1708P4)





IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - COLD WATER

PW-C45 PREMIUM

PRESSURE

130÷190
bar

FLOW RATE

500÷900
l/h

ABSORBED POWER

2,9÷4,9
kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT PROPORTIONAL SWITCHING OFF - IPSF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ NOZZLE CLOGGED CONTROL - NCC
- ▶ WORKING HOURS COUNTER - WHC
- ▶ FLOODING PREVENTION SYSTEM - FPS
- ▶ MAINTENANCE CHECK LED
- ▶ WARNING LEDS
- ▶ DRY RUNNING PROTECTION - DRP



MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



DIY AND GARDENING



HEAVY INDUSTRY



INNOVATION



G6000™
CERAMIC
HIGH-TECH GUN



IPC
PUMP



MSC™
MULTIFUNCTION
SAFETY
CONTROL

SPECS



COLLAPSIBLE HANDLE FOR
COMPACT STORAGE AND EASY
TRANSPORT



NEW STORAGE SPACE FOR ALL
EQUIPMENT AND ACCESSORIES



REMOVABLE COVER, AND EASY OIL
FILL-EMPTY SYSTEM FOR A RAPID
MAINTENANCE

TECHNICAL DATA

		PW-C45 DP 1310P4 M	PW-C45 DP 1708P4 M	PW-C45 DP 1814P4 T	PW-C45 DP 1915P4 T
CODE		IDAF40913	IDAF40914	IDAF40916	IDAF40917
PERFORMANCE					
Operating pressure	bar/Mpa	30-130/3-13	30-170/3-17	30-180/3-18	30-190/3-19
Flow rate	l/h	300-600	400-500	450-840	450-900
Max inlet water temperature	°C	50	50	50	50
Power supply	Ph-V-Hz/A	1-230-50/14,1	1-230-50/14,5	3-400-50/9,6	3-400-50/10,3
Absorbed power	kW	2,9	3	4,6	4,9
Motor pole/rpm		4-1400	4-1400	4-1400	4-1400
Remote control		DTS	DTS	DTS	DTS
Pump/head/pistons		lpc plunger/brass/ceramic	lpc plunger/brass/ceramic	lpc plunger/brass/ceramic	lpc plunger/brass/ceramic
Detergent tank	l	-	-	-	-
Detergent delivery		low pressure	low pressure	low pressure	low pressure
Dimension (LxWxH)	cm	67x42x95	67x42x95	67x42x95	67x42x95
Weight	kg	40,1	40,2	44	47,3

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000 +
EXTENSION P330+M22



CODE: TBAP40229
H.P. HOSE 1/4" 10 m



CODE: LCPR40087
EXTENSION P70 - INOX



CODE: UGLN11196
H.P. NOZZLE 1/4 15035
(FOR 1310P4)



CODE: UGLN75421
H.P. NOZZLE 1/4 15025
(FOR 1708P4)



CODE: UGLN49987
H.P. NOZZLE 1/4 15045 -
(FOR 1814P4/1915P4)



OPTIONAL ACCESSORIES

CODE: KTRI40505
HOSE REEL KIT
(WITHOUT HOSE)



CODE: KTRI40506
HOSE REEL KIT
(WITH 20 m HOSE)



CODE: LCPR29360
MUDGUARD LANCE P90



CODE: RCIN10810
HOSE COUPLINGS M22



CODE: TBAP23853
DRAIN KIT 10 m - M22



CODE: LCLC49492
LANCE FOR WASHING
FLOORS 0,35
(FOR 1310P4/1708P4)



CODE: LCPR24943
SANDBLASTER KIT Ø 1,3 mm
(FOR 1310P4/1708P4)



CODE: PRCH40041
SAND BAG 25 Kg



CODE: SPID24939
FIXED HYDROBRUSH
LANCE



CODE: LCPR93178
TURBO LANCE TTR-16 +
M22 Ø1,35 (FOR 1310P4)



CODE: LCPR40011
TURBO LANCE TTR-16 +
M22 Ø 1,30 (FOR 1708P4)



CODE: LCPR40014
TURBO LANCE TPR-20 +
M22 Ø1,30 (FOR 1814P4)



CODE: KTRI40479
KIT FOR HOT WATER
FEEDING VERSION



ACCESSORIES TO DELIVERY CHEMICAL PRODUCT

OPTION [1]

OPTION [2]

CODE: LCPR40040
FOAMER KIT 1 I



CODE: KTRI40527
EJECTOR KIT + P70 HYJET



CODE: LCLC49493
LANCE FOR WASHING
FLOORS 0,45 - (FOR
1814P4/1915P4)



CODE: LCPR14859
SANDBLASTER KIT Ø 1,5 -
(FOR 1814P4/1915P4)



CODE: KTRI00038
INJECTOR KIT



CODE: LCPR40053
TURBO LANCE TPR-20 +
M22 Ø1,50 - (FOR 1915P4)



CODE: KTRI40586
MAINTENANCE KIT 500H
(FOR 1310P4/ 1708P4)



CODE: KTRI40588
MAINTENANCE KIT 500H
(FOR 1814P4/1915P4)





IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - COLD WATER

PW-C45

PAINTED STEEL STRUCTURE

PRESSURE

130÷190
bar

FLOW RATE

600÷900
l/h

ABSORBED POWER

2,8÷4,9
kW



EXCLUSIVE CHARACTERISTICS

► DELAYED TOTAL STOP - DTS

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



DIY AND GARDENING



HEAVY INDUSTRY



INNOVATION



G6000™
CERAMIC
HIGH-TECH GUN



IPC
PUMP



MSC™
MULTIFUNCTION
SAFETY
CONTROL

SPECS



IPC PLUNGER PUMP WITH BRASS
HEAD AND CERAMIC PISTONS.



HEAVY-DUTY STRUCTURE, ANTI
COLLISION, STEEL FRAME COVER.



LARGE WHEELS IMPROVE
MANEUVERABILITY AND EASE
TRANSPORT.

TECHNICAL DATA

		PW-C45 D1310P4m M	PW-C45 D1915P4m T
CODE		IDAF41104	IDAF41105
PERFORMANCE			
Operating pressure max	bar/Mpa	40-130/4-13	40-190/4-19
Flow rate	l/h	300-600	360-900
Inlet water max. temperature	°C	50	50
Power supply	Ph-V-Hz/A	1-230-50/13,4	3-400-50/10,2
Absorbed power	kW	2,8	4,9
Motor pole/rpm		4-1400	4-1400
Remote control		DTS	DTS
Pump/head/pistons		lpc plunger/brass/ceramic	lpc plunger/brass/ceramic
Detergent tank	l	-	-
Detergent delivery		-	-
Dimension (LxWxH)	cm	78x45x100	78x45x100
Weight	kg	47	53

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000 +
EXTENSION P330+M22



CODE: LCPR40087
EXTENSION P70 - INOX



CODE: UGLN11196
H.P. NOZZLE 1/4 15035
(FOR 1310)



CODE: UGLN49987
H.P. NOZZLE 1/4 15045
(FOR 1915)



CODE: TBAP40229
H.P. HOSE 10 m 1/4"



OPTIONAL ACCESSORIES

CODE: RCIN10810
HOSE COUPLINGS
M22-M22



CODE: TBAP23853
DRAIN KIT 10 m - M22



CODE: LCPR29360
MUDGUARD LANCE P90



ACCESSORIES TO DELIVERY CHEMICAL PRODUCT

OPTION (1)

OPTION (2)

CODE: LCPR40040
FOAMER KIT 1 I



CODE: KTRI40527
EJECTOR KIT + P70 HYJET



CODE: TBAP40229
H.P.HOSER1 15 m 5/16"



CODE: TBAP44379
H.P.HOSE R1 20 m N5/16"



CODE: LCPR13557
SANDBLASTER KIT D.1,6 -
(FOR 1915)



CODE: LCPR14858
SANDBLASTER KIT D.1,4 -
(FOR 1310)



CODE: PRCH40041
SAND BAG 25 Kg



CODE: LCPR93178
TURBO LANCE TTR-16
Ø 1,35



CODE: LCLC49492
LANCE FOR WASHING
FLOORS 0,35 - (FOR 1310)



CODE: LCLC49493
LANCE FOR WASHING
FLOORS 0,45 - (FOR 1915)



CODE: KTRI40505
HOSE REEL KIT



CODE: KTRI40479
KIT FOR HOT WATER
FEEDING VERSION





IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - COLD WATER

PW-C50

DELAYED TOTAL STOP MODELS

PRESSURE

160÷210
bar

FLOW RATE

1000÷1300
l/h

ABSORBED POWER

6,3÷6,7
kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT PROPORTIONAL SWITCH OFF - IPSF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ NOZZLE CLOGGED CONTROL - NCC
- ▶ WORKING HOURS COUNTER - WHC
- ▶ FLOODING PREVENTION SYSTEM - FPS



WITHOUT HOSE REEL

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



HEAVY INDUSTRY



INNOVATIONS



G6000™
CERAMIC
HIGH-TECH GUN



MSC™
MULTIFUNCTION
SAFETY
CONTROL



IPC
PUMP

SPECS



PROFESSIONAL PRESSURE
GAUGE ENABLING A
CONSTANT CHECK OF
WORKING PRESSURE



LARGE DIAMETER WHEELS
(PUNCTURE PROOF)



STURDY PAINTED STEEL
FRAME

TECHNICAL DATA

		PW-C50 D2117P T	PW-C50 D1622P T
Code		IDAF40261	IDAF40270
PERFORMANCE			
Operating pressure	bar/Mpa	30-210/3-21	30-160/3-16
Flow rate	l/h	1000	1300
Max inlet water temperature	°C	50	50
Power supply	Ph-V-Hz/A	3-400-50/12	3-400-50/13
Absorbed power	kW	6,4	6,7
Motor pole/rpm		4-1400	4-1400
Remote control		DTS	DTS
Pump/head/pistons		IPC plunger/brass/ceramic	IPC plunger/brass/ceramic
Detergent tank	l	4	4
Detergent delivery		low pressure	low pressure
Dimension (LxWxH)	cm	77x51x88	77x51x88
Weight	kg	68	67

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000 +
EXTENSION P330+M22



CODE: LCPR40047
EXTENSION P580
1,45GLO (FOR 2117)



CODE: LCPR40056
EXTENSION P580 1,75GRI
(FOR 1622)



CODE: TBAP40256
HIGH PRESSURE HOSE 10 m



OPTIONAL ACCESSORIES

CODE: SPID24911
HYDROBRUSH LANCE



CODE: RCIN10810
HOSE COUPLINGS



CODE: TBAP23853
DRAIN KIT 10 m
(FOR 2117)



CODE: TBAP24406
DRAIN KIT 20 m
(FOR 1622)



CODE: LCPR40040
FOAMER KIT 1 l



CODE: LCLC49494
LANCE FOR WASHING
FLOOR 0,55



CODE: LCPR14859
SANDBLASTER KIT Ø 1,5 mm
(FOR 2117)



CODE: LCPR14860
SANDBLASTER KIT Ø 1,7 mm
(FOR 1622)



CODE: PRCH40041
SAND BAG 25 Kg



CODE: KTRI29366
PLUNGER EJECTOR DEVICE



CODE: LCPR40054
TURBO LANCE TPR255
M22 0,40 (FOR 2117)



CODE: LCPR40055
TURBO LANCE R.J. 255
M22 0,70 (FOR 1622)



CODE: KTRI40436
MAINTENANCE KIT 500H
(FOR 1622)



CODE: KTRI40338
MAINTENANCE KIT 500H
(FOR 2117)



CODE: KTRI40304
KIT FOR HOT WATER
FEEDING VERSION -
(FOR 1622)



CODE: KTRI40336
KIT FOR HOT WATER
FEEDING VERSION - (2117)





IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - COLD WATER

PW-C55 VALUE

PRESSURE

170÷250
bar

FLOW RATE

900÷1300
l/h

ABSORBED POWER

6,4÷8,4
kW



EXCLUSIVE CHARACTERISTICS

► DELAYED TOTAL STOP - DTS

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



HEAVY INDUSTRY



INNOVATION



G6000™
CERAMIC
HIGH-TECH GUN



IPC
PUMP



MSC™
MULTIFUNCTION
SAFETY
CONTROL

SPECS



COLLAPSIBLE HANDLE FOR
COMPACT STORAGE AND EASY
TRANSPORT



NEW STORAGE SPACE FOR ALL
EQUIPMENT AND ACCESSORIES



REMOVABLE COVER, AND EASY OIL
FILL-EMPTY SYSTEM FOR A RAPID
MAINTENANCE

TECHNICAL DATA

		PW-C55 D2117P T	PW-C55 D1721P T	PW-C55 D2021P T	PW-C55 D2515P T
CODE		IDAF40922	IDAF40923	IDAF40924	IDAF40925
PERFORMANCE					
Operating pressure	bar/Mpa	30-210/3-21	30-170/3-17	30-200/3-20	30-250/3-25
Flow rate	l/h	300-1000	300-1300	400-1300	450-900
Max inlet water temperature	°C	50	50	50	50
Power supply	Ph-V-Hz/A	3-400-50/13,3	3-400-50/14	3-400-50/15,8	3-400-50/14,9
Absorbed power	kW	6,4	7,3	8,4	7,5
Motor pole/rpm		4-1400	4-1400	4-1400	4-1400
Remote control		DTS	DTS	DTS	DTS
Pump/head/pistons		lpc plunger/brass/ceramic	lpc plunger/brass/ceramic	lpc plunger/brass/ceramic	lpc plunger/brass/ceramic
Detergent tank	l	-	-	-	-
Detergent delivery		low pressure	low pressure	low pressure	low pressure
Dimension (LxWxH)	cm	88x48x104	88x48x104	88x48x104	88x48x104
Weight	kg	61,4	63,3	69	69,1

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000 +
EXTENSION P330+M22



CODE: LCPR40087
EXTENSION P70 INOX
(FOR 1721/2117)



CODE: LCPR40159
LANCE P70 INOX 0°
(FOR 2021/2515)



CODE: UGLN49987
H.P. NOZZLE 1/4 15045
(FOR 2117)



CODE: UGLN02303
H.P. NOZZLE 1/4 15065
(FOR 2021)



CODE: UGLN49986
H.P. NOZZLE 1/4 1504 (FOR
2515)



CODE: UGLN49997
H.P. NOZZLE 1/4 25075
(FOR 1721)



CODE: TBAP25324
HIGH PRESSURE HOSE
10 m



OPTIONAL ACCESSORIES

CODE: KTRI40505
HOSE REEL KIT (WITHOUT
HOSE)



CODE: KTRI40506
HOSE REEL KIT (WITH 20 m
HOSE)



CODE: LCPR29360
MUDGUARD LANCE P90



CODE: TBAP23853
DRAIN KIT 10 m
(FOR 2117)



CODE: TBAP24406
DRAIN KIT 20 m
(FOR 1721/2021)



CODE: RCIN10810
HOSE COUPLINGS M22



CODE: PRCH40041
SAND BAG 25 Kg



CODE: KTRI00038
INJECTOR KIT



CODE: LCPR40135
EXTENSION P70 + TPR-
255 Ø0,45 (FOR 2117)



ACCESSORIES TO DELIVERY CHEMICAL PRODUCT

OPTION (1)

CODE: LCPR40040
FOAMER KIT 1 l



OPTION (2)

CODE: KTRI40527
EJECTOR KIT + P70 HY.JET



CODE: LCPR14859
SANDBLASTER KIT Ø 1,5 -
(FOR 2117)



CODE: LCPR14858
SANDBLASTER KIT Ø 1,4 -
(FOR 2515)



CODE: LCPR40170
EXTENSION P70 + R.J.255
Ø0,75 (FOR 1721)



CODE: LCPR40174
EXTENSION P70 + R.J.255
Ø0,70 (FOR 2021)



CODE: LCPR40103
EXTENSION P70 + TPR-
255 Ø0,40 (FOR 2515)



CODE: SPID24939
FIXED HYDROBRUSH
LANCE



CODE: LCLC49494
LANCE FOR WASHING
FLOORS 0,55



CODE: KTRI40590
MAINTENANCE KIT 500H
(FOR 1721P/2021P)



CODE: KTRI40589
MAINTENANCE KIT 500H
(FOR 2117P)



CODE: KTRI40591
MAINTENANCE KIT 500H
(FOR 2515)



CODE: KTRI40336
KIT FOR HOT WATER
FEEDING VERSION
(FOR 2117)



CODE: KTRI40323
KIT FOR HOT WATER
FEEDING VERSION
(1721/2021)



CODE: KTRI40304
KIT FOR HOT WATER
FEEDING VERSION
(FOR 2515)





IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - COLD WATER

PW-C55 PREMIUM

PRESSURE

170÷250
bar

FLOW RATE

900÷1300
l/h

ABSORBED POWER

6,4÷8,4
kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT PROPORTIONAL SWITCHING OFF - IPSF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ NOZZLE CLOGGED CONTROL - NCC
- ▶ WORKING HOURS COUNTER - WHC
- ▶ FLOODING PREVENTION SYSTEM - FPS
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ MAINTENANCE CHECK LED
- ▶ WARNING LEDS



MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



HEAVY INDUSTRY



INNOVATION



G6000™
CERAMIC
HIGH-TECH GUN



IPC
PUMP



MSC™
MULTIFUNCTION
SAFETY
CONTROL

SPECS



COLLAPSIBLE HANDLE FOR
COMPACT STORAGE AND EASY
TRANSPORT



NEW STORAGE SPACE FOR ALL
EQUIPMENT AND ACCESSORIES



REMOVABLE COVER, AND EASY OIL
FILL-EMPTY SYSTEM FOR A RAPID
MAINTENANCE

TECHNICAL DATA

CODE		PW-C55 DP2117P T IDAF40926	PW-C55 DP1721P T IDAF40927	PW-C55 DP2021P T IDAF40928	PW-C55 DP2515P T IDAF40929
PERFORMANCE					
Operating pressure	bar/Mpa	30-210/3-21	30-170/3-17	30-200/3-20	30-250/3-25
Flow rate	l/h	300-1000	300-1300	400-1300	450-900
Max inlet water temperature	°C	50	50	50	50
Power supply	Ph-V-Hz/A	3-400-50/13,3	3-400-50/14	3-400-50/15,8	3-400-50/14,9
Absorbed power	kW	6,4	7,3	8,4	7,5
Motor pole/rpm		4-1400	4-1400	4-1400	4-1400
Remote control		DTS	DTS	DTS	DTS
Pump/head/pistons		lpc plunger/brass/ceramic	lpc plunger/brass/ceramic	lpc plunger/brass/ceramic	lpc plunger/brass/ceramic
Detergent tank	l	-	-	-	-
Detergent delivery		low pressure	low pressure	low pressure	low pressure
Dimension (LxWxH)	cm	88x48x104	88x48x104	88x48x104	88x48x104
Weight	kg	61,4	63,3	69	69,1

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000 +
EXTENSION P330+M22



CODE: LCPR40087
EXTENSION P70 INOX
(FOR 1721/2117)



CODE: LCPR40159
LANCE P70 INOX 0°
(FOR 2021/2515)



CODE: UGLN49987
H.P. NOZZLE 1/4 15045
(FOR 2117)



CODE: UGLN02303
H.P. NOZZLE 1/4 15065
(FOR 2021)



CODE: UGLN49986
H.P. NOZZLE 1/4 1504
(FOR 2515)



CODE: UGLN49997
H.P. NOZZLE LANCE 1/4
25075 - (FOR 1721)



CODE: TBAP25324
HIGH PRESSURE HOSE
10 m



OPTIONAL ACCESSORIES

CODE: KTRI40505
HOSE REEL KIT (WITHOUT
HOSE)



CODE: KTRI40506
HOSE REEL KIT (WITH 20 m
HOSE)



CODE: LCPR29360
MUDGUARD LANCE P90



CODE: TBAP23853
DRAIN KIT 10 m
(FOR 2117)



CODE: TBAP24406
DRAIN KIT 20 m
(FOR 1721/2021)



CODE: RCIN10810
HOSE COUPLINGS M22



CODE: PRCH40041
SAND BAG 25 Kg



CODE: KTRI00038
INJECTOR KIT



CODE: LCPR40135
EXTENSION P70 + TPR-
255 Ø0,45 (FOR 2117)



CODE: LCPR40103
EXTENSION P70 + TPR-
255 Ø0,40 (FOR 2515)



CODE: SPID24939
FIXED HYDROBRUSH
LANCE



CODE: LCLC49494
LANCE FOR WASHING
FLOORS 0,55



CODE: KTRI40591
MAINTENANCE KIT 500H
(FOR 2515)



CODE: KTRI40336
KIT FOR HOT WATER
FEEDING VERSION
(FOR 2117)



CODE: KTRI40323
KIT FOR HOT WATER
FEEDING VERSION
(1721/2021)



ACCESSORIES TO DELIVERY CHEMICAL PRODUCT

OPTION [1]

OPTION [2]

CODE: LCPR40040
FOAMER KIT 1 I



CODE: KTRI40527
EJECTOR KIT + P70 HY.JET



CODE: LCPR14859
SANDBLASTER KIT Ø1,5 -
(FOR 2117)



CODE: LCPR14858
SANDBLASTER KIT Ø1,4 -
(FOR 2515)



CODE: LCPR40170
EXTENSION P70 + R.J.255
Ø0,75 (FOR 1721)



CODE: LCPR40174
EXTENSION P70 + R.J.255
Ø0,70 (FOR 2021)



CODE: KTRI40590
MAINTENANCE KIT 500H -
(FOR 1721/2021)



CODE: KTRI40589
MAINTENANCE KIT 500H -
(FOR 2117)



CODE: KTRI40304
KIT FOR HOT WATER
FEEDING VERSION
(FOR 2515)





IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - COLD WATER

PW-C55

(PAINTED STEEL STRUCTURE)

PRESSURE

170÷210
bar

FLOW RATE

1000÷1300
l/h

ABSORBED POWER

6,9÷8,1
kW



EXCLUSIVE CHARACTERISTICS

► DELAYED TOTAL STOP - DTS

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



HEAVY INDUSTRY



INNOVATION



G6000™
CERAMIC
HIGH-TECH GUN



IPC
PUMP



MSC™
MULTIFUNCTION
SAFETY
CONTROL

SPECS



IPC PLUNGER PUMP WITH BRASS
HEAD AND CERAMIC PISTONS



HEAVY-DUTY STRUCTURE, ANTI
COLLISION, STEEL FRAME COVER



LARGE WHEELS IMPROVE
MANEUVERABILITY AND EASE
TRANSPORT

TECHNICAL DATA

		PW-C55 D2117P4m T	PW-C55 D1721P4m T	PW-C55 D2021P4m T
CODE		IDAF41106	IDAF41108	IDAF41109
PERFORMANCE				
Operating pressure max	bar/Mpa	40-210/4-21	40-170/4-17	40-200/4-20
Flow rate	l/h	360-1000	360-1300	390-1300
Inlet water max. temperature	°C	50	50	50
Power supply	Ph-V-Hz/A	3-400-50/13,6	3-400-50/13,8	3-400-50/15,8
Absorbed power	kW	6,9	7,1	8,1
Motor pole/rpm		4-1400	4-1400	4-1400
Remote control		DTS	DTS	DTS
Pump/head/pistons		lpc plunger/brass/ceramic	lpc plunger/brass/ceramic	lpc plunger/brass/ceramic
Detergent tank	l	-	-	-
Detergent delivery		-	-	-
Dimension (LxWxH)	cm	78x45x100	78x45x100	78x45x100
Weight	kg	66,40	67,5	73

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000 +
EXTENSION P330+M22



CODE: LCPR40087
EXTENSION P70 INOX
(FOR 2117)



CODE: LCPR40159
EXTENSION P70 INOX 0°
(FOR 1721/2021)



CODE: UGLN49987
H.P. NOZZLE 1/4 15045
(FOR 2117)



CODE: UGLN49997
H.P. NOZZLE 1/4 15075
(FOR 1721)



CODE: UGLN02303
H.P. NOZZLE 1/4 15065 -
(FOR 2021)



CODE: TBAP25324
H.P. HOSE R1 10 m
5/16"



OPTIONAL ACCESSORIES

CODE: RCIN10810
HOSE COUPLINGS M22



CODE: TBAP23853
DRAIN KIT 10 m - M22



CODE: TBAP24406
DRAIN KIT 20 M - M22 -
(FOR 1721/2021)



CODE: TBAP40062
H.P.HOSER1 15m 5/16"



CODE: TBAP44379
H.P.HOSE R1 20 m N5/16"



CODE: LCPR13557
SANDBLASTER KIT D.1,6 -
(FOR 1915)



ACCESSORIES TO DELIVERY CHEMICAL PRODUCT

OPTION (1)

OPTION (2)

CODE: LCPR40040
FOAMER KIT 1 I



CODE: KTRI40527
EJECTOR KIT + P70 HY.JET



CODE: TBAP40062
H.P.HOSER1 15m 5/16"



CODE: TBAP44379
H.P.HOSE R1 20 m N5/16"



CODE: LCPR13557
SANDBLASTER KIT D.1,6 -
(FOR 1915)



CODE: PRCH40041
SAND BAG 25 Kg



CODE: LCPR29360
MUDGUARD LANCE P90



CODE: LCPR40054
TURBO LANCE TPR255 Ø
0,40 - (FOR 2117)



CODE: LCPR40131
EXTENSION P70 + R.JET
255 Ø 0,75 - (FOR 1721)



CODE: LCPR40132
EXTENSION P70 + R.JET
255 Ø 0,65 - (FOR 2021)



CODE: KTRI40505
HOSE REEL KIT



CODE: KTRI40336
KIT FOR HOT WATER
FEEDING VERSION
(FOR 2117)



CODE: KTRI40323
KIT FOR HOT WATER
FEEDING VERSION
(FOR 1721)



CODE: KTRI40436
KIT FOR HOT WATER
FEEDING VERSION
(FOR 2021)





IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - COLD WATER

PW-C85

PRESSURE

200÷350
bar

FLOW RATE

900÷1800
l/h

ABSORBED POWER

12,3÷12,5
kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT PROPORTIONAL SWITCH OFF - IPSF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ NOZZLE CLOGGED CONTROL - NCC
- ▶ WORKING HOURS COUNTER - WHC
- ▶ FLOODING PREVENTION SYSTEM - FPS



PAINTED STEEL STRUCTURE

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



HEAVY INDUSTRY



INNOVATIONS



G6000™
CERAMIC
HIGH-TECH GUN



MSC™
MULTIFUNCTION
SAFETY
CONTROL



IPC
PUMP

SPECS



IPC PLUNGER PUMP WITH
BRASS HEAD AND CERAMIC
PISTONS



HEAVY-DUTY STRUCTURE,
ANTI-COLLISION, STEEL
FRAME COVER



MAINTENANCE-FREE
ELECTRIC MOTOR, AIR-
COOLED AND PROTECTED
WITH THERMAL CUTOUT

TECHNICAL DATA

		15 HP	
		PW-C85 D2030P4 T IDAF40832	PW-C85 D3515P4 T IDAF40827
Code			
PERFORMANCE			
Operating pressure	bar/Mpa	40-200/4-20	350/35
Flow rate	l/h	390-1800	900
Max inlet water temperature	°C	50	50
Power supply	Ph-V-Hz/A	3-400-50/23	3-400-50/22,4
Absorbed power	kW	12,5	12,3
Motor pole/rpm		4-1400	4-1400
Remote control		DTS	DTS
Pump/head/pistons		lpc plunger/brass/ceramic	lpc plunger/brass/ceramic
Detergent tank	l	-	-
Detergent delivery		-	-
Dimension (LxWxH)	cm	78x59x90	78x59x90
Weight	kg	115	115

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000
(FOR 2030)



CODE: IPIP42787
GRIP RL56 M24 + 3/8
(FOR 3515)



CODE: LCPR40159
EXTENSION P70 INOX 0°
(FOR 2030)



CODE: LCLC42786
EXTENSION L=105 cm
(FOR 3515)



CODE: UGLN02314
H.P. NOZZLE 1/4 2510
(FOR 2030)



CODE: UGLN40026
H.P. NOZZLE 1/4 15035
500 BAR (FOR 3515)



CODE: TBAP40010
H.P. HOSE R2 10 m 3/8"
M22 (FOR 2030)



CODE: TBAP00029
H.P. HOSE R2 10 m 5/16"
3/8M-M - (FOR 3515)



OPTIONAL ACCESSORIES

CODE: RCIN10810
HOSE COUPLINGS M22
(NOT FOR 3515)



CODE: TBAP24406
DRAIN KIT 20 m
(NOT FOR 3515)



CODE: LCPR29360
MUDGUARD LANCE P90
(NOT FOR 3515)



CODE: LCPR40040
FOAMER HEAD KIT 1 I
(NOT FOR 3515)



CODE: LCLC40022
SANDBLASTER KIT P105 cm
Ø0,35 (FOR 3515)



CODE: PRCH40041
SAND BAG 25 Kg



CODE: LCPR40133
EXTENSION P70 + R.J.255
Ø100 (FOR 2030)



CODE: LCLC47893
EXTENSION 105 cm
TURBO Ø035 (FOR 3515)



CODE: KTRI40400
HOSE REEL KIT (FOR 2030)



CODE: KTRI40441
MAINTENANCE KIT 500H
(FOR 2030)



CODE: KTRI40440
MAINTENANCE KIT 500H
(FOR 3515)





IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - COLD WATER

ABSOLUTE-C

PRESSURE

200÷500

bar

FLOW RATE

1000÷2500

l/h

ABSORBED POWER

16÷22

kW



EXCLUSIVE CHARACTERISTICS

- ▶ THERMOSTATIC VALVE - TSV
- ▶ REMOTE-CONTROLLED SAFETY STOP - ST
- ▶ DRY RUNNING PROTECTION - DRP

Ø40 STEEL TUBE FRAME WITH STAINLESS STEEL COVERS

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



HEAVY INDUSTRY



INNOVATIONS



MSC™
MULTIFUNCTION
SAFETY
CONTROL



IPC
PUMP

SPECS



PROFESSIONAL PRESSURE GAUGE ENABLING THE CONSTANT MONITORING OF WORKING PRESSURE



HIGH-CAPACITY & SELF-CLEANING FILTER



THERMOSTATIC VALVE PROTECTING THE PUMP FROM POSSIBLE OVERHEATING

TECHNICAL DATA

		ABSOLUTE-C S2041P T	ABSOLUTE-C S3521P T	ABSOLUTE-C S5015P T	ABSOLUTE-C S5022P T
Code		IDAF40349	IDAF40350	IDAF40351	IDAF40932
PERFORMANCE					
Operating pressure	bar/Mpa	200/20	350/25	500/50	500/50
Flow rate	l/h	2500	1300	1000	1320
Max inlet water temperature	°C	50	50	50	50
Power supply	Ph-V-Hz/A	3-400-50/31	3-400-50/29,8	3-400-50/30,6	3-400-50/39,3
Absorbed power	kW	17,5	17,5	16	22
Motor pole/rpm		4-1400	4-1400	4-1400	4-1400
Remote control		ST	ST	ST	ST
Pump/head/pistons		lpc plunger/brass/ceramic	lpc plunger/brass/ceramic	lpc plunger/brass/ceramic	lpc plunger/brass/ceramic
Detergent tank	l	-	-	-	-
Detergent delivery		-	-	-	-
Dimension (LxWxH)	cm	120x70x100	120x70x100	120x70x100	120x70x100
Weight	kg	190	182	185	220

STANDARD EQUIPMENT

CODE: IPPR40006
HANDGRIP G3600 + P330 M24 (FOR 2041)



CODE: IPPR40005
HANDGRIP G7300 + EXTENSION330 M24 M24 (FOR 3521)



CODE: IPPR40024
HANDGRIP ST3600 + P380 M24 (FOR 5015/5022)



CODE: LCPR40028
EXTENSION P70 INOX M24 (FOR 2041)



CODE: LCPR40026
EXTENSION P70 INOX M24 (FOR 3521/5015/5022)



CODE: UGLN07790
H.P NOZZLE 1/4 2513 (FOR 2041)



CODE: UGLN05200
H.P NOZZLE 1/4 1505 (FOR 3521)



CODE: UGLN40018
H.P NOZZLE 1/4 15028 500BAR (FOR 5015)



CODE: UGLN40040
H.P NOZZLE 1/4 15040 (FOR 5022)



CODE: TBAP40050
H.P HOSE R3 15 m 3/8" M24 (FOR 3521/5015/5022)



CODE: TBAP40054
H.P HOSE R2 15 m 1/2" M24 (FOR 2041)



OPTIONAL ACCESSORIES

CODE: RCIN40011
HOSE COUPLINGS M24 500B (FOR 5015)



CODE: RCIN40012
HOSE COUPLINGS M24 HF (FOR 2041/3521)



CODE: LCPR40032
ROTATING LANCE P70 M24 (FOR 3521)



CODE: LCPR40033
ROTATING LANCE P70 M24 (FOR 2041)



CODE: LCPR40031
ROTATING LANCE P70 M24(FOR 5015)



CODE: LCPR40173
ROTATING LANCE P70 M24 (FOR 5022)



CODE: TBAP40070
DRAIN KIT 10 m M24 CD.03 INOX (FOR 5015)



CODE: TBAP40071
DRAIN KIT 15 m M24 CD.03 INOX (FOR 5015)



CODE: TBAP40072
DRAIN KIT 10 m M24 CD.05 INOX (FOR 3521/5022)



CODE: TBAP40073
DRAIN KIT 15 m M24 CD.05 INOX (FOR 3521/5022)



CODE: LCPR40142
SANDBLASTER KIT 15028 (FOR 5015)



CODE: LCPR40144
SANDBLASTER KIT 1505 (FOR 3521)



CODE: LCPR40172
SANDBLASTER KIT 15040 (FOR 5022)



CODE: PRCH40041
SAND BAG 25 Kg





IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - COLD WATER



BENZ-C

ENDOTHERMIC ENGINE

PRESSURE

180÷250

bar

FLOW RATE

540÷1300

l/h

ENGINE POWER

6,5÷13

Hp



BENZ-C H1809 A



BENZ-C H1811P



BENZ-C H2515P P
BENZ-C H DL2515P P
BENZ-C L2216P P
BENZ-C L2021P P
BENZ-C L DL2217P P
BENZ-C L DL2021P P

EXCLUSIVE CHARACTERISTICS

- ▶ THERMOSTATIC VALVE - TSV
- ▶ ENGINE THROTTLE CONTROL - RS (ONLY DL MODELS)

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



HEAVY INDUSTRY



INNOVATIONS



G6000™
CERAMIC
HIGH-TECH GUN

SPECS



"L" VERSIONS ARE PROVIDED WITH A GEARBOX



HYDRAULIC SPEED REDUCER REDUCES ENGINE RPM WHEN PUMP IS BY-PASS



FLEXIBLE COUPLING BETWEEN PUMP AND ENGINE

TECHNICAL DATA

		BENZ-C H1809 A	BENZ-C H1811P P	BENZ-C H2515P P	BENZ-C H DL2515P P	BENZ-C L2216P P	BENZ-C L2021P P	BENZ-C L DL2217P P	BENZ-C L DL2021P P
Code		IDAF41150	IDAF41151	IDAF41152	IDAF41157	IDAF41153	IDAF41158	IDAF41154	IDAF41159
PERFORMANCE									
Pressure	bar/Mpa	180/18	30-180/3-18	30-250/3-25	30-250/3-25	30-220/3-22	30-200/3-20	30-220/3-22	30-200/3-20
Flow rate	l/h	540	330-660	450-900	450-900	500-1000	400-1260	450-1000	450-1260
Max inlet water temperature	°C	50	50	50	50	50	50	50	50
Engine type		Honda GX200 (gasoline)	Honda GX200 (gasoline)	Honda GX390 (gasoline)	Honda GX390 (gasoline)	Honda GX390 (gasoline)	Honda GX390 (gasoline)	Honda GX390 (gasoline)	Honda GX390 (gasoline)
Engine power	Hp	6,5	6,5	13	13	13	13	13	13
Pump speed	rpm	3000	3000	3000	3000	1500	1500	1500	1500
Remote control		BYP	BYP	BYP	BYP	BYP	BYP	BYP	BYP
Pump/head/pistons		Axial/brass/inox	IPC plunger/brass/ceramic	IPC plunger/brass/ceramic	IPC plunger/brass/ceramic	IPC plunger/brass/ceramic	IPC plunger/brass/ceramic	IPC plunger/brass/ceramic	IPC plunger/brass/ceramic
Detergent tank	l	-	-	-	-	-	-	-	-
Detergent delivery		low pressure	low pressure	low pressure	low pressure	low pressure	low pressure	low pressure	low pressure
Dimension (LxWxH)	cm	86x56x54	86x56x54	105x66x75	105x66x75	105x66x75	105x66x75	105x66x75	105x66x75
Weight	kg	46	49,5	78,2	78,2	84	85	85	85
Motor-pump coupling		direct	direct	elastic coupling	elastic coupling	gearbox	gearbox	gearbox	gearbox

STANDARD EQUIPMENT

CODE: IPPR40025
**HANDGRIP G6000 +
EXTENSION P330+M22**



CODE: LCPR40013
**EXTENSION INOX P70 +
HY.JET**



CODE: UGLN49988
**H.P. NOZZLE 1/4 25025 -
(FOR 1809)**



CODE: UGLN49990
**H.P. NOZZLE 1/4 25034 -
(FOR 1811/2515)**



CODE: UGLN05199
**H.P. NOZZLE 1/4 2505 -
(FOR 2216/2217)**



CODE: UGLN49995
**H.P. NOZZLE 1/4 25065 -
(FOR 2021)**



CODE: TBAP40256
H.P. HOSE 10 m 5/16"



OPTIONAL ACCESSORIES

CODE: RCIN10810
HOSE COUPLINGS M22



CODE: LCPR24906
**LANCE WITH DOUBLE
NOZZLE HOLDER**



CODE: LCPR29360
MUDGUARD LANCE P90



CODE: TBAP23853
**DRAIN KIT MT 10
(FOR 1809/1811)**



CODE: TBAP24406
**DRAIN KIT 20 m
(FOR 2216/2217/2021)**



CODE: LCPR93177
**TURBO LANCE TTR16
Ø 1.30- (FOR 1809)**



CODE: LCPR40008
**TURBO LANCE P70 Ø 035 -
(FOR 1811/2515)**



CODE: LCPR40009
**TURBO LANCE P70 Ø 035 -
(FOR 1811/2515)**



CODE: LCPR41973
**TURBO LANCE P70 Ø 055
(FOR 2216/2217)**



CODE: LCPR88522
**TURBO LANCE P70 Ø 065
(FOR 2021)**



CODE: TBAP40062
FLEXIBLE HOSE 15 m



CODE: TBAP44379
FLEXIBLE HOSE 20 m



CODE: KTRI40186
HOSE REEL KIT



CODE: LCPR40040
FOAMER HEAD KIT 1 l



CODE: LCPR24393
**SANDBLASTER KIT Ø 1,3 -
(FOR 1809)**



CODE: LCPR24393
**SANDBLASTER KIT Ø 1,3 mm
(FOR 1809)**



CODE: LCPR14858
**SANDBLASTER KIT Ø 1,4 mm
(FOR 1811/2515)**



CODE: LCPR13557
**SANDBLASTER KIT Ø 1,6 mm
(FOR 2216/2217)**



CODE: LCPR14860
**SANDBLASTER KIT Ø 1,7 mm
(FOR 2021)**



CODE: PRCH40041
SAND BAG 25 Kg



CODE: LCLC49492
**LANCE FOR WASHING
FLOORS 0,35 - (FOR
1809/1811)**



CODE: LCLC49494
**LANCE FOR WASHING
FLOORS 0,55 (FOR 2021)**





IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - COLD WATER

DIESEL-C

ELECTRIC STARTER

PRESSURE

200 bar

FLOW RATE

1000 l/h

ENGINE POWER

10 Hp



YANMAR SERIE
DIESEL ENGINE

EXCLUSIVE CHARACTERISTICS

- THERMOSTATIC VALVE - TSV
- ENGINE THROTTLE CONTROL - RS

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



HEAVY INDUSTRY



INNOVATIONS



G6000™
CERAMIC
HIGH-TECH GUN



IPC
PUMP

SPECS



LARGE DIAMETER, WIDE
TREAD TYRED WHEELS
SUITABLE FOR ANY SURFACE



PROVIDED WITH A
REDUCTION GEAR IN ORDER
TO EXTEND PUMP LIFESPAN



EQUIPPED WITH ENGINE
THROTTLE CONTROL IT
REDUCES ENGINE RPM WHEN
BY-PASS IS ACTIVATED

TECHNICAL DATA

Code	IDAF40794	
PERFORMANCE		
Operating pressure max	bar/Mpa	30-200/3-20
Flow rate	l/h	630-1000
Max inlet water temperature	°C	50
Engine type	Yanmar L100N6 (diesel)	
Engine power	Hp	10
Engine speed	rpm	1500
Remote control	BYP	
Pump/head/pistons	IPC plunger/brass/ceramic	
Detergent tank	l	-
Detergent delivery	low pressure	
Dimension (LxWxH)	cm	105x66x75
Weight	kg	120
Motor-pump coupling	gearbox	

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000



CODE: LCPR40013
EXTENSION INOX P70+ HYJET



CODE: UGLN49987
H.P NOZZLE 1/4 15045



CODE: TBAP40256
HIGH PRESSURE HOSE 10 m



OPTIONAL ACCESSORIES

CODE: RCIN10810
HOSE COUPLINGS M22



CODE: LCPR24906
LANCE WITH DOUBLE
NOZZLE HOLDER



CODE: LCPR29360
MUDGUARD LANCE P90



CODE: TBAP23853
DRAIN KIT 10 m



CODE: TBAP24406
DRAIN KIT 20 m



CODE: TBAP40062
FLEXIBLE HOSE 15 m



CODE: TBAP44379
FLEXIBLE HOSE 20 m



CODE: KTRI40526
HOSE REEL KIT



CODE: LCPR40040
FOAM HEAD KIT 1 l



CODE: LCPR14859
SANDBLASTER KIT Ø 1,5



CODE: PRCH40041
SAND BAG 25 Kg



CODE: LCPR40054
TURBO LANCE TPR-255
Ø0,40



CODE: LCLC49494
LANCE FOR WASHING
FLOORS Ø,55



CODE: KTRI40444
MAINTENANCE KIT 500H



CODE: KTRI40336
KIT FOR HOT WATER
FEEDING VERSION





IPC

BY TENNANT COMPANY

HOT WATER GENERATOR

FIRE BOX

PRESSURE

175÷350
bar

FLOW RATE

1260 l/h

ABSORBED POWER

0,3 kW



EXCLUSIVE CHARACTERISTICS

- BOILER IGNITION DELAY - IBD

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



HEAVY INDUSTRY



SPECS



SINGLE PHASE BURNER
MOTOR CONNECTED TO FAN
AND DIESEL FUEL PUMP



COVER AND TROLLEY IN
PAINTED SHEET METAL



ELECTRIC CONTROL PANEL
WITH ON-OFF SWITCH AND
THERMOSTAT

TECHNICAL DATA

		30M FIRE BOX	40M FIRE BOX	40/350 FIRE BOX
Code		CDVE49715	CDVE49716	CDVE40027
PERFORMANCE				
Operating pressure max	bar/Mpa	175/17,5	200/20	350/35
Flow rate	l/h	360-1260	360-1260	360-1260
Outlet water max. temperature	°C	140	140	140
Power supply	Ph-V-Hz/A	1-230-50/2	1-230-50/2	1-230-50/2
Absorbed power	kW	0,3	0,3	0,3
Fuel tank	l	18	18	18
Fuel consumption max	kg/h	5,8	7,2	7,2
Boiler thermal power	kW	70	90	90
Dimension (LxWxH)	cm	120x70x100	120x70x100	120x70x100
Weight	kg	108	111	112

STANDARD EQUIPMENT

CODE: RCIN03755
HOSE COUPLINGS



CODE: TBAP29050
HIGH PRESSURE HOSE
L2310 R2 3/8F - 3/8F





HOT WATER

EXCLUSIVE TECHNOLOGIES	76
PW-H10	78
PW-H28	80
PW-H28/4 PAINTED STEEL STRUCTURE	82
PW-H31 VALUE	84
PW-H61 VALUE	86
PW-H61 PREMIUM	88
PW-H90	90
PW-H101 VALUE	92
PW-H101 PREMIUM	94
PW-H101 HTM	96
PW-H101 AUTOMATIC	98
PW-H100 P PAINTED STEEL STRUCTURE	100
SKID FUEGO	102



IPC

BY TENNANT COMPANY

EXCLUSIVE TECHNOLOGIES

REMOTE CONTROLS

BY-PASS (BYP)	This system activates the machine's water recycling function when the trigger is released.
IMMEDIATE TOTAL STOP (ITS)	Instantly stops the machine when the trigger is released.
DELAYED TOTAL STOP (DTS)	Stops the machine 30" seconds after it last use.
DECELERATOR FOR REDUCTION OF ENGINE REVOLUTIONS (RS)	Reduced engine revolutions when the machine is in by-pass stage. It ensures long life and reduce fuel consumption.

SAFETY DEVICES

INTELLIGENT PROPORTIONAL SWITCH OFF (IPSF)	Automatic stop of the machine after a period of inactivity, which varies according to how long the machine has been used.
MICRO LEAKAGE CONTROL (MLC)	The machine stops in case of dangerous leakage in the high pressure hydraulic circuit.
DRY RUNNING PROTECTION (DRP)	Stops the machine in case of lack of water.
THERMOSTATIC VALVE (TSV)	In case of prolonged by-pass system operation, this system prevents water from overheating inside the high pressure pump.
LANCE NOZZLE CLOGGED CONTROL (NCC)	Stops the machine when the nozzle is clogged.
IGNITION BOILER DELAY (IBD)	Ensures low fume emission levels when the boiler is started.
WORKING HOURS COUNTER (WHC)	An electronic hour counter that shows the working hours of the machine.
IPC TEMPERATURE STABILIZER (ATC)	It keeps the temperature of the boiler constant.
DIGITAL TEMPERATURE STABILIZER CONTROL (DTSC)	An extremely accurate electronic control device that ensures constant water temperature.
INFRARED FLAME CONTROL SYSTEM (FCS)	This system stops the machine in case of boiler malfunction.

CONTROLS

MAINTENANCE CHECK LED (MCL)	This control device allerts you when maintenance is required (maintenance is scheduled every 200 hrs).
MAINTENANCE CHECK LED/ DISPLAY (MCLD)	Detailed maintenance information (LED + DISPLAY)
LIMESCALE/CORROSION PROTECTION UNIT (LCPU)	It protects hot-water machines againts limescale and corrosion.
FUEL LEVEL CONTROL (FLC)	Detects and reports the fuel lackage.
ANTISCALE LEVEL CONTROL (ALC)	Detects and reports the descaler lackage and stops the machine burner to prevents limescale deposits..
FLOODING PREVENTION SYSTEM (FPS)	This system stops the machine after 60 minutes of continuous activity.
DIRECT INJECTION DETERGENT AND ANTI-SCALE CONTROLS (DIAD)	Reducing detergent expense mechanical vibrations and noise related to the traditional systems
HIGH BRIGHTNESS LED SIGNALS (HBLs)	Signal lamps to keep everything under control.
LED INDICATOR LIGHT REACHING DESIRED TEMPERATURE (TL)	Informs the operator when the water reaches the selected temperature.

EXCLUSIVE TECHNOLOGIES

	PW-H10	PW-H28	PW-H31	PW-H61 VALUE PW-H101 VALUE	PW-H61 PREMIUM	PW-H90	PW-H101 PREMIUM PW-H101 HTM	PW-H101 AUTOMATIC	SKID FUEGO
									•
	•	•							
			•	•	•	•	•	•	
									•
			•	•	•	•	•	•	
			•	•	•	•	•	•	
			•	•	•		•	•	
									•
			•	•	•	•	•	•	
	•	•	•	•	•		•	•	•
			•	•	•		•	•	
		•	•	•					
					•		•	•	
							•	•	
			•	•	•		•	•	
					•		•	•	
				•	•	•	•	•	
			•	•	•	•	•	•	
					•	•	•	•	
			•	•	•		•	•	
			•	•	•		•	•	
					•		•	•	



IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - HOT WATER

PW-H10

PRESSURE

120÷140
bar

FLOW RATE

430÷450
l/h

ABSORBED POWER

2,1÷2,5
kW



PW-H10 P I 1408 AOM

EXCLUSIVE CHARACTERISTICS

- ▶ IMMEDIATE TOTAL STOP - ITS
- ▶ BOILER IGNITION DELAY - IBD

MOST FREQUENTLY USE

DIY AND GARDENING



INNOVATIONS



G6000™
CERAMIC
HIGH-TECH GUN

SPECS



LARGE FRONT FOOT FOR
GREATER STABILITY



STURDY ERGONOMIC
HANDLE FOR AN EASY
MANOEUVRABILITY



4 LITRES DIESEL TANK MADE
OF TRANSPARENT PLASTIC, IN
ORDER TO ENSURE CONSTANT
MONITORING OF DIESEL LEVEL

TECHNICAL DATA

		WITHOUT HOSE REEL		WITH HOSE REEL
		PW-H10 I1207AA M	PW-H10 I1408AA M	PW-H10P I1408AO M
Code		IDAC40572	IDAC40573	IDAC40574
PERFORMANCE				
Operating pressure	bar/Mpa	120/12	140/14	140/14
Flow rate	l/h	430	450	450
Outlet water temperature	°C	60	60	60
Power supply	Ph-V-Hz/A	1-230-50/9,4	1-230-50/9,7	1-230-50/11,2
Absorbed power	kW	2,1	2,3	2,5
Motor pole/rpm		2-2800	2-2800	2-2800
Remote control		ITS	ITS	ITS
Pump/head/pistons		Axial/aluminium/inox	Axial/aluminium/inox	Axial/brass/inox
Boiler thermal power	kW	26	26	26
Fuel consumption	kg/h	1,8	1,9	1,9
Fuel tank	l	4	4	4
Detergent tank	l	-	-	-
Detergent delivery		low pressure	low pressure	low pressure
Dimension (LxWxH)	cm	68x48x75	68x48x75	68x48x75
Weight	kg	44	50	55

STANDARD EQUIPMENT

CODE: IPPR40017
HANDGRIP MV2009
(FOR I1207AA/I1408AA)



CODE: IPPR40025
HANDGRIP G6000
(FOR I1408AO)



CODE: LCPR40037
EXTENSION P50
ZINC PLATED (FOR
I207AA/I408AA)



CODE: LCPR40071
LANCE WITH MULTIREG
NOZZLE Ø 1,10
(FOR I408AO)



CODE: UGLN49985
H.P NOZZLE 1/4 1503
(FOR I207)



CODE: UGLN75421
H.P NOZZLE 1/4 15025
(FOR I408AO)



CODE: TBAP28305
HIGH PRESSURE HOSE 8 m
(FOR I1207AA/I1408AA)



CODE: TBAP93872
HIGH PRESSURE HOSE 8 m
(FOR I1408AO)



CODE: LCPR40038
FOAMER M22
(FOR I1207AA/I1408AA)



CODE: LCPR40040
FOAMER M22 I I
(FOR I1408AO)



CODE: LCPR40011
TURBO LANCE M22 D. 1,15
(FOR I408AO)



OPTIONAL ACCESSORIES

CODE: SPID24911
ROTATING HYDROBRUSH
LANCE



CODE: SPID24939
FIXED HYDROBRUSH
LANCE



CODE: TBAP23853
DRAIN KIT 10 m



CODE: LCPR14857
SANDBLASTER KIT Ø 1,2 mm
(FOR I408)



CODE: PRCH40041
SAND BAG 25 Kg





IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - HOT WATER

PW-H28

PRESSURE

130 bar

FLOW RATE

500 l/h

ABSORBED POWER

2,7 kW

EXCLUSIVE CHARACTERISTICS

- ▶ IMMEDIATE TOTAL STOP - ITS ("I" MODELS)
- ▶ IGNITION BOILER DELAY - IBD
- ▶ IPC TEMPERATURE STABILIZER - ATC

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



DIY AND GARDENING



HEAVY INDUSTRY



INNOVATIONS



ALL
TERRAIN



MODERN
MODULAR
BUILD UP



IPC'S
EXCLUSIVE
BOILER



IPC
PUMP

SPECS



LARGE DIAMETER WHEELS
IN ORDER TO FACILITATE
MOVEMENTS



ACCESSORY STORAGE
COMPARTMENT



STURDY AND LARGE TANK
IN ROTOMOULDED PLASTIC
MATERIAL



PW-H28/4

PW-H28

PW-H28 I1308A M
WITHOUT PRESSURE ADJUSTMENT

TECHNICAL DATA

3 WHEELS

Code

4 WHEELS

Code

PERFORMANCE

Operating pressure	bar/Mpa	130/13
Flow rate	l/h	500
Outlet water temperature	°C	30-110
Power supply	Ph-V-Hz/A	1-230-50/12,3
Absorbed power	kW	2,7
Motor pole/rpm		2-2800
Remote control		ITS
Pump/head/pistons		Axial/brass/ceramic
Boiler thermal power	kW	37,8
Fuel consumption	kg/h	3,2
Fuel tank	l	18
Detergent tank	l	-
Detergent delivery		low pressure
Dimension (LxWxH)	cm	82x63x87
Weight	kg	75

IMMEDIATE TOTAL STOP VERSION

PW-H28 I1308A M

IDAC40680

PW-H28/4 I1308A M

IDAC40683

STANDARD EQUIPMENT

CODE: IPPR40017
HANDGRIP MV2009



CODE: UGLN11196
H.P. NOZZLE 1/4 15035



CODE: TBAP28305
HIGH PRESSURE HOSE 8 m



CODE: LCPR40037
EXTENSION P50
ZINC PLATED



OPTIONAL ACCESSORIES

CODE: LCPR29362
HYDROBRUSH LANCE



CODE: SPID24939
FIXED HYDROBRUSH LANCE



CODE: KTRI40303
HOSE REEL KIT



CODE: LCPR40040
FOAMER KIT 1 l



CODE: RCIN10810
HOSE COUPLING M22



CODE: KTRI29377
FEEDING KIT



CODE: TBAP23853
DRAIN KIT 10 m



CODE: KTRI29366
PLUNGER EJECTOR DEVICE



CODE: LCPR40104
EXTENSION P70 + TPR255
Ø 0,35



CODE: LCPR24943
SANDBLASTER KIT Ø 1,3 mm



CODE: PRCH40041
SAND BAG 25 Kg



CODE: LCLC49492
LANCE FOR WASHING
FLOORS Ø 0,35





IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - HOT WATER

PW-H28/4

STAINLESS STEEL COVER

PRESSURE

130 ÷ 170
bar

FLOW RATE

600 ÷ 800
l/h

ABSORBED POWER

2,7 ÷ 4,7
kW

**EXCLUSIVE
CHARACTERISTICS**

- ▶ BOILER IGNITION DELAY - IBD
- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ NOZZLE CLOGGED CONTROL - NCC
- ▶ FLOODING PREVENTION SYSTEM - FPS
- ▶ IPC TEMPERATURE STABILIZER - ATC



WITH NO-MARKING RUBBER WHEELS

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



DIY AND GARDENING



HEAVY INDUSTRY



INNOVATIONS



G6000™
CERAMIC
HIGH-TECH GUN



ALL
TERRAIN



MODERN
MODULAR
BUILD UP



IPC'S
EXCLUSIVE
BOILER



IPC
PUMP

SPECS



LARGE WHEELS IMPROVE
MANEUVERABILITY AND
EASE TRANSPORT



STAINLESS STEEL COVER



LANCE HOLDER WITH
LOCKING SYSTEM

TECHNICAL DATA

		PW-H28/4 D1310P4 M IDAC41124	PW-H28/4 D1713P T IDAC41125
Code			
PERFORMANCE			
Operating pressure	bar/Mpa	40-130/4-13	40-170/4-17
Flow rate	l/h	280-600	400-800
Outlet water temperature	°C	30-130	30-130
Power supply	Ph-V-Hz/A	1-230-50/12,3	3-400-50/9,1
Absorbed power	kW	2,7	4,7
Motor pole/rpm		4-1400	2-2800
Remote control		DTS	DTS
Pump/head/pistons		lpc plunger/brass/ceramic	lpc plunger/brass/ceramic
Boiler thermal power	kW	37,8	37,8
Fuel consumption	kg/h	3,2	3,2
Fuel tank	l	18	18
Detergent tank	l	-	-
Detergent delivery		low pressure	low pressure
Dimension (LxWxH)	cm	82x63x87	82x63x87
Weight	kg	87	90

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000



CODE: LCPR40087
EXTENSION P70 INOX



CODE: TBAP28305
H.P. HOSE 8 m



CODE: UGLN49986
H.P. NOZZLE 1/4 1504



OPTIONAL ACCESSORIES

CODE: LCPR29362
HYDROBRUSH LANCE



CODE: SPID24939
FIXED HYDROBRUSH LANCE



CODE: KTRI40303
HOSE REEL KIT



CODE: LCPR40040
FOAMER KIT 1 l



CODE: RCIN10810
HOSE COUPLING M22



CODE: KTRI29377
FEEDING KIT



CODE: TBAP23853
DRAIN KIT 10 m



CODE: KTRI29366
PLUNGER EJECTOR DEVICE



CODE: LCPR40103
EXTENSION P70 + TPR255 Ø0,4



CODE: LCPR14858
SANDBLASTER KIT Ø 1,4



CODE: PRCH40041
SAND BAG 25 kg



CODE: LCLC49492
LANCE FOR WASHING FLOORS Ø 0,35



CODE: LCLC41140
LANCE FOR WASHING FLOORS INOX



CODE: TBAP39120
NO-MARKING HIGH PRESSURE HOSE 10 m



CODE: TBAP39122
NO-MARKING HIGH PRESSURE HOSE 20 m



CODE: KTRI40316
MAINTENANCE KIT 500H - (FOR 1310)



CODE: KTRI40307
MAINTENANCE KIT 500H - (FOR 1713)





IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - HOT WATER



PW-H31 VALUE

PRESSURE

130 ÷ 170
bar

FLOW RATE

500 ÷ 800
l/h

ABSORBED POWER

2,5 ÷ 4,7
kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT PROPORTIONAL SWITCH OFF - IPSF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ LANCE NOZZLE CLOGGED CONTROL - NCC
- ▶ IGNITION BOILER DELAY - IBD
- ▶ FLOODING PREVENTION SYSTEM - FPS
- ▶ IPC TEMPERATURE STABILIZER - ATC



PW-H31
VALUE

PW-H31/4
VALUE

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



DIY AND GARDENING



HEAVY INDUSTRY



INNOVATIONS



AMSC™
ADVANCED
MULTIFUNCTION
SAFETY CONTROLS



CIRCULAR
DESIGN
& OPERATION



ALL
TERRAIN



MODERN
MODULAR
BUILD UP



IPC
PUMP



IPC'S
EXCLUSIVE
BOILER

SPECS



CONTROL PANEL WITH
INDICATOR LAMPS



USER FRIENDLY ACCESS TO
ADJUSTMENT



STURDY AND LARGE TANK
AND ACCESSORIES STORAGE

TECHNICAL DATA

3 WHEELS

Code	PW-H31 D1309P M	PW-H31 D1310P4 M	PW-H31 D1509P4 M	PW-H31 D1708P4 M	PW-H31 D1713P T
	IDAC41351	IDAC41352	IDAC41353	IDAC41354	IDAC41355
4 WHEELS	PW-H31/4 D1309P M	PW-H31/4 D1310P4 M	PW-H31/4 D1509P4 M	PW-H31/4 D1708P4 M	PW-H31/4 D1713P T
Code	IDAC41356	IDAC41357	IDAC41358	IDAC41359	IDAC41360

PERFORMANCE

Operating pressure	bar/Mpa	30-130/3-13	30-130/3-13	30-150/3-15	30-170/4-17	30-170/3-17
Flow rate	l/h	280-540	300-600	300-540	300-500	400-800
Outlet water temperature	°C	30-110	30-110	30-110	30-110	30-110
Power supply	Ph-V-Hz/A	1-230-50/11,5	1-230-50/11,5	1-230-50/11,5	1-230-50/11,5	3-400-50/9,1
Absorbed power	kW	2,5	2,7	2,7	2,7	4,7
Motor pole/rpm		2-2800	4-1400	4-1400	4-1400	2-2800
Remote control		DTS	DTS	DTS	DTS	DTS
Pump/head/pistons		lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic
Boiler thermal power	kW	37,8	37,8	37,8	37,8	37,8
Fuel consumption	Kg/h	3,2	3,2	3,2	3,2	3,2
Fuel tank	l	18	18	18	18	18
Detergent tank	l	-	-	-	-	-
Detergent delivery		low pressure	low pressure	low pressure	low pressure	low pressure
Dimension (LxWxH)	m	82x63x87	82x63x87	82x63x87	82x63x87	82x63x87
Weight	Kg	80	80	80	80	90

STANDARD EQUIPMENT

CODE: IPPR40031
HANDGRIP G4000
CERAMIC TECH



CODE: LCPR40013
EXTENSION P 70 -
HYPERJET 1/4F



CODE: UGLN49986
H.P. NOZZLE 1/4 1504 -
(FOR 1310/1713)



CODE: UGLN49985
H.P. NOZZLE 1/4 1504 -
(FOR 1509/1309)



CODE: UGLN75421
H.P. NOZZLE 1/4 15025 -
(FOR 1708)



CODE: TBAP40308
HIGH PRESSURE HOSE
10 m



OPTIONAL ACCESSORIES

CODE: LCPR29362
HYDROBRUSH LANCE



CODE: SPID24939
FIXED HYDROBRUSH LANCE



CODE: KTRI40303
HOSE REEL KIT



CODE: LCPR40040
FOAMER KIT 1 l



CODE: RCIN10810
HOSE COUPLING M22



CODE: KTRI29377
FEEDING KIT



CODE: TBAP23853
DRAIN KIT 10 m



CODE: KTRI29366
PLUNGER EJECTOR DEVICE



CODE: LCPR40103
EXTENSION P70 +
TPR255 Ø 0,4 - (FOR
1713/1310/1714)



CODE: LCPR40104
EXTENSION P70 + TPR255
Ø 0,35 - (FOR 1309/1509)



CODE: LCPR24943
SANDBLASTER KIT Ø 1,3 mm
(FOR 1309/1509/1708)



CODE: LCPR14858
SANDBLASTER KIT Ø 1,4 mm
(FOR 1310/1713)



CODE: PRCH40041
SAND BAG 25 Kg



CODE: LCLC49492
LANCE FOR WASHING
FLOORS Ø 0,35



CODE: LCPR40214
EXTENSION P70 Ø 0,30
(FOR 1708)



CODE: KTRI40637
MAINTENANCE KIT 500H
(FOR 1309)



CODE: KTRI40638
MAINTENANCE KIT 500H
(FOR 1310)



CODE: KTRI40641
MAINTENANCE KIT 500H
(FOR 1713)



CODE: KTRI40639
MAINTENANCE KIT 500H
(FOR 1509)



CODE: KTRI40640
MAINTENANCE KIT 500H
(FOR 1708)





IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - HOT WATER



PW-H61 VALUE

PRESSURE

150÷200
bar

FLOW RATE

800÷1150
l/h

ABSORBED POWER

5÷6,4
kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT PROPORTIONAL SWITCH OFF - IPSF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ LANCE NOZZLE CLOGGED CONTROL - NCC
- ▶ IGNITION BOILER DELAY - IBD
- ▶ WORKING HOURS COUNTER - WHC
- ▶ IPC TEMPERATURE STABILIZER - ATC
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ MAINTENANCE CHECK LED - MCL



PW-H61
VALUE

PW-H61/4
VALUE

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



DIY AND GARDENING



HEAVY INDUSTRY



INNOVATIONS



AMSC™
ADVANCED
MULTIFUNCTION
SAFETY CONTROLS



ALL
TERRAIN



DIAD
DIRECT INJECTION
DETERGENT AND
ANTI-SCALE



MODERN
MODULAR
BUILD UP



CIRCULAR
DESIGN
& OPERATION



IPC'S
EXCLUSIVE
BOILER



G6000™
CERAMIC
HIGH-TECH GUN



IPC
PUMP

SPECS



CONTROL PANEL WITH
INDICATOR LAMPS



USER FRIENDLY ACCESS TO
ADJUSTMENT AND LIQUID
REFILLING



NEW AND MORE RESISTANT
PLASTIC

TECHNICAL DATA

3 WHEELS

Code

PW-H61 D1813P4 T

IDAC41361

PW-H61 D1915P4 T

IDAC41362

PW-H61 D1517P4 RT

IDAC41377

PW-H61 D1719P4 T

IDAC41364

PW-H61 D2017P4 T

IDAC41363

4 WHEELS

Code

PW-H61/4 D1813P4 T

IDAC41365

PW-H61/4 D1915P4 T

IDAC41366

PW-H61/4 D1517P4 RT

IDAC41381

PW-H61/4 D1719P4 T

IDAC41368

PW-H61/4 D2017P4 T

IDAC41367

PERFORMANCE

Operating pressure	bar/Mpa	30-180/3-18	30-190/3-19	30-150/3-19	30-170/3-17	30-200/3-20
Flow rate	l/h	450-800	450-900	500-1000	600-1150	500-1000
Outlet water temperature	°C	30-110	30-110	30-110	30-110	30-110
Power supply	Ph-V-Hz/A	3-400-50/9,7	3-400-50/10,6	3-400-50/10,6	3-400-50/13,2	3-400-50/13,2
Absorbed power	kW	5	5	5	6,4	6,4
Motor pole/rpm		4-1400	4-1400	4-1400	4-1400	4-1400
Remote control		DTS	DTS	DTS	DTS	DTS
Pump/head/pistons		lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic
Boiler thermal power	kW	70	70	70	≥70	≥70
Fuel consumption	kg/h	5,8	5,8	5,8	5,8	5,8
Fuel tank	l	25	25	25	25	25
Detergent tank	l	22	22	22	22	22
Detergent delivery		high pressure	high pressure	high pressure	high pressure	high pressure
Dimension (LxWxH)	cm	110x70x90	110x70x90	110x70x90	110x70x90	110x70x90
Weight	kg	120	122	122	140	140

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000



CODE: LCPR40087
EXTENSION P70 - INOX



CODE: UGLN49986
H.P. NOZZLE 1/4 1504
(FOR 1813)



CODE: UGLN02294
H.P. NOZZLE 1/4 15055 -
(FOR 1517)



CODE: UGLN49987
H.P. NOZZLE 1/4 15045
(FOR 1915/2017)



CODE: UGLN49996
H.P. NOZZLE 1/4 2507 -
(FOR 1719)



CODE: -
ANTI-SCALE TREATMENT
M421 1 Kg



CODE: TBAP40308
HIGH PRESSURE HOSE 10 m
(FOR 1813/1915)



CODE: TBAP40309
HIGH PRESSURE HOSE 10 m
(FOR 1517/1719/2017)



OPTIONAL ACCESSORIES

CODE: SPID24939
FIXED HYDROBRUSH
LANCE P70



CODE: LCLC41140
LANCE FOR WASHING
FLOORS INOX



CODE: LCLC49494
LANCE FOR WASHING
FLOORS Ø 0,55 - (FOR 1517)



CODE: LCLC49493
LANCE FOR WASHING
FLOORS Ø 0,45 - (FOR
1813/1915/2017)



CODE: KTRI40235
HOSE REEL KIT



CODE: RCIN10810
HOSE COUPLING M22



CODE: TBAP23853
DRAIN KIT 10 m -
(FOR 1813/1915)



CODE: TBAP24406
DRAIN KIT 20 m - M22 -
(FOR 1517/1719/2017)



CODE: LCPR40103
EXTENSION P70 TPR255
Ø 0,40 - (FOR 1813)



CODE: LCPR40135
EXTENSION P70 TPR255 Ø
0,45 - (FOR 1915/2017)



CODE: LCPR40182
EXTENSION P70 TPR255
Ø 0,55 - (FOR 1517)



CODE: LCPR88522
EXTENSION P70 S458
Ø 0,65 - (FOR 1719)



CODE: LCPR14859
SANDBLASTER KIT D.1,5 -
(FOR 1813/1915/2017)



CODE: LCPR14861
SANDBLASTER KIT Ø 2,0 -
(FOR 1719)



CODE: LCPR13557
SANDBLASTER KIT D.1,6 -
(FOR 1517)



CODE: PRCH40041
SAND BAG 25 Kg



CODE: PRCH40039
ANTI-SCALE TREATMENT
M421 1 Kg X 6



CODE: PRCH40040
ANTI-SCALE TREATMENT
M421 10 Kg



CODE: KTRI40431
ANTI-SCALE TREATMENT
M421 10 Kg



CODE: KTRI40642
MAINTENANCE KIT 500H
(FOR 1813)



CODE: KTRI40643
MAINTENANCE KIT 500H
(FOR 1915)



CODE: KTRI40644
MAINTENANCE KIT 500H
(FOR 1517)



CODE: KTRI40645
MAINTENANCE KIT 500H
(FOR 1719)



CODE: KTRI40646
MAINTENANCE KIT 500H
(FOR 2017)





IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - HOT WATER



PW-H61 PREMIUM

PRESSURE

150÷200
bar

FLOW RATE

800÷1150
l/h

ABSORBED POWER

5÷6,4
kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT PROPORTIONAL SWITCH OFF - IPSF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ LANCE NOZZLE CLOGGED CONTROL - NCC
- ▶ IGNITION BOILER DELAY - IBD
- ▶ WORKING HOURS COUNTER - WHC
- ▶ DIGITAL TEMPERATURE STABILIZER CONTROL - DTSC
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ ANTISCALE LEVEL CONTROL - ALC
- ▶ FUEL LEVEL CONTROL - FLC
- ▶ MAINTENANCE CHECK LED - MCL
- ▶ LED INDICATOR LIGHT REACHING TEMPERATURE - TL



PW-H61
PREMIUM

PW-H61/4
PREMIUM

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



DIY AND GARDENING



HEAVY INDUSTRY



INNOVATIONS



AMSC™
ADVANCED
MULTIFUNCTION
SAFETY CONTROLS



DIAD
DIRECT INJECTION
DETERGENT AND
ANTI-SCALE



CIRCULAR
DESIGN
& OPERATION



DIGITAL
DISPLAY
DD



IPC
PUMP



G6000™
CERAMIC
HIGH-TECH GUN



ALL
TERRAIN



MODERN
MODULAR
BUILD UP



IPC'S
EXCLUSIVE
BOILER

SPECS



CONTROL PANEL WITH
INDICATOR LAMPS AND
DISPLAY



USER FRIENDLY ACCESS TO
ADJUSTMENT AND LIQUID
REFILLING



NEW AND MORE RESISTANT
PLASTIC

TECHNICAL DATA

3 WHEELS

		PW-H61P D1813P4 T	PW-H61P/4 D1915P4 T	PW-H61P/4 D1517P4RT	PW-H61P D1719P4 T	PW-H61P D2017P4 T
Code		IDAC41369	IDAC41370	IDAC41385	IDAC41372	IDAC41371

4 WHEELS

		PW-H61/4PD1813P4T	PW-H61/4PD1915P4T	PW-H61/4PD1517P4RT	PW-H61/4PD1719P4T	PW-H61/4PD2017P4T
Code		IDAC41373	IDAC41374	IDAC41389	IDAC41376	IDAC41375

PERFORMANCE

Operating pressure	bar/Mpa	30-180/3-18	30-190/3-19	30-150/3-15	30-170/3-17	30-200/3-20
Flow rate	l/h	450-800	450-900	500-1000	600-1150	500-1000
Outlet water temperature	°C	30-140	30-140	30-140	30-140	30-140
Power supply	Ph-V-Hz/A	3-400-50/9,7	3-400-50/10,6	3-400-50/10,6	3-400-50/13,2	3-400-50/13,2
Absorbed power	kW	5	5	5	6,4	6,4
Motor pole/rpm		4-1400	4-1400	4-1400	4-1400	4-1400
Remote control		DTS	DTS	DTS	DTS	DTS
Pump/head/pistons		lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic
Boiler thermal power	kW	70	70	70	≥70	≥70
Fuel consumption	kg/h	5,8	5,8	5,8	5,8	5,8
Fuel tank	l	25	25	25	25	25
Detergent tank	l	22	22	22	22	22
Detergent delivery		high pressure	high pressure	high pressure	high pressure	high pressure
Dimension (LxWxH)	cm	110x70x90	110x70x90	110x70x90	110x70x90	110x70x90
Weight	kg	120	122	122	140	140

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000



CODE: LCPR40087
EXTENSION P70 - INOX



CODE: UGLN49986
H.P. NOZZLE 1/4 1504
(FOR 1813)



CODE: UGLN02294
H.P. NOZZLE 1/4 15055 -
(FOR 1517)



CODE: UGLN49987
H.P. NOZZLE 1/4 15045
(FOR 1915/2017)



CODE: UGLN49996
H.P. NOZZLE 1/4 2507 -
(FOR 1719)



CODE: -
ANTI-SCALE TREATMENT
M421 1 Kg



CODE: TBAP40308
HIGH PRESSURE HOSE 10 m
(FOR 1813/1915)



CODE: TBAP40309
HIGH PRESSURE HOSE 10 m
(FOR 1517/1719/2017)



OPTIONAL ACCESSORIES

CODE: SPID24939
FIXED HYDROBRUSH
LANCE P70



CODE: LCLC41140
LANCE FOR WASHING
FLOORS INOX



CODE: LCLC49494
LANCE FOR WASHING
FLOORS Ø 0,55 - (FOR 1517)



CODE: LCLC49493
LANCE FOR WASHING
FLOORS Ø 0,45 - (FOR
1813/1915/2017)



CODE: KTRI40235
HOSE REEL KIT



CODE: RCIN10810
HOSE COUPLING M22



CODE: TBAP23853
DRAIN KIT 10 m -
(FOR 1813/1915)



CODE: TBAP24406
DRAIN KIT 20 m - M22 -
(FOR 1517/1719/2017)



CODE: LCPR40103
EXTENSION P70 TPR255
Ø 0,40 - (FOR 1813)



CODE: LCPR40135
EXTENSION P70 TPR255 Ø
0,45 - (FOR 1915/2017)



CODE: LCPR40182
EXTENSION P70 TPR255
Ø 0,55 - (FOR 1517)



CODE: LCPR88522
EXTENSION P70 S458
Ø 0,65 - (FOR 1719)



CODE: LCPR14859
SANDBLASTER KIT D.1,5 -
(FOR 1813/1915/2017)



CODE: LCPR14861
SANDBLASTER KIT Ø 2,0 -
(FOR 1719)



CODE: LCPR13557
SANDBLASTER KIT D.1,6 -
(FOR 1517)



CODE: PRCH40041
SAND BAG 25 Kg



CODE: PRCH40039
ANTI-SCALE TREATMENT
M421 1 Kg X 6



CODE: KTRI40431
ANTI-SCALE TREATMENT
M421 10 Kg



CODE: KTRI40642
MAINTENANCE KIT 500H
(FOR 1813)



CODE: KTRI40643
MAINTENANCE KIT 500H
(FOR 1915)



CODE: KTRI40644
MAINTENANCE KIT 500H
(FOR 1517)



CODE: KTRI40645
MAINTENANCE KIT 500H
(FOR 1719)



CODE: KTRI40646
MAINTENANCE KIT 500H
(FOR 2017)





IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - HOT WATER

PW-H90*

PRESSURE

150÷190

bar

FLOW RATE

1300

l/h

ABSORBED POWER

7,1÷8,5

kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ NOZZLE CLOGGED CONTROL - NCC
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ ANTI-SCALE LEVEL CONTROL - ALC
- ▶ FUEL LEVEL CONTROL - FLC



* BASIC VERSION

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



DIY AND GARDENING



HEAVY INDUSTRY



INNOVATIONS



G6000™
CERAMIC
HIGH-TECH GUN



IPC'S
EXCLUSIVE
BOILER



IPC
PUMP



M421
ANTI-SCALE

SPECS



CONNECTION BETWEEN PUMP AND MOTOR IS PROVIDED WITH FLEXIBLE COUPLING



ELECTRIC PANEL IS PROVIDED WITH A TRANSPARENT COVER IN ORDER TO PROTECT IT FROM SPASHES AND DIRT



ERGONOMIC HANDLE FOR EASY CONVENIENT TRANSPORT

TECHNICAL DATA

		WITHOUT HOSE REEL	
		PW-H90 D1521P T	PW-H90 D1921P T
Code		IDAC40361	IDAC40362
PERFORMANCE			
Operating pressure	bar/Mpa	30-150/4-15	30-190/4-19
Flow rate	l/h	650-1300	650-1300
Outlet water temperature	°C	30-140	30-140
Power supply	Ph-V-Hz/A	3-400-50/13	3-400-50/16
Absorbed power	kW	7,1	8,5
Motor pole/rpm		4-1400	4-1400
Remote control		DTS	DTS
Pump/head/pistons		IPC plunger/brass/ceramic	IPC plunger/brass/ceramic
Boiler thermal power	kW	85,5	85,5
Fuel consumption	kg/h	7,6	7,6
Fuel tank	l	30	30
Detergent tank	l	16	16
Detergent delivery		high pressure	high pressure
Dimension (LxWxH)	cm	131x77x95	131x77x95
Weight	kg	175	182

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000



CODE: LCPR40160
EXTENSION PD70 INOX 0°



CODE: UGLN49997
H.P. NOZZLE 1/4 25075
(FOR 1521 - 2PCS)



CODE: UGLN49996
H.P. NOZZLE 1/4 2507
(FOR 1921- 2PCS)



CODE: TBAP40009
HIGH PRESSURE HOSE
10 m



OPTIONAL ACCESSORIES

CODE: LCPR29360
MUDGUARD LANCE - P90



CODE: LCPR24906
LANCE WITH DOUBLE
NOZZLE HOLDER - P70



CODE: LCPR29363
STEAM LANCE - P70



CODE: LCLC41140
LANCE FOR WASHING
FLOORS



CODE: RCIN10810
HOSE COUPLING M22



CODE: LCPR14860
SANDBLASTER KIT Ø 1,7 mm
(FOR 1921)



CODE: PRCH40041
SAND BAG 25 Kg



CODE: LCPR40088
EXTENSION P70 -
TURBO 0.80



CODE: TBAP24406
DRAIN KIT 20 m



CODE: PRCH40039
ANTI-SCALE TREATMENT
M421 1 Kg X 6



CODE: PRCH40040
ANTI-SCALE TREATMENT
M421 10 Kg



CODE: KTRI40433
MAINTENANCE KIT 500H





IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - HOT WATER



PW-H101 VALUE

PRESSURE

200÷250
bar

FLOW RATE

900÷1300
l/h

ABSORBED POWER

7,7÷8,5
kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT PROPORTIONAL SWITCH OFF - IPSF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ LANCE NOZZLE CLOGGED CONTROL - NCC
- ▶ IGNITION BOILER DELAY - IBD
- ▶ WORKING HOURS COUNTER - WHC
- ▶ FLOODING PREVENTION SYSTEM - FPS
- ▶ FUEL LEVEL CONTROL - FLC
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ IPC TEMPERATURE STABILIZER - ATC
- ▶ MAINTENANCE CHECK LED - MCL



PW-H101
VALUE

PW-H101/4
VALUE

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



HEAVY INDUSTRY



INNOVATIONS



AMSC™
ADVANCED
MULTIFUNCTION
SAFETY CONTROLS



ALL
TERRAIN



DIAD
DIRECT INJECTION
DETERGENT AND
ANTI-SCALE



MODERN
MODULAR
BUILD UP



CIRCULAR
DESIGN
& OPERATION



IPC'S
EXCLUSIVE
BOILER



G6000™
CERAMIC
HIGH-TECH GUN



IPC
PUMP

SPECS



CONTROL PANEL WITH
INDICATOR LAMPS



USER FRIENDLY ACCESS TO
ADJUSTMENT AND LIQUID
REFILLING



NEW AND MORE RESISTANT
PLASTIC

TECHNICAL DATA

3 WHEELS

Code

PW-H101 D2021P T

IDAC41379

PW-H101 D2515P T

IDAC41380

4 WHEELS

Code

PW-H101/4 D2021P T

IDAC41383

PW-H101/4 D2515P T

IDAC41384

PERFORMANCE

Operating pressure	bar/Mpa	30-200/3-20	30-250/3-25
Flow rate	l/h	650-1300	450-900
Outlet water temperature	°C	30-110	30-110
Power supply	Ph-V-Hz/A	3-400-50/16,6	3-400-50/16
Absorbed power	kW	8,5	7,7
Motor pole/rpm		4-1400	4-1400
Remote control		DTS	DTS
Pump/head/pistons		lpc plunger/brass/ceramic	lpc plunger/brass/ceramic
Boiler thermal power	kW	≤100	≥70
Fuel consumption	kg/h	7,4	5,8
Fuel tank	l	25	25
Detergent tank	l	22	22
Detergent delivery		high pressure	high pressure
Dimension (LxWxH)	cm	110x70x90	110x70x90
Weight	kg	172	172

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000



CODE: LCPR40159
EXTENSION P70 INOX 0°



CODE: UGLN49986
H.P. NOZZLE 1/4 1504
(FOR 2515)



CODE: UGLN02303
H.P. NOZZLE 1/4 15065
(FOR 2021)



CODE: TBAP40256
HIGH PRESSURE HOSE 10 m
(FOR 2021)



CODE: TBAP40309
H.P. HOSE R1 10 m 5/16"



CODE: -
ANTI-SCALE TREATMENT
M421 1 Kg



OPTIONAL ACCESSORIES

CODE: LCPR29360
MUDGUARD LANCE - P90



CODE: LCPR24906
LANCE WITH DOUBLE
NOZZLE HOLDER - P70



CODE: SPID24939
FIXED HYDROBRUSH
LANCE P70



CODE: LCLC41140
LANCE FOR WASHING
FLOORS INOX



CODE: LCPR14860
SANDBLASTER KIT Ø 1,7 mm
(FOR 2021)



CODE: LCPR14858
SANDBLASTER KIT Ø 1,4 mm
(FOR 2515)



CODE: PRCH40041
SAND BAG 25 Kg



CODE: TBAP24406
DRAIN KIT 20 m
(FOR 2021)



CODE: LCPR40103
EXTENSION P70 + TPR255
Ø 0,4 (FOR 2515)



CODE: LCPR40171
EXTENSION P70 + R.J.255
Ø0,65 (FOR 2021)



CODE: LCPR29363
STEAM LANCE - P70



CODE: KTRI40341
HOOSE REEL KIT



CODE: PRCH40039
ANTI-SCALE TREATMENT
M421 1 Kg X6



CODE: PRCH40040
ANTI-SCALE TREATMENT
M421 10 Kg



CODE: KTRI40647
MAINTENANCE KIT 500H
(FOR 2021)



CODE: KTRI40648
MAINTENANCE KIT 500H
(FOR 2515)





IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - HOT WATER



PW-H101 PREMIUM

PRESSURE

200÷250
bar

FLOW RATE

900÷1300
l/h

ABSORBED POWER

7,7÷8,5
kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT PROPORTIONAL SWITCH OFF - IPSF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ LANCE NOZZLE CLOGGED CONTROL - NCC
- ▶ IGNITION BOILER DELAY - IBD
- ▶ WORKING HOURS COUNTER - WHC
- ▶ FLOODING PREVENTION SYSTEM - FPS
- ▶ FUEL LEVEL CONTROL - FLC
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ ANTISCALE LEVEL CONTROL - ALC
- ▶ DIGITAL TEMPERATURE STABILIZER CONTROL - DTSC
- ▶ MAINTENANCE CHECK LED - MCL
- ▶ INFRARED FLAME CONTROL SYSTEM - FCS
- ▶ LED INDICATOR LIGHT REACHING TEMPERATURE TL



PW-H101
PREMIUM

PW-H101/4
PREMIUM

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



HEAVY INDUSTRY



INNOVATIONS



AMSC™
ADVANCED
MULTIFUNCTION
SAFETY CONTROLS



DIAD
DIRECT INJECTION
DETERGENT AND
ANTI-SCALE



CIRCULAR
DESIGN
& OPERATION



DIGITAL
DISPLAY
DD



IPC
PUMP



G6000™
CERAMIC
HIGH-TECH GUN



ALL
TERRAIN



MODERN
MODULAR
BUILD UP



IPC'S
EXCLUSIVE
BOILER

SPECS



CONTROL PANEL WITH
INDICATOR LAMPS AND
DISPLAY



BOILER CAN BE OPENED
FROM THE TOP FOR AN EASY
CLEANING



EASILY ACCESSIBLE
ANTISCALE TANK

TECHNICAL DATA

3 wheels

Code

4 wheels

Code

PERFORMANCE

		PW-H101P D2021P T IDAC41387	PW-H101P D2515P T IDAC41388
		PW-H101/4P D2021P T IDAC41391	PW-H101/4P D2515P T IDAC41392
Operating pressure	bar/Mpa	30-200	30-250/3-25
Flow rate	l/h	650-1300	450-900
Outlet water temperature	°C	30-140	30-140
Power supply	Ph-V-Hz/A	3-400-50/16,6	3-400-50/16
Absorbed power	kW	8,5	7,7
Motor pole/rpm		4-1400	4-1400
Remote control		DTS	DTS
Pump/head/pistons		lpc plunger/brass/ceramic	lpc plunger/brass/ceramic
Boiler thermal power	kW	≤100	≥70
Fuel consumption	kg/h	7,4	5,8
Fuel tank	l	25	25
Detergent tank	l	22	22
Detergent delivery		high pressure	high pressure
Dimension (LxWxH)	cm	110x70x90	110x70x90
Weight	kg	172	172

STANDARD EQUIPMENT

CODE: IPPR40025

H.P. HOSE R1 10M 5/16"



CODE: LCPR40159

EXTENSION P70 INOX 0°



CODE: UGLN49986

H.P. NOZZLE 1/4 1504
(FOR 2515)



CODE: UGLN02303

H.P. NOZZLE 1/4 15065
(FOR 2021)



CODE: TBAP40256

HIGH PRESSURE HOSE 10 m
(FOR 2021)



CODE: TBAP40309

HIGH PRESSURE HOSE 10 m
(FOR 2515)



CODE: -

ANTI-SCALE TREATMENT
M421 1 Kg



OPTIONAL ACCESSORIES

CODE: LCPR29360

MUDGUARD LANCE - P90



CODE: LCPR24906

LANCE WITH DOUBLE
NOZZLE HOLDER - P70



CODE: SPID24939

FIXED HYDROBRUSH
LANCE P70



CODE: LCLC41140

LANCE FOR WASHING
FLOORS INOX



CODE: LCPR14860

SANDBLASTER KIT Ø 1,7 mm
(FOR 2021)



CODE: LCPR14858

SANDBLASTER KIT Ø 1,4 mm
(FOR 2515)



CODE: PRCH40041

SAND BAG 25 Kg



CODE: TBAP24406

DRAIN KIT 20 m
(FOR 2021)



CODE: LCPR40103

EXTENSION P70 + TPR255
Ø0,4 (FOR 2515)



CODE: LCPR40171

EXTENSION P70 + R.J.255
Ø0,65 (FOR 2021)



CODE: LCPR29363

STEAM LANCE - P70



CODE: KTRI40341

HOSE REEL KIT



CODE: PRCH40039

ANTI-SCALE TREATMENT
M421 1 Kg X6



CODE: PRCH40040

ANTI-SCALE TREATMENT
M421 10 Kg



CODE: KTRI40647

MAINTENANCE KIT 500H
(FOR 2021)



CODE: KTRI40648

MAINTENANCE KIT 500H
(FOR 2515)





IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - HOT WATER

PW-H101 HTM



PRESSURE

200 bar

FLOW RATE

900 l/h

ABSORBED POWER

6,4 kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ NOZZLE CLOGGED CONTROL - NCC
- ▶ IGNITION BOILER DELAY - IBD
- ▶ WORKING HOURS COUNTER - WHC
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ DIGITAL TEMPERATURE STABILIZER CONTROL - DTSC
- ▶ ANTISCALE LEVEL CONTROL - ALC
- ▶ FUEL LEVEL CONTROL - FLC
- ▶ INFRARED FLAME CONTROL SYSTEM - FCS
- ▶ MAINTENANCE CHECKLED - MCL



PW-H101
HTM

PW-H101/4
HTM

SPECIAL MACHINE: 100°C MAX TEMPERATURE, BOTH HIGH AND LOW PRESSURE MODE

(WITH NO-MARKING RUBBER WHEELS / 3 WHEELS VERSION)

MOST FREQUENTLY USE

AGRICULTURE/FARMING



AUTOMOTIVE



CONSTRUCTION



RETAIL



LOGISTICS AND TRANSPORT



INDUSTRY



COMMUNITIES



WASTE MANAGEMENT



INNOVATIONS



AMSC™
ADVANCED
MULTIFUNCTION
SAFETY CONTROLS



CIRCULAR
DESIGN
& OPERATION



IPC
PUMP



DIGITAL
DISPLAY
DD



IPC'S
EXCLUSIVE
BOILER



G6000™
CERAMIC
HIGH-TECH GUN



ALL
TERRAIN



MODERN
MODULAR
BUILD UP



M421
ANTI-SCALE

SPECS



WARNING LAMP INFORMS WHEN TEMPERATURE IS BETWEEN 90-100°C



BOILER CAN BE OPENED FROM THE TOP FOR AN EASY CLEANING



COMPLETE WITH NON MARKING WHEELS FOR FLAT SURFACED (3 WHEELS VERSIONS)

TECHNICAL DATA

3 wheels

Code

4 wheels

Code

PERFORMANCE

Operating pressure	bar/Mpa	30-200/3-20
Flow rate	l/h	450-900
Outlet water temperature	°C	100
Power supply	Ph-V-Hz/A	3-400-50/13
Absorbed power	kW	6,4
Motor pole/rpm		4-1400
Remote control		DTS
Pump/head/pistons		lpc plunger/brass/ceramic
Boiler thermal power	kW	100
Fuel consumption	kg/h	7,4
Fuel tank	l	25
Detergent tank	l	22
Detergent delivery		high pressure
Dimension (LxWxH)	cm	110x70x90
Weight	kg	140

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000
WITH CERAMIC VALVE



CODE: LCPR40191
EXTENSION PD70 cm
INOX



CODE: UGLN05200
H.P. NOZZLE 1/4 1505



CODE: UGLN07790
L.P. NOZZLE 1/4 2513



CODE: TBAP40237
H.P. HOSE 10MT 1/4"
(NO-MARKING)



OPTIONAL ACCESSORIES

CODE: KTRI40341
HOSE REEL KIT



CODE: LCLC41140
LANCE FOR WASHING
FLOORS INOX



CODE: PRCH40039
ANTISCALE TREATMENT
M421 1Kg X6



CODE: PRCH40040
ANTISCALE TREATMENT
M421 10 Kg



CODE: KTRI40568
MAINTENANCE KIT 500H



CODE: RCIN10810
HOSE COUPLING M22



CODE: LCLC40027
STAINLESS STEEL FLOOR
CLEANER



CODE: UGLN49988
H.P. NOZZLE 1/4 25025



LANCE WITHOUT NOZZLES.
USE: NO. 2 CODE: UGLN49988
THAT SHOULD BE ORDERED
SEPARATELY



IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - HOT WATER



PW-H101 AUTOMATIC

PRESSURE

200 bar

FLOW RATE

1300 l/h

ABSORBED POWER

8,5 kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT PROPORTIONAL SWITCH OFF - IPSF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ LANCE NOZZLE CLOGGED CONTROL - NCC
- ▶ IGNITION BOILER DELAY - IBD
- ▶ WORKING HOURS COUNTER - WHC
- ▶ FLOODING PREVENTION SYSTEM - FPS
- ▶ FUEL LEVEL CONTROL - FLC
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ ANTISCALE LEVEL CONTROL - ALC
- ▶ DIGITAL TEMPERATURE STABILIZER CONTROL - DTSC
- ▶ MAINTENANCE CHECK LED - MCL
- ▶ INFRARED FLAME CONTROL SYSTEM - FCS
- ▶ LED INDICATOR LIGHT REACHING TEMPERATURE TL



MOST FREQUENTLY USE

AGRICULTURE/FARMING



AUTOMOTIVE



CONSTRUCTION



RETAIL



LOGISTICS AND TRANSPORT



INDUSTRY



COMMUNITIES



WASTE MANAGEMENT



INNOVATIONS



AMSC™
ADVANCED
MULTIFUNCTION
SAFETY CONTROLS



CIRCULAR
DESIGN
& OPERATION



IPC
PUMP



DIGITAL
DISPLAY
DD



AUTOMATIC
PRESSURE
WASHER



IPC'S
EXCLUSIVE
BOILER



G6000™
CERAMIC
HIGH-TECH GUN



ALL
TERRAIN



MODERN
MODULAR
BUILD UP



M421
ANTI-SCALE

SPECS



CONTROL PANEL WITH
INDICATOR LAMPS AND
DISPLAY



USER FRIENDLY ACCESS TO
ADJUSTMENT AND LIQUID
REFILLING



BOILER CAN BE OPENED
FROM THE TOP FOR AN EASY
CLEANING

TECHNICAL DATA

3 wheels

Code

4 wheels

Code

PERFORMANCE

Operating pressure	bar/Mpa	30-200
Flow rate	l/h	650-1300
Outlet water temperature	°C	30-140
Power supply	Ph-V-Hz/A	3-400-50/16,6
Absorbed power	kW	8,5
Motor pole/rpm		4-1400
Remote control		DTS
Pump/head/pistons		lpc plunger/brass/ceramic
Boiler thermal power	kW	≤100
Fuel consumption	kg/h	7,4
Fuel tank	l	25
Detergent tank	l	22
Detergent delivery		high pressure
Dimension (LxWxH)	cm	110x70x90
Weight	kg	172

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000



CODE: LCPR40159
EXTENSION P70 INOX 0°



CODE: UGLN02303
H.P. NOZZLE 1/4 15065



CODE: TBAP40309
HIGH PRESSURE HOSE 10 m



CODE: -
ANTI-SCALE TREATMENT
M421 1 Kg



OPTIONAL ACCESSORIES

CODE: LCPR29360
MUDGUARD LANCE - P90



CODE: SPID24939
FIXED HYDROBRUSH
LANCE P70



CODE: LCLC41140
LANCE FOR WASHING
FLOORS INOX



CODE: LCPR14860
SANDBLASTER KIT Ø 1,7 mm



CODE: PRCH40041
SAND BAG 25 Kg



CODE: TBAP24406
DRAIN KIT 20 m



CODE: LCPR40171
EXTENSION P70 + R.J.255
Ø0,65



CODE: LCPR29363
STEAM LANCE - P70



CODE: KTRI40341
HOSE REEL KIT



CODE: PRCH40039
ANTI-SCALE TREATMENT
M421 1 Kg X6



CODE: PRCH40040
ANTI-SCALE TREATMENT
M421 10 Kg





IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - HOT WATER

PW-H100 P

STAINLESS STEEL COVER

PRESSURE

170÷250
bar

FLOW RATE

900÷1300
l/h

ABSORBED POWER

5÷8,5
kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ LANCE NOZZLE CLOGGED CONTROL - NCC
- ▶ IGNITION BOILER DELAY - IBD
- ▶ WORKING HOURS COUNTER - WHC
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ DIGITAL TEMPERATURE STABILIZER CONTROL - DTSC
- ▶ ANTISCALE LEVEL CONTROL - ALC
- ▶ FUEL LEVEL CONTROL - FLC
- ▶ INFRARED FLAME CONTROL SYSTEM - FCS
- ▶ MAINTENANCE CHECK LED - MCL



STAINLESS STEEL COVER

WITH NO-MARKING RUBBER WHEELS

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



HEAVY INDUSTRY



INNOVATIONS



G6000™
CERAMIC
HIGH-TECH GUN



ALL
TERRAIN



MODERN
MODULAR
BUILD UP



IPC'S
EXCLUSIVE
BOILER



IPC
PUMP



M421
ANTI-SCALE

SPECS



LARGE WHEELS IMPROVE
MANEUVERABILITY AND EASE
TRANSPORT



STAINLESS STEEL COVER



HANDLE AND TANKS IN
ROTOMOULDED PLASTIC MATERIAL

TECHNICAL DATA

		PW-H100P D1915P T	PW-H100P D2017P T	PW-H100P D1721P T	PW-H100P D2021P T	PW-H100P D2515P T
Code		IDAC41126	IDAC41127	IDAC41128	IDAC41129	IDAC41130
PERFORMANCE						
Operating pressure	bar/Mpa	30-190/3-19	30-200/3-20	30-170/3-17	30-200/3-20	30-250/3-25
Flow rate	l/h	450-900	500-1000	650-1300	650-1300	450-900
Outlet water temperature	°C	30-140	30-140	30-140	30-140	30-140
Power supply	Ph-V-Hz/A	3-400-50/10,6	3-400-50/13,2	3-400-50/14,6	3-400-50/16,6	3-400-50/16
Absorbed power	kW	5	6,4	7,9	8,5	7,7
Motor pole/rpm		4-1400	4-1400	4-1400	4-1400	4-1400
Remote control		DTS	DTS	DTS	DTS	DTS
Pump/head/pistons		lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic
Boiler thermal power	kW	70	≥70	≤100	≤100	≥70
Fuel consumption	Kg/h	5,8	5,8	7,4	7,4	5,8
Fuel tank	l	25	25	25	25	25
Detergent tank	l	22	22	22	22	22
Detergent delivery		high pressure	high pressure	high pressure	high pressure	high pressure
Dimension (LxWxH)	cm	110x70x90	110x70x90	110x70x90	110x70x90	110x70x90
Weight	Kg	144,70	168,60	158	186,60	186,60

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000



CODE: LCPR40159
EXTENSION P70 INOX 0°
(FOR 1721/2021/2515)



CODE: LCPR40087
EXTENSION P70
INOX(FOR 1915/2017)



CODE: UGLN49987
H.P. NOZZLE 1/4 15045
(FOR 1915/2017)



CODE: UGLN49986
H.P. NOZZLE 1/4 1504
(FOR 2515)



CODE: UGLN49997
H.P. NOZZLE 1/4 25075
(FOR 1721)



CODE: UGLN02303
H.P. NOZZLE 1/4 15065
(FOR 2021)



CODE: TBAP40009
H.P. HOSE 10 m R2 5/16"
(FOR 1721/2021/2515)



CODE: TBAP25324
H.P. HOSE 10 m R1 5/16"
(FOR 1915/2017)



OPTIONAL ACCESSORIES

CODE: LCPR29360
MUDGUARD LANCE - P90



CODE: SPID24939
FIXED HYDRO BRUSH
LANCE



CODE: LCLC41140
LANCE FOR WASHING
FLOORS



CODE: LCPR29363
STEAM LANCE P70



CODE: LCPR14858
SANDBLASTER KIT D. 1,4
(FOR 2515)



CODE: LCPR14859
SANDBLASTER KIT D. 1,5
(FOR 1915/2017)



CODE: LCPR14860
SANDBLASTER KIT D. 1,7
(FOR 2021)



CODE: PRCH40041
SAND BAG 25 Kg



CODE: KTRI40341
HOSE REEL KIT



CODE: TBAP23853
DRAIN KIT 10 m
(FOR 1915/2017)



CODE: TBAP24406
DRAIN KIT 20 m
(FOR 1721/2021)



CODE: PRCH40039
ANTI-SCALE TREATMENT
M421 1 Kg X6



CODE: PRCH40040
ANTI-SCALE TREATMENT
M421 10 Kg



CODE: TBAP39120
NON-MARKING H.P.
HOSE R1 10 m 5/16"
(1915/2017/1721)



CODE: TBAP39121
NON-MARKING H.P. HOSE
R2 10 m 5/16"
(FOR 2021P4/2515P4)



CODE: TBAP39122
NON-MARKING H.P.
HOSE R1 20 m 5/16"
(1915/2017/1721)



CODE: TBAP39123
NON-MARKING H.P. HOSE
R2 20 m 5/16"
(FOR 2021P4/2515P4)



CODE: LCPR40135
EXTENSION P70 + TPR255
Ø0,45 - (FOR 1915/2017)



CODE: LCPR40103
EXTENSION P70 + TPR255
Ø0,4 - (FOR 2515)



CODE: LCPR40171
EXTENSION P70 + R.J. 255
Ø0,65 - (FOR 2021)



CODE: LCPR40170
EXTENSION P70 + R.J. 255
Ø0,75 - (FOR 1721)



CODE: KTRI40314
MAINTENANCE KIT 500H
(FOR 1915)



CODE: KTRI40431
MAINTENANCE KIT 500H
(FOR 2017)



CODE: KTRI40434
MAINTENANCE KIT 500H
(FOR 1721/2021)



CODE: KTRI40435
MAINTENANCE KIT 500H
(FOR 2515)





IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - HOT WATER

SKID FUEGO

PRESSURE

180 bar

FLOW RATE

1080 l/h

ENGINE POWER

11 Hp

EXCLUSIVE CHARACTERISTICS

- ▶ BY-PASS - BYP
- ▶ ENGINE THROTTLE CONTROL - RS
- ▶ BOILER IGNITION DELAY - IBD

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



HEAVY INDUSTRY



PETROL ENGINE

INNOVATIONS



G6000™
CERAMIC
HIGH-TECH GUN



IPC'S
EXCLUSIVE
BOILER



M421
ANTI-SCALE

SPECS



POWERFUL HONDA GX 340 LX
AIR COOLED 4 STROKE OHV
PETROL ENGINE



EPOXY POLYESTER POWDER
COATED TUBULAR FLAME-
TROLLEY



MOBILE UNITS OR TRUCK
MOUNTED

TECHNICAL DATA

		SKID FUEGO-H L1818PI P
Code	IDAC49710	
PERFORMANCE		
Operating pressure	bar/Mpa	70-180/7-18
Flow rate	l/h	680-1080
Outlet water temperature	°C	80-120
Engine type	Honda GX340 LX (gasoline)	
Engine power	Hp	11
Engine speed	Rpm	1800
Remote control	BY-PASS	
Pump/head/pistons	Plunger/brass/ceramic	
Boiler thermal power	kW	67
Fuel consumption	kg/h	5,6
Fuel tank	l	26
Detergent tank	l	optional (16 l)
Detergent delivery	high pressure	
Dimension (LxWxH)	cm	117x68x87
Weight	kg	235,4

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000



CODE: LCPR40159
EXTENSION P70 INOX 0°



CODE: UGLN49994
H.P. NOZZLE 1/4 2506



CODE: TBAP40009
HIGH PRESSURE HOSE 10 m



OPTIONAL ACCESSORIES

CODE: LCPR29360
MUDGUARD LANCE - P90



CODE: LCPR24906
LANCE WITH DOUBLE
NOZZLE HOLDER



CODE: LCPR29363
STEAM LANCE - P70



CODE: SPID24939
FIXED HYDROBRUSH
LANCE



CODE: LCPR29362
HYDROBRUSH LANCE



CODE: RCIN10810
HOSE COUPLINGS



CODE: TBAP24406
DRAIN KIT 20 m



CODE: LCPR88522
EXTENSION P70 TURBO
D. 0.65



CODE: KTRI37674
HOSE REEL KIT P 35-15
WALL



CODE: KTRI26685
TROLLEY KIT P 1-15
(WITH 3 WHEELS)

PICTURE
NOT
AVAILABLE

CODE: KTRI27587
HOSE REEL KIT P35-7
(FOR KTRI26685)

PICTURE
NOT
AVAILABLE

CODE: KTRI26686
TROLLEY KIT P 1-16
(WITH 4 WHEELS)

PICTURE
NOT
AVAILABLE

CODE: KTRI26688
HOSE REEL KIT P35-5 (FOR
KTRI26686)

PICTURE
NOT
AVAILABLE

CODE: KTRI26687
LANCE HOLDER KIT

PICTURE
NOT
AVAILABLE

CODE: KTRI26690
DETERGENT TANK

PICTURE
NOT
AVAILABLE

CODE: KTRI26689
DESCALING DEVICE

PICTURE
NOT
AVAILABLE

CODE: AVTB39119
STAINLESS STEEL HOSE
REEL



CODE: KTRI28914
ROTATING ARM



CODE: LCPR14860
SANDBLASTER KIT D.1,7



CODE: PRCH40041
SAND BAG 25 Kg



CODE: PRCH00039
ANTISCALE TREATMENT
M421 (1 Kg X 6)



CODE: PRCH00040
ANTISCALE TREATMENT
M421 10 Kg





STATIONARY

EXCLUSIVE TECHNOLOGIES	106
-------------------------------	-----

MLC-C	108
--------------	-----

ML CMP	110
---------------	-----

ML-C	112
-------------	-----

SML-C	114
--------------	-----

IWD-H	116
--------------	-----



IPC

BY TENNANT COMPANY

EXCLUSIVE TECHNOLOGIES

REMOTE CONTROLS

DELAYED TOTAL STOP (DTS)	Stops the machine 30 seconds after its last use
---------------------------------	---

SAFETY DEVICES

MICRO LEAKAGE CONTROL (MLC)	The machine stops in case of dangerous leakage in the high-pressure hydraulic circuit
------------------------------------	---

DRY RUNNING PROTECTION (DRP)	Stops the machine in case of lack of water
-------------------------------------	--

LANCE NOZZLE CLOGGED CONTROL (NCC)	Stops the machine when the nozzle is clogged
---	--

IGNITION BOILER DELAY (IBD)	Ensures low fume emission levels when the boiler is started
------------------------------------	---

WORKING HOUR COUNTER (WHC)	An electronic hour counter that shows the working hours of the machine
-----------------------------------	--

INTELLIGENT PROPORTIONAL SWITCHING OFF (IPSF)	Automatic total stop of the machine after a period of inactivity, which varies according to how long the machine has been used
--	--

INTELLIGENT AUTOMATIC SWITCH OFF (IASF)	This intelligent system automatically switches off the machine after 20 minutes of inactivity
--	---

INFRARED FLAME CONTROL SYSTEM (FCS)	This system stops the machine in case of boiler malfunction
--	---

CONTROLS

LIMESCALE/CORROSION PROTECTION UNIT (LCPU)	It protects the hot water machines against limescale and corrosion
---	--

FUEL LEVEL CONTROL (FLC)	Detects and reports the fuel lackage
---------------------------------	--------------------------------------

ANTI-SCALE LEVEL CONTROL (ALC)	Detects and reports the descaler lackage and stops the machine burner to prevent limescale deposits
---------------------------------------	---

FLOODING PREVENTION SYSTEM (FPS)	This system stops the machine after 60 minutes of continuous activity
---	---

EXCLUSIVE TECHNOLOGIES

	MLC-C	MLCMP	ML-C SML-C	IWD-H
	•	•	•	•
	•	•		•
		•		• (optional)
	•	•		•
				•
	•	•		
	•	•		
				•
				•
				•
				• (optional)
				• (optional)
	•	•	•	



IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - COLD WATER STATIONARY

MLC-C

DELAYED TOTAL STOP MODELS

PRESSURE

130÷210
bar

FLOW RATE

600÷1000
l/h

ABSORBED POWER

3÷6,4
kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ FLOODING PREVENTION SYSTEM - FPS
- ▶ NOZZLE CLOGGED CONTROL - NCC
- ▶ WORKING HOURS COUNTER - WHC
- ▶ INTELLIGENT PROPORTIONAL SWITCH OFF - IPSF
- ▶ DRY RUNNING PROTECTION - DRP



MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



DIY AND GARDENING



HEAVY INDUSTRY



INNOVATIONS



G6000™
CERAMIC
HIGH-TECH GUN



IPC
PUMP

SPECS



EQUIPPED WITH PAINTED
METAL PLATE FOR WALL
MOUNTING



PUMP WITH BRASS HEAD
AND THREE CERAMIC
PISTONS ENSURING
LONG-TERM LIFESPAN



PROFESSIONAL PRESSURE
GAUGE ENSURING A COSTANT
CONTROL OF WORKING
PRESSURE

TECHNICAL DATA

		MLC-C D1310P4 M	MLC-C D1813P T	MLC-C D1915P4 T	MLC-C D2117P4 T
Code		PPEL40079	PPEL40081	PPEL40083	PPEL40085
PERFORMANCE					
Operating pressure	bar/Mpa	30-130/3-13	30-180/3-18	30-190/3-19	30-210/3-21
Flow rate	l/h	300-600	400-800	450-900	480-1000
Inlet water max. temperature	°C	50	50	50	50
Power supply	Ph-V-Hz/A	1-230-50/14,3	3-400-50/8,6	3-400-50/9,4	3-400-50/12
Absorbed power	kW	3	4,7	5,1	6,4
Motor pole/rpm		4-1400	2-2800	4-1400	4-1400
Remote control		DTS	DTS	DTS	DTS
Pump/head/pistons		lpc plunger/brass/ceramic	lpc plunger/brass/ceramic	lpc plunger/brass/ceramic	lpc plunger/brass/ceramic
Detergent tank	l	-	-	-	-
Detergent delivery		-	-	-	-
Dimension (LxWxH)	cm	53x34x60	53x34x60	53x36x60	58x39x60
Weight	kg	31	40	45,2	50,2

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000



CODE: LCPR40087
EXTENSION P70 INOX



CODE: UGLN40000
**H.P. NOZZLE 1/4 15034
(FOR 1310)**



CODE: UGLN49987
**H.P. NOZZLE 1/4 15045
(FOR 1813/1915/2117)**



CODE: TBAP40256
HIGH PRESSURE HOSE 10 m



OPTIONAL ACCESSORIES

CODE: IPIP40022
GRIP G6000 BAYONET



CODE: LCLC40004
**EXTENSION P70 - INOX
BAYONET**



CODE: LCPR40039
**FOAMER KIT 1 l BAYONET
(FOR IPIP40022)**



CODE: LCPR40040
**FOAMER KIT M22 1 l
(FOR IPPR40025)**



CODE: LCPR14858
**SANDBASTER KIT Ø 1,4
(FOR 1310) TO USE WITH
IPPR40025**



CODE: LCPR14859
**SANDBASTER KIT Ø 1,5
(FOR 2117) TO USE WITH
IPPR40025**



CODE: LCPR13557
**SANDBASTER KIT Ø 1,6
(FOR 1813/1915) TO USE
WITH IPPR40025**



CODE: PRCH40041
SAND BAG 25 Kg



CODE: LCPR93178
**TURBO LANCE TTR-16
D.1,35 - (FOR 1310/1915)
TO USE WITH IPPR40025**



CODE: LCPR40016
**TURBO LANCE TTR-16 D.1,40
(FOR 1813) TO USE WITH
IPPR40025**



CODE: LCPR40054
**TURBO LANCE TPR-255
D.O.40 - (FOR 2117) TO
USE WITH IPPR40025**



CODE: KTRI40311
**MAINTENANCE KIT 500H
(FOR 1310)**



CODE: KTRI40317
**MAINTENANCE KIT 500H
(FOR 1813)**



CODE: KTRI40313
**MAINTENANCE KIT 500H
(FOR 1915)**



CODE: KTRI40338
**MAINTENANCE KIT 500H
(FOR 2117)**



CODE: KTRI40479
**KIT FOR HOT WATER
FEEDING VERSION
(FOR 1310P4/1915P4)**



CODE: KTRI40478
**KIT FOR HOT WATER
FEEDING VERSION
(FOR 1813P)**



CODE: KTRI40336
**KIT FOR HOT WATER
FEEDING VERSION
(FOR 2117P4)**





IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - COLD WATER STATIONARY

ML CMP

DELAYED TOTAL STOP MODELS

PRESSURE

130÷210
bar

FLOW RATE

600÷1000
l/h

ABSORBED POWER

3÷7,5
kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ FLOODING PREVENTION SYSTEM - FPS
- ▶ NOOZLE CLOG CONTROL - NCC
- ▶ WORKING HOURS COUNTER - WHC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ INTELLIGENT PROPORTIONAL SWITCHING OFF - IPSF



MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



DIY AND GARDENING



HEAVY INDUSTRY



INNOVATIONS



G6000™
CERAMIC
HIGH-TECH GUN



IPC
PUMP

SPECS



EASY ACCESS TO ALL
COMPONENTS FOR AN EASY
MAINTENANCE



HIGH CAPACITY INLET WATER
FILTER



BY-PASS VALVE IS PROVIDED
WITH 1 HOLDING METAL
PLATE IN ORDER TO PROTECT
IT FROM MECHANICAL STRESS

TECHNICAL DATA

		ML CMP D1310P4 M	ML CMP D1813P T	ML CMP D1915P4 T	ML CMP D2117P4 T
Code		IDAF40486	IDAF40535	IDAF40536	IDAF40537
PERFORMANCE					
Operating pressure	bar/Mpa	30-130/3-13	30-180/3-18	30-190/3-19	30-210/3-21
Flow rate	l/h	300-600	400-800	450-900	480-1000
Inlet water max. temperature	°C	50	50	50	50
Power supply	Ph-V-Hz/A	1-230-50/15	3-400-50/8,5	3-400-50/9,5	3-400-50/12
Absorbed power	kW	3	5,1	6,5	7,5
Motor pole/rpm		4-1400	2-2800	4-1400	4-1400
Remote control		DTS	DTS	DTS	DTS
Pump/head/pistons		lpc plunger/brass/ceramic	lpc plunger/brass/ceramic	lpc plunger/brass/ceramic	lpc plunger/brass/ceramic
Detergent tank	l	-	-	-	-
Detergent delivery		-	-	-	-
Dimension (LxWxH)	cm	59x39x29	59x39x29	59x39x29	59x39x29
Weight	kg	49,2	50	56,4	67

STANDARD EQUIPMENT

CODE: IPIP40022
GRIP G6000 BAYONET



CODE: LCLC40004
EXTENSION P70 INOX BAYONET



CODE: UGLN49990
H.P NOZZLE 1/4 25034 (FOR 1310)



CODE: UGLN49991
H.P NOZZLE 1/4 2504 (FOR 1813)



CODE: UGLN49987
H.P NOZZLE 1/4 15045 (FOR 1915/2117)



CODE: TBAP40486
HIGH PRESSURE HOSE 10 m (FOR 1310, 1813, 1915)



CODE: TBAP40256
HIGH PRESSURE HOSE 10 m (FOR 2117)



OPTIONAL ACCESSORIES

CODE: IPPR40025
HANDGRIP G6000



CODE: LCPR40087
EXTENSION P70 INOX



CODE: LCPR14858
SANDBLASTER KIT Ø 1,4 - (FOR 1310) TO BE USED WITH IPPR40025



CODE: LCPR14859
SANDBLASTER KIT Ø 1,5 - (FOR 2117) TO BE USED WITH IPPR40025



CODE: LCPR13557
SANDBLASTER KIT Ø 1,6 - (FOR 1813/1915) TO BE USED WITH IPPR40025



CODE: LCPR93178
TURBO LANCE TTR-16 D.1,35 - (FOR 1310/1915) TO BE USED WITH IPPR40025



CODE: LCPR40016
TURBO LANCE TTR-16 D.1,40 - (FOR 1813) TO BE USED WITH IPPR40025



CODE: LCPR40054
TURBO LANCE TPR-255 D.0,40 - (FOR 2117) TO BE USED WITH IPPR40025



CODE: KTRI37674
HOSE REEL KIT



CODE: AVTB39119
INOX HOSE REEL KIT



CODE: RCIN10810
HOSE COUPLINGS



CODE: KTRI28914
ROTATING ARM



CODE: LCPR40039
FOAMER KIT BAYONET



CODE: KTRI40311
MAINTENANCE KIT 500H (FOR 1310)



CODE: KTRI40317
MAINTENANCE KIT 500H (FOR 1813)



CODE: KTRI40313
MAINTENANCE KIT 500H (FOR 1915)



CODE: KTRI40338
MAINTENANCE KIT 500H (FOR 2117)



CODE: KTRI40479
KIT FOR HOT WATER FEEDING VERSION (FOR 1310P4/1915P4)



CODE: KTRI40478
KIT FOR HOT WATER FEEDING VERSION (FOR 1813P)



CODE: KTRI40336
KIT FOR HOT WATER FEEDING VERSION (FOR 2117P4)





IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - COLD WATER STATIONARY

ML-C

PRESSURE

150÷200
bar

FLOW RATE

900÷1260
l/h

ABSORBED POWER

5,5÷7,1
kW



EXCLUSIVE CHARACTERISTICS

► DELAYED TOTAL STOP - DTS

STAINLESS STEEL STRUCTURE

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



DIY AND GARDENING



HEAVY INDUSTRY



INNOVATIONS



G6000™
CERAMIC
HIGH-TECH GUN

SPECS



HIGH PRESSURE DETERGENT
DELIVERY DOSING SYSTEM



PROFESSIONAL PRESSURE
GAUGE ENSURING A COSTANT
CONTROL OF WORKING
PRESSURE



PUMP WITH BRASS HEAD
AND THREE CERAMIC
PISTONS ENSURING A LONG
TERM LIFESPAN

TECHNICAL DATA

		ML-C D1515PIT	ML-C D1521PIT	ML-C D1618PIT	ML-C D2015PIT
Code		IDAF40366	IDAF40367	IDAF40368	IDAF40369
PERFORMANCE					
Operating pressure	bar/Mpa	150/15	150/15	160/16	200/20
Flow rate	l/h	900	1260	1080	900
Inlet water max. temperature	°C	50	50	50	50
Power supply	Ph-V-Hz/A	3-400-50/9,4	3-400-50/14	3-400-50/14,1	3-400-50/13,2
Absorbed power	kW	5,5	7,1	7,1	7,1
Motor pole/rpm		4-1400	4-1400	4-1400	4-1400
Remote control		DTS	DTS	DTS	DTS
Pump/head/pistons		IPG plunger/brass/ceramic	IPG plunger/brass/ceramic	IPG plunger/brass/ceramic	IPG plunger/brass/ceramic
Detergent tank	l	optional [2x25 l]	optional [2x25 l]	optional [2x25 l]	optional [2x25 l]
Detergent delivery		high pressure	high pressure	high pressure	high pressure
Dimension (LxWxH)	cm	77x41x41	77x41x41	77x41x41	77x41x41
Weight	kg	85	90	92	92
Motor -pump coupling		elastic coupling	elastic coupling	elastic coupling	elastic coupling

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000



CODE: LCPR40087
EXTENSION P70 INOX (FOR 1515/2015)



CODE: LCPR40159
EXTENSION P70 INOX 0° - (FOR 1521/1618)



CODE: UGLN49987
H.P. NOZZLE 1/4 15045 (FOR 2015)



CODE: UGLN49993
H.P. NOZZLE 1/4 25055 (FOR 1515)



CODE: UGLN49997
H.P. NOZZLE 1/4 25075 (FOR 1521)



CODE: UGLN49995
H.P. NOZZLE 1/4 25065 (FOR 1618)



CODE: TBAP25324
H.P. HOSE R1 10 m 5/16" (FOR 1515)



CODE: TBAP40010
H.P. HOSE R2 10 m 3/8" (FOR 1521/1618)



CODE: TBAP40009
H.P. HOSE R2 10 m 5/16" (FOR 2015)



OPTIONAL ACCESSORIES

CODE: KTRI37674
HOSE REEL KIT



CODE: AVTB39119
INOX HOSE REEL KIT



CODE: LCPR39134
FOAMER HEAD P30



CODE: KTRI28914
ROTATING ARM



CODE: LCCL41140
LANCE FOR WASHING FLOORS INOX



CODE: KTRI28935
LANCE HOLDER



CODE: LCPR14859
SANDBLASTER KIT Ø 1,5 mm (FOR 2015)



CODE: LCPR14860
SANDBLASTER KIT Ø 1,7 mm (FOR 1515/1618)



CODE: PRCH40041
SAND BAG 25 Kg



CODE: KTRI39249
PAINTED WALL FIXING BRACKET



CODE: KTRI75463
STAINLESS STEEL WALL FIXING BRACKET



CODE: KTRI39250
PAINTED STAND



CODE: KTRI75370
STAINLESS STEEL STAND



CODE: KTRI39246
REMOTE CONTROL



CODE: KTRI75367
REMOTE CONTROL WITH DETERGENT CONTROL



CODE: KTRI39247
REMOTE CONTROL WITH DETERGENT CONTROL + WAX CONTROL



CODE: KTRI49930
KIT FOR HOT WATER FEEDING VERSION (FOR 1515/1521/2015)



CODE: KTRI49931
KIT FOR HOT WATER FEEDING VERSION (FOR 1618)



CODICE: MPVR13701
25L DETERGENT TANK 2 PCS



CODICE: LCPR41973
TURBO LANCE Ø 0.55 (FOR 1515)



CODE: LCPR40088
TURBO LANCE Ø 0.80 (FOR 1521)



CODE: LCPR88522
TURBO LANCE Ø 0.65 (FOR 1618)



CODE: LCPR40045
TURBO LANCE Ø 0.45 (FOR 2015)





IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - COLD WATER STATIONARY

SML-C

PRESSURE

100÷200
bar

FLOW RATE

1260÷1800
l/h

ABSORBED POWER

6,3÷9,4
kW



EXCLUSIVE CHARACTERISTICS

► DELAYED TOTAL STOP - DTS

MOST FREQUENTLY USE

AUTOMOTIVE

AGRICULTURE

CONSTRUCTION INDUSTRY

MUNICIPALITIES

DIY AND GARDENING

HEAVY INDUSTRY

STAINLESS STEEL STRUCTURE

INNOVATIONS



G6000™
CERAMIC
HIGH-TECH GUN

SPECS



HIGH PRESSURE DETERGENT
DELIVERY DOSING SYSTEM



PROFESSIONAL PRESSURE
GAUGE ENSURING A COSTANT
CONTROL OF WORKING
PRESSURE



STAINLESS STEEL WATER
TANK

TECHNICAL DATA

		SML-C D1030P T	SML-C D2021PIT
Code		IDAF40370	IDAF40372
PERFORMANCE			
Operating pressure	bar/Mpa	100/10	200/20
Flow rate	l/h	1800	1260
Inlet water max. temperature	°C	50	50
Power supply	Ph-V-Hz/A	3-400-50/12,8	3-400-50/17
Absorbed power	kW	6,3	9,4
Motor pole/rpm		4-1400	4-1400
Remote control		DTS	DTS
Pump/head/pistons		lpg plunger/brass/ceramic	lpg plunger/brass/ceramic
Detergent tank	l	optional (2x25)	optional (2x25)
Detergent delivery		high pressure	high pressure
Dimension (LxWxH)	cm	93x44x41	77x41x41
Weight	kg	80	120

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000



CODE: LCPR40159
EXTENSION P70 INOX 0°



CODE: UGLN02317
H.P. NOZZLE 1/4 2515
(FOR 1030)



CODE: UGLN49994
H.P. NOZZLE 1/4 2506
(FOR 2021)



CODE: TBAP40010
H.P. HOSE R2 10 m 5/16"



OPTIONAL ACCESSORIES

CODE: KTRI37674
HOSE REEL KIT



CODE: AVTB39119
INOX HOSE REEL KIT INOX



CODE: LCPR39134
FOAMER HEAD P30



CODE: KTRI28914
ROTATING ARM



CODE: LCLC41140
LANCE FOR WASHING
FLOORS INOX



CODE: KTRI28935
LANCE HOLDER



CODE: LCPR14860
SANDBLASTER KIT Ø 1,7 mm
(FOR 2021)



CODE: PRCH40041
SAND BAG 25 Kg



CODICE: MPVR13701
25L DETERGENT TANK
2 PCS



CODE: LCPR88522
EXTENSION P70 TURBO
D.065 (FOR 2021)



CODE: KTRI75461
PAINTED WALL FIXING
BRACKET



CODE: KTRI75369
PAINTED STAND



CODE: KTRI75462
STAINLESS STEEL WALL
FIXING BRACKET



CODE: KTRI75371
STAINLESS STEEL STAND



CODE: KTRI49930
KIT FOR HOT WATER
FEEDING VERSION



CODE: KTRI39246
REMOTE CONTROL



CODE: KTRI75367
REMOTE CONTROL WITH
DETERGENT CONTROL



CODE: KTRI39247
REMOTE CONTROL WITH
DETERGENT CONTROL +
WAX CONTROL





IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - HOT WATER STATIONARY

IWD-H

PRESSURE

150÷200

bar

FLOW RATE

900÷1260

l/h

ABSORBED POWER

6,5÷9,5

kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ NOZZLE CLOGGING CONTROL - NCC
- ▶ INFRARED FLAME CONTROL SYSTEM - FCS
- ▶ BOILER IGNITION DELAY - IBD
- ▶ FUEL LEVEL CONTROL - FLC (OPTIONAL)
- ▶ ANTI-SCALE LEVEL CONTROL - ALC (OPTIONAL)
- ▶ LIMESCALE/CORROSION PROTECT UNIT - LCPU
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF



MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



DIY AND GARDENING



HEAVY INDUSTRY



INNOVATIONS



G6000™
CERAMIC
HIGH-TECH GUN



IPC'S
EXCLUSIVE
BOILER

SPECS



STAINLESS STEEL
STRUCTURE



PILOT LIGHTS INDICATING
MACHINE AND BURNER
FUNCTIONING, PLUSH FLAME
CONTROL



PROFESSIONAL PRESSURE
GAUGE ENSURING A COSTANT
CONTROL OF WORKING
PRESSURE

TECHNICAL DATA

		MUR. IWD-H D1615PI T	MUR. IWD-H D1618PI T	MUR. IWD-H D2015PI T	MUR. IWD-H D1521PI T	MUR. IWD-H D2021PI T
Code		IDAC48037	IDAC48038	IDAC48039	IDAC48040	IDAC48041
PERFORMANCE						
Operating pressure	bar/Mpa	160/16	165/16,5	200/20	150/15	200/20
Flow rate	l/h	900	1080	900	1260	1260
Outlet water max. temperature	°C	30-120	30-120	30-120	30-120	30-145
Power supply	Ph-V-Hz/A	3-400-50/10,5	3-400-50/13	3-400-50/14	3-400-50/13	3-400-50/16
Absorbed power	kW	6,5	7,2	7,2	7,2	9,5
Motor pole/rpm		4-1400	4-1400	4-1400	4-1400	4-1400
Boiler thermal power	kW	67	88	88	88	88
Fuel consumption	l/h	5,8	7,4	7,4	7,4	7,4
Remote control		DTS	DTS	DTS	DTS	DTS
Fuel tank	l	optional (25 l)	optional (25 l)	optional (25 l)	optional (25 l)	optional (25 l)
Detergent tank	l	optional (2x25 l)	optional (2x25 l)	optional (2x25 l)	optional (2x25 l)	optional (2x25 l)
Detergent delivery		high pressure	high pressure	high pressure	high pressure	high pressure
Anti-scale tank	l	2	2	2	2	2
Pump/head/pistons		ipg plunger/brass/ceramic	ipg plunger/brass/ceramic	ipg plunger/brass/ceramic	ipg plunger/brass/ceramic	ipg plunger/brass/ceramic
Dimension (LxWxH)	cm	122x60x75	122x60x75	122x60x75	122x60x75	122x60x75
Weight	kg	185	190	186	186	210

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000



CODE: LCPR40087
EXTENSION P70 INOX
(FOR 1615/2015)



CODE: LCPR40159
EXTENSION P70 INOX 0°
(FOR 1618/1521/2021)



CODE: UGLN49993
H.P. NOZZLE 1/4 25055
(FOR 1615)



CODE: UGLN49995
H.P. NOZZLE 1/4 25065
(FOR 1618/2021)



CODE: UGLN49987
H.P. NOZZLE 1/4 15045
(FOR 2015)



CODE: UGLN49997
H.P. NOZZLE 1/4 15075
(FOR 1521)



CODE: TBAP40008
H.P. HOSE R1 10 m 5/16"
(FOR 1615/1618/1521)



CODE: TBAP40009
H.P. HOSE R2 10 m 5/16"
(FOR 2015)



CODE: TBAP40010
H.P. HOSE R2 10 m 3/8"
(FOR 2021)



OPTIONAL ACCESSORIES

CODE: AVTB39119
INOX HOSE REEL KIT



CODE: KTRI28914
ROTATING ARM



CODE: LCLC41140
LANCE FOR WASHING
FLOOR - INOX



CODE: LCPR29360
MUDGUARD LANCE



CODE: KTRI48114
REMOTE CONTROL WITH
DETERGENT + WAX CONTROL



CODE: KTRI48110
WALL FIXING BRACKET



CODE: KTRI48111
STAND



CODE: LCPR41973
TURBO LANCE Ø0,55 -
(FOR 1615)



CODE: LCPR88522
TURBO LANCE Ø0,65 -
(FOR 1618/2021)




CODE: LCPR40088
TURBO LANCE Ø0,80 -
(FOR 2015/1521)




CODE: LAFN48112
FLUE EXTENSION




CODE: LCPR13557
SANDBLASTER KIT Ø1,6 mm
(FOR 1615)



CODE: LCPR14860
SANDBLASTER KIT Ø1,7 mm
(FOR 1618/2021)



CODE: LCPR14859
SANDBLASTER KIT Ø1,5 mm
(FOR 2015)



CODE: PRCH40041
SAND BAG 25 Kg



CODE: MPVR13701
25 l FUEL TANK 1 PC



CODE: MPVR13701
25 l DETERGENT TANK
2 PCS





ELECTRICALLY HEATED BOILER

EXCLUSIVE TECHNOLOGIES	120
-------------------------------	-----

PW-E101	SPECIAL-HIGH TEMPERATURE	122
----------------	---------------------------------	-----

PW-E101	PLASTIC COVER	124
----------------	----------------------	-----

PW-E100	STAINLESS STEEL COVER	126
----------------	------------------------------	-----

IWD-E	128
--------------	-----



IPC

BY TENNANT COMPANY

EXCLUSIVE TECHNOLOGIES

REMOTE CONTROLS

INTELLIGENT AUTOMATIC SWITCH OFF (IASF)

Switch Off the machine after 20 minutes of no-use

INTELLIGENT PROPORTIONAL SWITCH OFF (IPSF)

Automatic stop of the machine after a period of inactivity, which varies according to how long the machine has been used.

MICRO LEAKAGE CONTROL (MLC)

It stops the machine in case of dangerous leakage in the HP hydraulic circuit

DRY RUNNING PROTECTION (DRP)

It stops the machine in case of water lack

LANCE NOZZLE CLOGGED CONTROL (NCC)

It stops the machine when the nozzle is clogged.

WORKING HOURS COUNTER (WHC)

Electronic hours counter indicating the working hours of the machine

MAINTENANCE CHECK LED (MCL)

This control device alerts you when maintenance is required

LIMESCALE/CORROSION PROTECTION UNIT (LCPU)

It protects the hot water machines from limescale deposits and corrosion

INTELLIGENT BOILER TEMPERATURE SETTING SYSTEMS (ITSS)

An extremely accurate electronic control device that ensures constant water temperature

CHEMICAL LEVEL CONTROL (CLC)

It detects and reports the fuel lackage

ANTI-SCALE LEVEL CONTROL (ALC)

It detects and reports the descaler lackage and stops the machine burner to prevent limescale deposits

FLOODING PREVENTION SYSTEM (FPS)

This system stops the machine after 60 minutes of continuous activity

FLOODING PREVENTION SYSTEM (FPS)

This system stops the machine after 60 minutes of continuous activity.



IPC

BY TENNANT COMPANY

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ LANCE NOZZLE CLOGGED CONTROL - NCC
- ▶ WORKING HOURS COUNTER - WHC
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ INTELLIGENT BOILER TEMPERATURE SETTING SYSTEM - ITSS
- ▶ ANTI-SCALE LEVEL CONTROL - ALC
- ▶ CHEMICAL LEVEL CONTROL - CLC
- ▶ FLOODING PREVENTION SYSTEM - FPS
- ▶ MAINTENANCE CHECK LED - MCL

MOST FREQUENTLY USE

INDUSTRY



AUTOMOTIVE



AGRICULTURE



MUNICIPALITIES



HIGH-PRESSURE WASHERS - HOT WATER (ELECTRIC BOILER)

PW-E101

ELECTRICALLY HEATED BOILER

PRESSURE

140
bar

FLOW RATE

240
l/h

ABSORBED POWER

14,1÷27,4
kW



SPECIAL - HIGH TEMPERATURE

WITH NO-MARKING RUBBER WHEELS

INNOVATIONS



AMSC™
ADVANCED
MULTIFUNCTION
SAFETY CONTROLS



CIRCULAR
DESIGN
& OPERATION



IPC
PUMP



DIGITAL
DISPLAY
DD



IPC'S
EXCLUSIVE
BOILER



G6000™
CERAMIC
HIGH-TECH GUN



ALL
TERRAIN



MODERN
MODULAR
BUILD UP

SPECS



LARGE WHEELS IMPROVE
MANEUVERABILITY AND
EASE TRANSPORT



CONTROL PANEL WITH
INDICATOR LAMPS AND
DISPLAY




3 STAGE HIGH EFFICIENCY
BOILER WITH AISI 316
STAINLESS STEEL STRUCTURE

TECHNICAL DATA


		PW-E101 D1404 P12 T	PW-E101 D1404 P24 T
Code		IDAC41398	IDAC41399
PERFORMANCE			
Operating pressure	bar/Mpa	30-140/3-14	30-140/3-14
Flow rate	l/h	240	240
Outlet water temperature max.	°C	80	80
Power supply	Ph-V-Hz/A	3-400-50/21,6	3-400-50/40
Absorbed power	kW	14,1	27,4
Motor pole/rpm		4-1400	4-1400
Remote control		DTS	DTS
Pump/head/pistons		lpc plunger/brass/ceramic	lpc plunger/brass/ceramic
Boiler thermal power	kW	12	24
Antiscale tank	l	25	25
Detergent tank	l	22	22
Detergent delivery		high pressure	high pressure
Dimension (LxWxH)	cm	110x70x90	110x70x90
Weight	Kg	113	113

STANDARD EQUIPMENT


CODE: IPPR40025
HANDGRIP G6000




CODE: LCPR40087
EXTENSION P70 INOX



CODE: TBAP40237
NO-MARKING H.P HOSE
10 m 1/4"



CODE: UGLN40042
H.P. NOZZLE 1/4" 1515



OPTIONAL ACCESSORIES

CODE: LCPR29360
MUDGUARD LANCE - P90



CODE: LCPR24906
LANCE WITH DOUBLE
NOZZLE HOLDER - P70



CODE: SPID24939
FIXED HYDROBRUSH
LANCE P70



CODE: LCLC41140
LANCE FOR WASHING
FLOORS INOX



CODE: TBAP23853
DRAIN KIT 10 m



CODE: TBAP24406
DRAIN KIT 20 m



CODE: KTRI40341
HOSE REEL KIT



CODE: TBAP39122
NO-MARKING HIGH
PRESSURE HOSE 20 m



CODE: PRCH40040
10 Kg ANTI-SCALE TANK



CODE: KTRI40542
REMOTE CONTROL



OPTIONAL ACCESSORY
HAS TO BE INSTALLED
DURING MANUFACTURING
PROCESS



IPC

BY TENNANT COMPANY

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ LANCE NOZZLE CLOGGED CONTROL - NCC
- ▶ WORKING HOURS COUNTER - WHC
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ INTELLIGENT BOILER TEMPERATURE SETTING SYSTEM - ITSS
- ▶ ANTI-SCALE LEVEL CONTROL - ALC
- ▶ CHEMICAL LEVEL CONTROL - CLC
- ▶ FLOODING PREVENTION SYSTEM - FPS
- ▶ MAINTENANCE CHECK LED - MCL

MOST FREQUENTLY USE

INDUSTRY



AUTOMOTIVE



AGRICULTURE



MUNICIPALITIES



HIGH-PRESSURE WASHERS - HOT WATER (ELECTRIC BOILER)

PW-E101

PRESSURE

170
bar

FLOW RATE

600÷720
l/h

ABSORBED POWER

16÷36,2
kW



WITH NO-MARKING RUBBER WHEELS

INNOVATIONS



AMSC™
ADVANCED
MULTIFUNCTION
SAFETY CONTROLS



CIRCULAR
DESIGN
& OPERATION



IPC
PUMP



DIGITAL
DISPLAY
DD



IPC'S
EXCLUSIVE
BOILER



G6000™
CERAMIC
HIGH-TECH GUN



ALL
TERRAIN



MODERN
MODULAR
BUILD UP

SPECS



LARGE WHEELS IMPROVE
MANEUVERABILITY AND EASE
TRANSPORT



CONTROL PANEL WITH
INDICATOR LAMPS AND
DISPLAY



3 STAGE HIGH EFFICIENCY
BOILER WITH AISI 316
STAINLESS STEEL STRUCTURE

TECHNICAL DATA

Code		PW-E101 D1710 P12 T IDAC41400	PW-E101 D1712 P24 T IDAC41401	PW-E101 D1712 P36 T IDAC41403
PERFORMANCE				
Operating pressure	bar/Mpa	30-170/3-17	30-170/3-17	30-170/3-17
Flow rate	l/h	450-600	450-720	450-720
Outlet water temperature	°C	80	80	80
Power supply	Ph-V-Hz/A	3-400-50/25	3-400-50/43,2	3-400-50/54
Absorbed power	kW	15,9	29	36,2
Motor pole/rpm		4-1400	4-1400	4-1400
Remote control		DTS	DTS	DTS
Pump/head/pistons		lpc plunger/brass/ceramic	lpc plunger/brass/ceramic	lpc plunger/brass/ceramic
Boiler thermal power	kW	12	24	36
Antiscale tank	l	25	25	25
Detergent tank	l	22	22	22
Detergent delivery		high pressure	high pressure	high pressure
Dimension (LxWxH)	cm	110x70x90	110x70x90	110x70x90
Weight	Kg	113	113	113

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000



CODE: LCPR40087
EXTENSION P70 INOX



CODE: TBAP40237
NO-MARKING H.P HOSE
10 m 1/4"



CODE: UGLN49986
H.P. NOZZLE 1/4" 1504 -
(FOR 24kW/ 36kW)



CODE: UGLN11196
H.P. NOZZLE 1/4" 15035 -
(FOR 12kW)



OPTIONAL ACCESSORIES

CODE: LCPR29360
MUDGUARD LANCE - P90



CODE: LCPR24906
LANCE WITH DOUBLE
NOZZLE HOLDER - P70



CODE: SPID24939
FIXED HYDROBRUSH
LANCE P70



CODE: LCLC41140
LANCE FOR WASHING
FLOORS INOX



CODE: TBAP23853
DRAIN KIT 10 m



CODE: TBAP24406
DRAIN KIT 20 m



CODE: KTRI40341
HOSE REEL KIT



CODE: TBAP39122
NO-MARKING HIGH
PRESSURE HOSE 20 m



CODE: PRCH40040
10 Kg ANTI-SCALE TANK



CODE: KTRI40542
REMOTE CONTROL



**OPTIONAL ACCESSORY
HAS TO BE INSTALLED
DURING MANUFACTURING
PROCESS**



IPC

BY TENNANT COMPANY

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ NOZZLE CLOGGING CONTROL - NCC
- ▶ WORKING HOURS COUNTER - WHC
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ INTELLIGENT BOILER TEMPERATURE SETTING SYSTEM - ITSS
- ▶ ANTI-SCALE LEVEL CONTROL - ALC
- ▶ CHEMICAL LEVEL CONTROL - CLC
- ▶ FLOODING PREVENTION SYSTEM - FPS
- ▶ MAINTENANCE CHECK LED - MCL

MOST FREQUENTLY USE

INDUSTRY



AUTOMOTIVE



AGRICULTURE



MUNICIPALITIES



HIGH-PRESSURE WASHERS - HOT WATER (ELECTRIC BOILER)

PW-E100

ELECTRICALLY HEATED BOILER STAINLESS STEEL SERIES

PRESSURE

170
bar

FLOW RATE

600÷720
l/h

ABSORBED POWER

16÷36,2
kW



WITH NO-MARKING RUBBER WHEELS

INNOVATIONS



G6000™
CERAMIC
HIGH-TECH GUN



IPC
PUMP



REDUCED
MAINTENANCE
COSTS



MSC™
MULTIFUNCTION
SAFETY
CONTROL



ALL
TERRAIN

SPECS



LARGE WHEELS IMPROVE
MANEUVERABILITY AND EASE
TRANSPORT



STAINLESS STEEL COVER



HANDLE AND TANKS IN
ROTOMOULDED PLASTIC MATERIAL

TECHNICAL DATA

Code		PW-E100 D1710 P12 T IDAC41131	PW-E100 D1712 P24 T IDAC41132	PW-E100 D1712 P36 T IDAC41133
PERFORMANCE				
Operating pressure	bar/Mpa	30-170/3-17	30-170/3-17	30-170/3-17
Flow rate	l/h	450-600	450-720	450-720
Outlet water temperature	°C	70	70	70
Power supply	Ph-V-Hz/A	3-400-50/25	3-400-50/43,2	3-400-50/53
Absorbed power	kW	15,9	29	36,2
Motor pole/rpm		4-1400	4-1400	4-1400
Remote control		DTS	DTS	DTS
Pump/head/pistons		lpc plunger/brass/ceramic	lpc plunger/brass/ceramic	lpc plunger/brass/ceramic
Boiler thermal power	kW	12	24	36
Antiscale tank	l	25	25	25
Detergent tank	l	22	22	22
Detergent delivery		high pressure	high pressure	high pressure
Dimension (LxWxH)	cm	110x70x90	110x70x90	110x70x90
Weight	Kg	133	133	133

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000



CODE: LCPR40087
EXTENSION P70 INOX



CODE: TBAP40237
NO-MARKING H.P HOSE
10 m 1/4"



CODE: UGLN49986
H.P. NOZZLE 1/4" 1504 -
(FOR 24kW/ 36kW)



CODE: UGLN11196
H.P. NOZZLE 1/4" 15035 -
(FOR 12kW)



OPTIONAL ACCESSORIES

CODE: LCPR29360
MUDGUARD LANCE - P90



CODE: LCPR24906
LANCE WITH DOUBLE
NOZZLE HOLDER - P70



CODE: SPID24939
FIXED HYDROBRUSH
LANCE P70



CODE: LCLC41140
LANCE FOR WASHING
FLOORS INOX



CODE: TBAP23853
DRAIN KIT 10 m



CODE: TBAP24406
DRAIN KIT 20 m



CODE: KTRI40341
HOSE REEL KIT



CODE: TBAP39122
NO-MARKING HIGH
PRESSURE HOSE 20 m



CODE: PRCH40040
10 Kg ANTI-SCALE TANK



CODE: KTRI40542
REMOTE CONTROL



**OPTIONAL ACCESSORY
HAS TO BE INSTALLED
DURING MANUFACTURING
PROCESS**



IPC

BY TENNANT COMPANY

HIGH-PRESSURE WASHERS - HOT WATER (ELECTRIC BOILER)

IWD-E

**ELECTRICALLY HEATED BOILER
STAINLESS STEEL SERIES**

PRESSURE

170
bar

FLOW RATE

600÷720
l/h

ABSORBED POWER

17,3÷35,8
kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ NOZZLE CLOGGING CONTROL - NCC
- ▶ WORKING HOURS COUNTER - WHC
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ INTELLIGENT BOILER TEMPERATURE SETTING SYSTEM - ITSS
- ▶ CHEMICAL LEVEL CONTROL - CLC
- ▶ FLOODING PREVENTION SYSTEM - FPS
- ▶ MAINTENANCE CHECK LED - MCL

- WITHOUT EXHAUST GAS
- GREATER EFFICIENCY WITHOUT USE FUEL



MOST FREQUENTLY USE

INDUSTRY



AUTOMOTIVE



AGRICULTURE



MUNICIPALITIES



INNOVATIONS



G6000™
CERAMIC
HIGH-TECH GUN



IPC
PUMP



MSC™
MULTIFUNCTION
SAFETY
CONTROL

SPECS



PROFESSIONAL PRESSURE GAUGE ENSURING A COSTANT CONTROL OF WORKING PRESSURE



HEAVY-DUTY STRUCTURE, WITH STAINLESS STEEL COVER



3 STAGE HIGH EFFICIENCY BOILER WITH AISI 316 STAINLESS STEEL STRUCTURE

TECHNICAL DATA

		IWD-E D1710 P12 T	IWD-E D1712 P24 T	IWD-E D1712 P36 T
Code		IDAC41134	IDAC41135	IDAC41136
PERFORMANCE				
Operating pressure	bar/Mpa	40-170/3-17	40-170/3-17	40-170/3-17
Flow rate	l/h	450-600	450-720	450-720
Outlet water temperature	°C	80	80	80
Power supply	Ph-V-Hz/A	3-400-50/27	3-400-50/44	3-400-50/53
Absorbed power	kW	17,3	29,5	35,8
Motor pole/rpm		4-1400	4-1400	4-1400
Remote control		DTS	DTS	DTS
Pump/head/pistons		lpc plunger/brass/ceramic	lpc plunger/brass/ceramic	lpc plunger/brass/ceramic
Boiler thermal power	kW	12	24	36
Antiscale tank	l	6	6	6
Detergent tank	l	25 (optional)	25 (optional)	25 (optional)
Detergent delivery		high pressure	high pressure	high pressure
Dimension (LxWxH)	cm	122x60x75	122x60x75	122x60x75
Weight	Kg	148,3	148,80	153,80

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000



CODE: LCPR40087
EXTENSION P70 INOX



CODE: TBAP40237
NO-MARKING H.P HOSE
10 m 1/4"



CODE: UGLN49986
H.P. NOZZLE 1/4" 1504 -
(FOR 24kW/ 36kW)



CODE: UGLN11196
H.P. NOZZLE 1/4" 15035 -
(FOR 12kW)



OPTIONAL ACCESSORIES

CODE: LCPR29360
MUDGUARD LANCE - P90



CODE: LCPR24906
LANCE WITH DOUBLE
NOZZLE HOLDER - P70



CODE: SPID24939
FIXED HYDROBRUSH
LANCE P70



CODE: LCLC41140
LANCE FOR WASHING
FLOORS INOX



CODE: TBAP23853
DRAIN KIT 10 m



CODE: TBAP24406
DRAIN KIT 20 m



CODE: TBAP39122
NO-MARKING HIGH
PRESSURE HOSE 20 m



CODE: PRCH40040
10 Kg ANTI-SCALE TANK



CODE: KTRI48111
PAINTED STEEL STAND



CODE: KTRI40538
STAINLESS STEEL STAND



CODE: KTRI40536
REMOTE COTROL



OPTIONAL ACCESSORY
HAS TO BE INSTALLED
DURING MANUFACTURING
PROCESS

CODE: MPVR13701
DETERGENT TANK 25 l



HOT WATER WEED REMOVAL SYSTEM

CARATTERISTICHE ESCLUSIVE	131
GREEN JET 7006	132
GREEN JET 1010	134
GREEN JET 7510	136

EXCLUSIVE TECHNOLOGIES

		GREEN JET
REMOTE CONTROLS		
DELAYED TOTAL STOP - DTS	It stops the machine after 1" seconds and after 5" seconds stops the machine burner.	•
SAFETY DEVICES		
INTELLIGENT AUTOMATIC SWITCH OFF - IASF	This intelligent system automatically switches off the machine after 20 minutes of inactivity.	•
DRY RUNNING PROTECTION - DRP	It stops the machine after 15" seconds in case of lack of water.	•
INFRARED FLAME CONTROL SYSTEM - FCS	This system stops the machine in case of boiler malfunction.	•
CONTROLS		
MAINTENANCE CHECK LED - MCL	This control device allerts you when maintenance is required (maintenance is scheduled every 150 hrs).	•
LIMESCALE/CORROSION PROTECTION UNIT - LCPU	It protects hot-water machines againts limescale and corrosion.	•
ANTISCALE LEVEL CONTROL - ALC	It detects and reports the descaler lackage and stops the machine burner to prevents limescale deposits. (Necessary to fill the tank with ant-scale liquid).	•



IPC

BY TENNANT COMPANY

WASHING AND WEED REMOVAL SYSTEM

GREEN JET 7006

PRESSURE

70 bar

FLOW RATE

360 l/h

ABSORBED POWER

1,5 kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ ANTISCALE LEVEL CONTROL - ALC
- ▶ MAINTENANCE CHECK LED - MCL

MOST FREQUENTLY USE

AGRICULTURE



PUBLIC WORK



MUNICIPALITIES



DIY AND GARDENING



INNOVATIONS



MSC™
MULTIFUNCTION
SAFETY
CONTROL



MODERN
MODULAR
BUILD UP



IPC'S
EXCLUSIVE
BOILER



M421
ANTI-SCALE

SPECS



LARGE DIAMETER WHEELS IN ORDER TO FACILITATE MOVEMENTS



ACCESSORY STORAGE COMPARTMENT



STURDY AND LARGE TANK IN ROTOMOULDED PLASTIC MATERIAL

TECHNICAL DATA

GREEN JET 7006 M

Code	IDAC41539	
PERFORMANCE		
Operating pressure	bar/Mpa	70/7,0
Flow rate	l/h	360
Outlet water temperature	°C	~100 (constant temperature)
Power supply	Ph-V-Hz	1-230-50
Absorbed power	kW	1,5
Motor pole	rpm	4- 1400
Remote control	DTS	
Pump/head/pistons	IPC plunger/brass/ceramic	
Boiler thermal power	kW	40
Fuel consumption	Kg/h	3,2
Fuel tank	l	18
Antiscale tank	l	2
Dimension (LxWxH)	cm	82x63x87
Weight	kg	75

STANDARD EQUIPMENT

CODE: IPPR40025 HANDGRIP G6000	CODE: LCPR40037 50 cm ZINC PLATED LANCE	CODE: UGLN49985 H.P. NOZZLE 1/4 1503	CODE: TBAP40229 H.P. HOSE 10 m 1/4''	CODE: LCLC40025 70 cm LANCE WITH SPRAY BAR (SPRAY BAR L= 50 cm)
				

OPTIONAL ACCESSORIES

CODE: PRCH40040
10 Kg ANTI-SCALE TANK





IPC

BY TENNANT COMPANY

HOT WATER WEED REMOVAL SYSTEM

GREEN JET 1010

PRESSURE

8
bar

FLOW RATE

600
l/h

ABSORBED POWER

0,8
kW

EXCLUSIVE TECNOLOGIES

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ ANTISCALE LEVEL CONTROL - ALC
- ▶ INFRARED FLAME CONTROL SYSTEM - FCS
- ▶ MAINTENANCE CHECK LED - MCL



MOST FREQUENTLY USE

AGRICULTURE



PUBLIC WORK



MUNICIPALITIES



INNOVATIONS



MSC™
MULTIFUNCTION
SAFETY
CONTROL



M421
ANTI-SCALE



REDUCED
MAINTENANCE
COSTS



IPC'S
EXCLUSIVE
BOILER

SPECS



STANDARD LIFTING HOOK TO
BE RAISED AND TRANSPORTED
ANYWHERE



DIRECT WATER SUPPLY OR
SUCTION WITH EXTERNAL
TANK



CONTROL PANEL SHOWING:
ON/OFF SWITCH, NETWORK
INDICATOR LIGHT, FLAME
CONTROL LIGHT, WARNING
LACK OF ANTISCALE, SERVICE
WARNING LIGHT (150 HRS),
READY WARNING LIGHT
(TEMPERATURE REACHED)

TECHNICAL DATA

GREEN JET 1010 M		
Code	GNVA40051	
Operating pressure	bar/Mpa	8/0,8
Flow rate	l/h	600
Outlet water temperature max	°C	~100
Power supply	Ph-V-Hz/A	1-230-50/3,8
Absorbed power	kW	0,8
Motor power	kW	0,55
Remote control	DTS	
Pump(type)	IPC volumetric rotary vane pump is self-priming, high-performance. The pump body is brass made	
Boiler thermal power	kW	74
Fuel consumption	Kg/h	5,2
Fuel tank	l	18
Antiscale tank	l	2
Dimension (LxWxH)	cm	83x109x100
Weight	Kg	142

STANDARD EQUIPMENT

CODE: IPPR40027
HANDGRIP ML330 +
EXTENSION 350 mm



CODE: LCLC40025
70 cm LANCE WITH SPRAY
BAR (SPRAY BAR L= 50 cm)



CODE: TBAP39122
H.P. HOSE 20 m
(NO-MARKING)



OPTIONAL

CODE: PRCH40040
ANTI-SCALE TREATMENT
M421 10 Kg





IPC

BY TENNANT COMPANY

HOT WATER WEED REMOVAL SYSTEM

GREEN JET 7510

PRESSURE

75
bar

FLOW RATE

600
l/h

ABSORBED POWER

1,9
kW

EXCLUSIVE TECNOLOGIES

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ ANTISCALE LEVEL CONTROL - ALC
- ▶ INFRARED FLAME CONTROL SYSTEM - FCS
- ▶ MAINTENANCE CHECK LED - MCL

MOST FREQUENTLY USE

AGRICULTURE



PUBLIC WORK



MUNICIPALITIES



SPECIAL APPLICATIONS - CLEANING, WASHING AND WEED CONTROL WITH ONE MACHINE

INNOVATIONS



MSC™
MULTIFUNCTION
SAFETY
CONTROL



M421
ANTI-SCALE



REDUCED
MAINTENA
COSTS



IPC'S
EXCLUSIVE
BOILER

SPECS



2 FIXED PNEUMATIC WHEELS AND 2 PIVOT WHEELS (1 WITH BREAK)



DIRECT WATER SUPPLY OR SUCTION WITH EXTERNAL TANK



CONTROL PANEL SHOWING: BURNER LOCKOUT INDICATOR LIGHT, WARNING LACK OF ANTISCALE, SCHEDULED MAINTENANCE (150 HRS), MAX TEMPERATURE INDICATOR (TEMPERATURE REACHED)

TECHNICAL DATA

Code			GREEN JET 7510 M GNVA40078
Operating pressure	bar/Mpa	75/7,5	
Flow rate	l/h	360	
Outlet water temperature max	°C	~100 (constant temperature)	
Power supply	Ph-V-Hz/A	1-230-50	
Absorbed power	kW	1,9	
Motor pole	rpm	4-1400	
Remote control		DTS	
Pump(type)		IPC plunger/brass/ceramic	
Boiler thermal power	kW	75	
Fuel consumption	Kg/h	6,3	
Fuel tank	l	18	
Antiscale tank	l	2	
Dimension (LxWxH)	cm	83x109x100	
Weight	Kg	75	

STANDARD EQUIPMENT

CODE: IPPR40025 HANDGRIP G6000	CODE: LCPR89117 70 cm DOUBLE STAINLESS STEEL LANCE	CODE: UGLN02299 H.P. NOZZLE 1/4 1506	CODE: TBAP40229 H.P. HOSE 10 m 1/4''	CODE: LCLC40025 70 cm LANCE WITH SPRAY BAR (SPRAY BAR L= 50 cm)
				

OPTIONAL

CODE: PRCH40040 ANTI-SCALE TREATMENT M421 10 Kg




STEAM GENERATORS

SUGGESTED SECTORS	140
EXCLUSIVE TECHNOLOGIES	142
SG-08/SG-10	144
SG-20/SG-30	146
SG-45	148
SG-48	150
SG-50	152
SG-55	154
SG-10 + PT 04	156

AUTOMOTIVE



CAR WASHING

- ▶ EXTERNAL DEGREASING AND DEWAXING
- ▶ INTERNAL DEEP CLEANING OF SEATS, MATS AND CEILINGS
- ▶ AC PIPELINE DEEP CLEANING

GARAGES/BODY REPAIR SHOPS AND TYRE CENTRES

CAR-HIRE AGENCIES/CAR DEALERS

- ▶ EXTERNAL DEGREASING AND DEWAXING
- ▶ INTERNAL DEEP CLEANING OF SEATS, MATS AND CEILINGS
- ▶ AC PIPELINE DEEP CLEANING

HO.RE.CA.



HOTELS

- ▶ DEEP GUEST ROOM CLEANING
- ▶ DEEP TOILET CLEANING
- ▶ DEEP MAT, PILLOW, CURTAIN CLEANING AND ODOR CONTROL

RESTAURANTS

- ▶ CARPET AND FURNITURE CLEANING
- ▶ DEEP TOILET CLEANING
- ▶ DEEP AND DAILY KITCHEN CLEANING

CATERING

- ▶ MACHINE AND FOOD PROCESSOR CLEANING
- ▶ DEEP TOILET CLEANING
- ▶ DEEP AND DAILY CLEANING

FOOD INDUSTRY AND RETAILERS



FOOD PROCESSING

- ▶ DEEP CLEANING OF MACHINERY AND FURNITURE
- ▶ DEEP CLEANING OF CONVEYOR BELTS
- ▶ DEEP CLEANING OF TRAYS AND CONTAINERS

FOOD TRANSPORT & STORAGE

- ▶ DEEP INTERNAL CLEANING OF TRUCKS AND VANS
- ▶ DEEP CLEANING OF STORAGE AREAS

FOOD DISPLAY

- ▶ DEEP CLEANING OF COLD DISPLAY UNITS
- ▶ GLASSES AND BENCHES DEEP CLEANING

LARGE COMMON AREAS



SCHOOLS

- ▶ DEEP CLEANING OF COMMON AREAS
- ▶ DEEP TOILET CLEANING AND ODOR CONTROL
- ▶ DAILY/DEEP CLEANING OF RESTAURANTS/KITCHENS

AIRPORTS

- ▶ DEEP CLEANING OF COMMON AREAS
- ▶ DEEP TOILET CLEANING AND ODOR CONTROL
- ▶ DAILY/DEEP CLEANING OF RESTAURANTS/KITCHENS

MARINE TERMINALS AND BUS/ TRAIN/UNDERGROUNDS/STATIONS

- ▶ DEEP CLEANING OF COMMON AREAS
- ▶ DEEP TOILET CLEANING AND ODOR CONTROL
- ▶ DAILY/DEEP CLEANING OF RESTAURANTS/KITCHENS



IPC

BY TENNANT COMPANY

EXCLUSIVE TECHNOLOGIES

BOILER POWER

Steam boilers designed to ensure best energy performance, component protection against limestone and corrosion. IPC boilers comply with the PED (Pressure Equipment Directive) which regulates the manufacturing of pressure equipment

ANTI-BUG

Our machines' dry saturated steam (for a temperature of 140-160°C within the boiler) ensures efficient disinfection. It is particularly useful in eliminating

POWER FILTER

A special stainless-steel filter that keeps machine circuits and accessories clean from impurities and limestone

SUCTION POWER

Available on some models as an integration to steam.
Great suction performance both on textiles and hard surfaces, and it can vacuum both dust and liquids

AUTOMATIC SHUTDOWN

This system automatically deactivates all machine functions when the pressure is lower than 2,5bar

SAFETY

Our products are protected against high temperatures and our electric panels are protected against humidity and infiltration.
Maximum safety is ensured by a protection system that protects against accidental steam discharges

ERGONOMICS

Devices that make the product very functional thanks to intuitive, noiseless, comfortable and easy to use components

FLEX POWER

Flexible hoses designed to resist heavy use or twisting forces

DURABILITY

High-quality boilers, heaters, pumps and electronic components. joints and valves in stainless steel or brass, plastic anti-shock device of maximum thickness.

EXCLUSIVE TECHNOLOGIES

	SG-08 SG-10	SG-20 SG-30	SG-45	SG-48	SG-50	SG-55
	•	•	•	•	•	•
	•	•	•	•	•	•
			•	•	•	•
		•		•	•	•
			•		•	•
	•	•	•	•	•	•
	•	•	•	•	•	•
	•	•	•	•	•	•

Specifications, descriptions and pictures are indicative: rights to technical modifications reserved without prior notice.



IPC

BY TENNANT COMPANY

STEAM GENERATORS

SG-08/SG-10 (ONLY STEAM)

PRESSURE

4,5÷6
bar

STEAM FLOW RATE

50÷80
g/min

ABSORBED POWER

2÷3,2
kW

EXCLUSIVE CHARACTERISTICS

- ▶ POWER BOILER
- ▶ ANTIBUG
- ▶ AUTOMATIC SHUTDOWN
- ▶ SAFETY
- ▶ ERGONOMICS
- ▶ FLEX POWER
- ▶ DURABILITY

MOST FREQUENTLY USE

AUTOMOTIVE



HO.RE.CA.



FOOD INDUSTRY AND RETAILERS



LARGE COMMON AREAS



SPECS



HANDLE FOR A CONVENIENT TRANSPORTATION



STAINLESS STEEL STRUCTURE SUITABLE FOR AREAS WHERE HYGENE IS A MUST



DIGITAL INDICATOR OF:
- BOILER TEMPERATURE
- STEAM READY
- WATER LACK



SG-10
BOILER WITH AUTO FILLING TANK

TECHNICAL DATA

		SG-8 S 4507 M	SG-10 S 5007 M	SG-10 S 6008 M
Code		GNVA40036	GNVA40037	GNVA40038
PERFORMANCE				
Operating pressure	bar/Mpa	4,5/0,45	5/0,5	6/0,6
Steam flow rate	g/min	~ 50÷60	~ 60÷70	~ 65÷80
Max steam temperature	°C	150	160	165
Start up time	min	~ 8	~ 3	~ 3
Power supply	Ph-V-Hz	1-230-50	1-230-50	1-230-50
Max absorbed power	kW	2	2,2	3,2
Boiler volume	l	2	1,8 (continuous recharge)	1,8 (continuous recharge)
Water tank	l	-	2,5	2,5
Dimension (LxWxH)	cm	45x28x31	45x28x31	45x28x31
Weight	kg	10	8	10

STANDARD EQUIPMENT

CODE: IPIP40019
HANDGRIP + STEAM HOSE
2,5 m



CODE: MPVR40851
EXTENSION TUBE
L=500 mm (2 PCS)



CODE: MPVR40852
NOZZLE JOINT



CODE: SPPV40052
BRUSH FOR WINDOW
CLEANING



CODE: SPPV40053
MULTIPURPOSE BRUSH



CODE: SPPV40054
TRIANGULAR BRUSH



CODE: SPPV40055
STEAM LANCE CURVED
L= 175



CODE: SPPV40056
SMALL ROUND BRUSH WITH
POLYESTER BRISTLES D.28



CODE: SPPV40057
SMALL ROUND BRUSH
WITH BRASS BRISTLES D.28



CODE: SPPV40058
RECTANGULAR CLOTH



OPTIONAL ACCESSORIES

CODE: MPVR40857
SELF REFFILING BOTTLE



CODE: AZMC40024
WRENCH FOR
MAINTENANCE



CODE: KTRI40446
TROLLEY





IPC

BY TENNANT COMPANY

STEAM GENERATORS

SG-20/SG-30 (STEAM+SUCTION)

PRESSURE

5÷5,5
bar

STEAM FLOW RATE

80÷100
g/min

ABSORBED POWER

3
kW

EXCLUSIVE CHARACTERISTICS

- ▶ POWER BOILER
- ▶ ANTI-BUG
- ▶ SUCTION POWER
- ▶ SAFETY
- ▶ ERGONOMICS
- ▶ FLEX POWER
- ▶ DURABILITY



SG-20

SG-30 - BOILER WITH AUTO-FILLING TANK

MOST FREQUENTLY USE

AUTOMOTIVE



HO.RE.CA.



FOOD INDUSTRY AND RETAILERS




LARGE COMMON AREAS



SPECS



HANDLE FOR A CONVENIENT TRANSPORTATION.



CONTROL PANEL ENSURING A CONSTANT CHECK OF MACHINE MAIN FUNCTIONS.



ROTARY KNOB FOR STEAM QUANTITY CONTROLLER

TECHNICAL DATA

		SG-20 S 5008 M	SG-30 P 5510 M
Code		GNVA40016	GNVA40017
PERFORMANCE			
Operating pressure	bar/Mpa	5/0,5	5,5/0,55
Steam flow rate	g/min	0-80	0-100
Max steam temperature	°C	140	140
Start up time	min	~ 7	~ 7
Power supply	Ph-V-Hz	1-230-50	1-230-50
Max absorbed power	kW	3	3
Boiler volume	l	2,2	2,2 (auto-filling)
Water/detergent tank	l	2	2
Dimension (LxWxH)	cm	57x40x65	57x40x65
Weight	kg	16	18

STANDARD EQUIPMENT

CODE: IPIP45757
HANDGRIP + HOSE
STEAM/SUCTION 2,5 m
(FOR SG-20)



CODE: IPIP40001
HANDGRIP + HOSE
STEAM/SUCTION 2,5 m
(FOR SG-30)



CODE: KTRI46482
ACCESSORIES KIT
STEAM/SUCTION



OPTIONAL ACCESSORIES

CODE: IPIP47898
HANDGRIP + HOSE
STEAM 2,5 m
(FOR SG-20)



CODE: IPIP45815
HANDGRIP + HOSE
STEAM 5 m
(FOR SG-30)



CODE: KTRI40275
STEAM ONLY
ACCESSORIES KIT



CODE: KTRI89496
TROLLEY



CODE: KTRI40269
DESCALING KIT
(10 PHIALS)



CODE: SPPV46076
BRASS BRUSH Ø30



CODE: SPPV40035
BRASS BRUSH Ø50





IPC

BY TENNANT COMPANY

STEAM GENERATORS

SG-45 (ONLY STEAM)

SOFT TOUCH PANEL

PRESSURE

5
bar

STEAM FLOW RATE

100
g/min

ABSORBED POWER

2,9
kW



EXCLUSIVE CHARACTERISTICS

- ▶ POWER BOILER
- ▶ ANTI-BUG
- ▶ POWER FILTER
- ▶ AUTOMATIC SHUTDOWN
- ▶ SAFETY
- ▶ ERGONOMICS
- ▶ FLEX POWER
- ▶ DURABILITY

MOST FREQUENTLY USE

AUTOMOTIVE



HO.RE.CA.



FOOD INDUSTRY AND RETAILERS



LARGE COMMON AREAS




SPECS



STEAM HOSE HOOK
EQUIPPED WITH SAFETY
PANEL



ROTARY KNOB FOR STEAM
FLOW RATE CONTROLLER



NON-MARKING WHEELS

TECHNICAL DATA

		SG-45 5008 M
Code		GNVA40020
PERFORMANCE		
Operating pressure	bar/Mpa	2,5-5/0,25-0,5
Steam flow rate	g/min	0-100
Max steam temperature	°C	160
Start up time	min	~ 6
Power supply	Ph-V-Hz/A	1-230-50/13
Max absorbed power	kW	2,9
Boiler volume	l	3
Water tank	l	7
Detergent tank	l	2
Dimension (LxWxH)	cm	66x43x67
Weight	Kg	20

STANDARD EQUIPMENT

CODE: IPIP45815
HANDGRIP + HOSE
STEAM 5 m



CODE: KTRI40275
STEAM ONLY
ACCESSORIES KIT



CODE: MPVR88900
TANK 5 l



OPTIONAL ACCESSORIES

CODE: IPIP40003
HANDGRIP + HOSE
STEAM 8 m



CODE: KTRI89495
TROLLEY



CODE: KTRI40269
DESCALING KIT
(10 PHIALS)





IPC

BY TENNANT COMPANY

STEAM GENERATORS

SG-48 (STEAM+SUCTION)

PRESSURE

8
bar

STEAM FLOW RATE

100
g/min

ABSORBED POWER

3,5
kW



EXCLUSIVE CHARACTERISTICS

- ▶ SUCTION POWER
- ▶ POWER BOIL
- ▶ ANTI BUGS
- ▶ POWER FILTER
- ▶ SAFETY
- ▶ ERGONOMICS
- ▶ POWER FLEX
- ▶ DURABILITY

MOST FREQUENTLY USE

AUTOMOTIVE



HO.RE.CA.



FOOD INDUSTRY AND RETAILERS



LARGE COMMON AREAS



SPECS



DIGITAL INDICATOR OF:
STEAM TEMPERATURE,
STEAM READY AND LACK OF
WATER.



STAINLESS STEEL STRUCTURE



5 LITRES DETERGENT AND
WATER TANK

TECHNICAL DATA

Code		SG-48 8010 M
PERFORMANCE		GNVA40043
Operating pressure	bar/Mpa	8/0,8
Steam flow rate	g/min	80÷100
Steam temperature (max)	°C	185
Start up time	min	6
Power supply	Ph-V-Hz/A	1-230-50/15,2
Absorbed power max.	kW	3,5
Vacuum power	kW	1,4
Boiler power	kW	3,4
Boiler volume	l	3,2
Water tank	l	5
Detergent tank	l	5
Dimension (LxWxH)	cm	74,5x48x104
Weight	Kg	32

STANDARD EQUIPMENT

CODE: IPIP40021
HANDGRIP + HOSE 4 m



CODE: MPVR40958
HOSE EXTENSION
L=500 mm 2 PZ



CODE: SPPV40060
MULTIPURPOSE FLOOR
BRUSH



CODE: SPPV40061
CARPET PROTECTION FOR
MULTIPURPOSE BRUSH



CODE: SPPV40062
FRAME WITH BRISTLES AND
RUBBER SCRAPERS FOR
MULTIPURPOSE BRUSH



CODE: SPPV40063
BRUSH FOR WINDOW
CLEANING



CODE: SPPV40064
TRANSPARENT NOZZLE



CODE: SPPV40065
LARGE SUCTION NOZZLE
+ SQUEEGEE



CODE: SPPV40066
SMALL SUCTION NOZZLE



CODE: SPPV40067
STEAM LANCE



CODE: SPPV40056
ROUND BRUSH POLYESTER
BRISTLE Ø28 mm



CODE: SPPV40068
ROUND BRUSH POLYESTER
BRISTLE Ø65 mm



CODE: SPPV40069
ROUND BRUSH POLYESTER
BRISTLE Ø40 mm



CODE: SPPV40070
ROUND BRUSH INOX
BRISTLE Ø40 mm



CODE: AZMC40024
WRENCH FOR
MAINTENANCE



CODE: SPPV40058
RECTANGULAR CLOTH



CODE: SPPV40072
INJECTION/EXTRACTION
NOZZLE



CODE: SPPV40073
BRISTLE FRAME FOR
INJECTION/EXTRACTION
NOZZLE L=150 mm



ACCESSORIES SUITABLE FOR INTERNAL CAR CLEANING

CODE: TTRT40000
ROTATING LANCE



CODE: TBFX40013
STEAM HOSE 6MT



ACCESSORY FOR CLEANING / SANITIZING BARRIQUE



IPC

BY TENNANT COMPANY

STEAM GENERATOR - STEAM+SUCTION

SG-50 (WITH TROLLEY)

PRESSURE

5÷7
bar

FLOW RATE

100÷140
g/min

ABSORBED POWER

3,5÷7,1
kW



EXCLUSIVE CHARACTERISTICS

- ▶ POWER BOILER
- ▶ ANTI BUGS
- ▶ AUTOMATIC SHUTDOWN
- ▶ SAFETY
- ▶ ERGONOMICS
- ▶ POWER FLEX
- ▶ DURABILITY
- ▶ POWER FILTER
- ▶ POWER SUCTION

MOST FREQUENTLY USE

HEALTHCARE



FOOD PROCESSING



FOOD RETAIL



TRANSPORT



INDUSTRY



EDUCATION



WINERY



HO.RE.CA.



INNOVATIONS



MODULAR
BUILD-UP

SPECS



STAINLESS STEEL
STRUCTURE, SUITABLE FOR
AREAS WHERE HYGIENE IS A
MUST



INTEGRATED TROLLEY
AND VACUUM CLEANER
TO FACILITATE
MANOEUVRABILITY AND
TRANSPORT



CONTROL PANEL WITH
MICRO TOUCH BUTTONS AND
ROTARY KNOB FOR STEAM
QUANTITY CONTROL

TECHNICAL DATA

		SG-50 S 5010 M	SG-50 S 5014 T
Code		GNVA40068	GNVA40069
PERFORMANCE			
Operating pressure	bar/Mpa	2,5-5/0,25-0,5	4,5-7/0,45-0,7
Steam flow rate	g/min	0-100	0-140
Steam temperature	°C	160	160
Start up time	min	~ 5	~ 5
Power supply	Pw-V-Hz/A	1-230-50/15	3-400-50/10,7
Absorbed power	kW	3,5	7,1
Boiler volume	l	4	5
Water tank	l	6	6
Detergent tank	l	6	6
Dimensions (LxWxH)	cm	109x40x107	109x40x107
Weight	kg	45	50

STANDARD EQUIPMENT (STEAM AND SUCTION)

CODE: IPIP40004
HANDGRIP + 5 m HOSE

CODE: KTRI40277
ACCESSORIES KIT *



SINGLE COMPONENTS INCLUDED IN KIT KTRI40277*

CODE: SPPV45770
MULTIUSE FLOOR
BRUSH

CODE: SPPV45762
INJECTION +
EXTRACTION
NOZZLE

CODE: SPPV45769
BRASS SQUEEGEE

CODE: SPPV45764
UNIVERSAL
STEAM LANCE

CODE: SPPV46531
SLOPING NOZZLE

CODE: SPPV87590
INSERT FOR
RECTANGULAR
BRUSH (TO BE
USED WITH SLOPING
NOZZLE SPPV46531)

CODE: MPVR45761
L= 50 cm HOSES
EXTENSION
(2PCS)

CODE: KTRI46580
O-RING KIT (FOR
HOSE EXTENSION
MPVR45761)



OPTIONAL ACCESSORIES (ONLY STEAM)

CODE: IPIP45815
HANDGRIP + 5 m HOSE

CODE: KTRI40275 **
ACCESSORIES KIT

CODE: SPPV40083
L=21 cm RECTANGULAR
MULTIUSE BRUSH (TO BE USED
WITH IPIP45815 + MPVR45785)

CODE: SPPV40084
STEAM CONTACT NOZZLE

CODE: SPPV40079
BASIC STEAM MOP



CODE: SPPV40080
ERGONOMIC STEAM MOP

CODE: FRAN01859
1 PC MICROFIBER CLOTH
(TO BE USED WITH STEAM MOP
SPPV40079/40080)

CODE: FRAN01860
10 PCS KIT MICROFIBER
CLOTH (TO BE USED WITH STEAM
MOP SPPV40079/40080)

CODE: PANN00125
1 PC MICROFIBER CLOTH
L=20 cm (TO BE USED WITH
RECTANGULAR MULTIUSE BRUSH
SPPV40083)

CODE: PANN00138
10 PCS KIT MICROFIBER
CLOTH L=20 cm (TO BE USED
WITH RECTANGULAR MULTIUSE
BRUSH SPPV40083)



CODE: PANN00136
1 PC MICROFIBER CLOTH 20
X3 cm (TO BE USED WITH STEAM
CONTACT NOZZLE SPPV40084)

CODE: PANN00139
10 PCS KIT MICROFIBER
CLOTH 20 X3 cm (TO BE USED
WITH STEAM CONTACT NOZZLE
SPPV40084)



SINGLE COMPONENTS INCLUDED IN KIT KTRI40275**

CODE: SPPV89000
RECTANGULAR
MULTI-USE BRUSH

CODE: MPVR45785
L= 50 cm HOSE
EXTENSION (2PCS)

CODE: SPPV45789
BRUSH FOR
WINDOW CLEANING

CODE: SPPV45793
120° CURVED STEAM
LANCE

CODE: SPPV89931
30 mm NYLON
BRISTLES BRUSH
(3PCS)

CODE: SPPV87589
50 mm NYLON
BRISTLES BRUSH
(3PCS)

CODE: KTRI89902
O-RING KIT (FOR HOSE
EXTENSION MPVR45785)





IPC

BY TENNANT COMPANY

STEAM GENERATORS

SG-55 (STEAM+SUCTION)

PRESSURE

8
bar

STEAM FLOW RATE

250
g/min

ABSORBED POWER

10,4
kW

EXCLUSIVE CHARACTERISTICS

- ▶ POWER BOIL
- ▶ ANTI BUGS
- ▶ POWER FILTER
- ▶ AUTOMATIC SHUTDOWN
- ▶ SAFETY
- ▶ ERGONOMICS
- ▶ POWER FLEX
- ▶ DURABILITY



MOST FREQUENTLY USE

AUTOMOTIVE



HO.RE.CA.



FOOD INDUSTRY AND RETAILERS



LARGE COMMON AREAS



SPECS



STANDARD VACUUM
CLEANER IN STAINLESS
STEEL STRUCTURE.



STAINLESS STEEL STRUCTURE



CONTROL PANEL:

- PRESSURE GAUGE
- BOILER TEMPERATURE DIGITAL INDICATOR
- STEAM READY INDICATOR LIGHT
- DETERGENT LACK INDICATOR LIGHT
- POWER SUPPLY INDICATOR LIGHT
- STEAM OUTPUT REGULATOR
- BOILER SWITCH
- DETERGENT SWITCH
- MAIN SWITCH

TECHNICAL DATA

Code		SG-55 8025 T
PERFORMANCE		GNVA40047
Operating pressure	bar/Mpa	8/0,8
Steam flow rate	g/min	250
Steam temperature (max)	°C	180
Start up time	min	~ 5
Power supply	Ph-V-Hz	3-400-50
Absorbed power max.	kW	10,4
Vacuum power	kW	1,4
Boiler volume	l	4,2
Water tank	l	15
Detergent tank	l	5
Dimension (LxWxH)	Cm	80x55x102
Weight	Kg	47

STANDARD EQUIPMENT

CODE: IPIP40021
HANDGRIP + HOSE 4 m



CODE: MPVR40958
HOSE EXTENSION
L=500 mm 2 PC



CODE: SPPV40060
MULTIPURPOSE FLOOR
BRUSH



CODE: SPPV40061
CARPET PROTECTION FOR
MULTIPURPOSE BRUSH



CODE: SPPV40062
FRAME WITH BRISTLES AND
RUBBER SCRAPERS FOR
MULTIPURPOSE BRUSH



CODE: SPPV40063
GLASS CLEANER



CODE: SPPV40065
LARGE SUCTION NOZZLE
+ SQUEEGEE



CODE: SPPV40066
SMALL SUCTION NOZZLE



CODE: SPPV40067
STEAM LANCE



CODE: SPPV40056
ROUND BRUSH POLYESTER
BRISTLE Ø28 mm



CODE: SPPV40068
ROUND BRUSH POLYESTER
BRISTLE Ø65 mm



CODE: SPPV40069
ROUND BRUSH POLYESTER
BRISTLE Ø40 mm



CODE: SPPV40070
ROUND BRUSH INOX
BRISTLE Ø40 mm



CODE: AZMC40024
WRENCH FOR
MAINTENANCE



CODE: SPPV40073
BRISTLE FRAME FOR
INJECTION/EXTRACTION
NOZZLE L=150 mm



CODE: SPPV40072
INJECTION/EXTRACTION
NOZZLE



CODE: TTRT40000
ROTATING LANCE



CODE: TBFX40013
STEAM HOSE 6MT



ACCESSORIES SUITABLE FOR INTERNAL CAR CLEANING

ACCESSORY FOR CLEANING / SANITIZING BARRIQUE



IPC

BY TENNANT COMPANY

MULTIPURPOSE STEAM TROLLEY

SG-10 + PT 04 (ONLY STEAM)



PRESSURE

5÷6
bar

FLOW RATE

70÷80
g/min

ABSORBED POWER

2,2÷3,2
kW



EXCLUSIVE CHARACTERISTICS

- ▶ POWER BOILER
- ▶ ANTI BUGS
- ▶ SAFETY
- ▶ ERGONOMICS
- ▶ FLEX POWER
- ▶ DURABILITY

MOST FREQUENTLY USE

HEALTHCARE



FOOD PROCESSING



FOOD RETAIL



TRANSPORT



INDUSTRY



EDUCATION



WINERY



HO.RE.CA.



INNOVATIONS



MODULAR
BUILD-UP

SPECS



TROLLEY WITH 125 mm
WHEELS (N° 2 WHEELS WITH
BREAK).



DIGITAL INDICATOR:
- BOILER TEMP
- STEAM READY
- WATER LACK



SG-10 HAS A STAINLESS
STEEL STRUCTURE

TECHNICAL DATA



		SG-10 S 5007 M GNVA40037*	SG-10 S 6008 M GNVA40038*
Code			
PERFORMANCE			
Operating pressure	bar/Mpa	5/0,5	6/0,6
Steam flow rate max	g/min	~60-70	~65-80
Steam temperature	°C	160	165
Start up time	min	~3	~2,5
Power supply	Ph-V-Hz	1-230-50	1-230-50
Absorbed power boiler	kW	2,2	3,2
Boiler volume	l	1,8	1,8
Water tank	l	2,5	2,5
Detergent tank	l	-	-
Weight	Kg	8	10
Dimensions (LxWxH)	cm	45x28x31	45x28x31

* Codes are referred to machines and do not include trolley



Code disassembled		CLEANING TROLLEY PT 04
Code assembled		CARR03159
PERFORMANCE		CARR03171
1 Working plan holder		v
1 Lid for bag holder		v
2 x 70l bag holder		v
1 Gloves or mask box holder		v
1 Gel bottle holde		v
2 Safety sign holders		v
2 Plastic holder for handle		v
1 Door with metal key		v
1 20l drawer		v
4 125mm castors		v
Supporting parts for steam applications		v
Dimensions (LxWxH)	cm	120x66x97
Weight	Kg	32

* Codes are referred to machines and do not include trolley

STANDARD EQUIPMENT (ONLY STEAM)

CODE: IPIP40019
2,5 m HANDGRIP + STEAM HOSE



CODE: MPVR40851
L=500 mm EXTENSION HOSES (2 PCS)



CODE: MPVR40852
BRUSH FOR WINDOW CLEANING



CODE: SPPV40052
GLASS CLEANER



CODE: SPPV40053
MULTIPURPOSE BRUSH



CODE: SPPV40054
TRIANGULAR BRUSH



CODE: SPPV40055
L= 175 mm CURVED STEAM LANCE



CODE: SPPV40056
Ø28 mm SMALL ROUND BRUSH WITH POLYESTER BRISTLES



CODE: SPPV40057
Ø28 mm SMALL ROUND BRUSH WITH BRASS BRISTLES



CODE: SPPV40058
RECTANGULAR CLOTH



OPTIONAL ACCESSORIES

CODE: SPPV40077
STEAM MOP



CODE: SPPV40076
CLOTH (FOR STEAM MOP SPPV40077)



CODE: MPVR40857
SELF REFFILING BOTTLE



CODE: AZMC40024
WRENCH FOR MAINTENANCE



CODE: SPPV40085
STEAM CONTACT NOZZLE



CODE: PANN00136
1 PCS MICROFIBER CLOTH 20 X3 cm (TO BE USED WITH STEAM CONTACT NOZZLE SPPV40084)



CODE: PANN00139
10 PCS KIT MICROFIBER CLOTH 20 X3 cm (TO BE USED WITH STEAM CONTACT NOZZLE SPPV40084)



STEAM + SUCTION BASIC ACCESSORIES

CODE: KTRI40272
WET & DRY VACUUM
SERVICE FOR SG-50



CODE: IPIP45757
HANDGRIP + HOSE
STEAM/SUCTION 2,5 m
(STANDARD FOR SG-20)



CODE: IPIP40001
HANDGRIP + HOSE
STEAM/SUCTION 2,5 m
(STANDARD FOR SG-30)



CODE: IPIP40004
HANDGRIP + HOSE
STEAM/SUCTION 5 m
(OPTIONAL FOR SG-50)



CODE: KTRI40277
ACCESSORIES KIT
STEAM/SUCTION
(FOR SG-50)



CODE: KTRI46482
ACCESSORIES KIT
STEAM/SUCTION
(FOR SG-20 / SG-30)



SINGLE COMPONENTS INCLUDED IN KIT KTRI46482

CODE: SPPV45770
MULTIUSE FLOOR BRUSH



CODE: SPPV45762
INJECTION + EXTRACTION
NOZZLE



CODE: SPPV45769
SQUEEGE NOZZLE



CODE: SPPV45764
UNIVERSAL STEAM LANCE



CODE: SPPV46531
SLOPING NOZZLE



CODE: SPPV87590
RECTANGULAR NYLON
BRUSH



CODE: MPVR45761
HOSE EXTENSION
STEAM/SUCTION (2 PCS)



CODE: KTRI46580
O-RING KIT



CODE: SPPV45763
STEAM NEBULIZER



CODE: MPVR45765
CURVED STEAM LANCE



CODE: SPPV89931
Ø30 NYLON BRISTLES
BRUSH (1 PC)



CODE: SPPV87585
ROUND BRUSH INSERT



CODE: SPPV87587
TRIANGULAR BRUSH
INSERT



CODE: SPPV45766
Ø30 HALF NYLON
BRISTLES BRUSH (3PCS)



SINGLE COMPONENTS INCLUDED IN KIT KTRI40277

CODE: SPPV45770
MULTIUSE FLOOR BRUSH



CODE: SPPV45762
INJECTION + EXTRACTION
NOZZLE



CODE: SPPV45769
SQUEEGE NOZZLE



CODE: SPPV45764
UNIVERSAL STEAM LANCE



CODE: SPPV46531
SLOPING NOZZLE



CODE: SPPV87590
RECTANGULAR NYLON
BRUSH



CODE: MPVR45761
HOSE EXTENSION
STEAM/SUCTION (2 PCS)



CODE: KTRI46580
O-RING KIT



SINGLE COMPONENTS INCLUDED IN MULTIUSE FLOOR BRUSH COD: SPPV45770

CODE: SPPV87588
DUST BRUSH INSERT



CODE: SPPV45774
STRIP BRISTLES BRUSH
L=300 mm



CODE: SPPV45772
STRIP BRISTLES BRUSH
L=300 mm



CODE: SPPV45773
STRIP BRISTLES BRUSH
L=300 mm



CODE: MPVR45775
STRIP BRISTLES BRUSH
L=300 mm



STEAM + SUCTION SPECIAL APPLICATIONS ACCESSORIES

CODE: SPPV40032
23 cm TRANSPARENT
INJECTION + EXTRACTION
NOZZLE



CODE: SPID45330
DEPRESSION TURBO BRUSH



CODE: SPPV40033
WALL PAPER REMOVER
210X290 mm



CODE: SPPV40038
WINDOW CLEAN NOZZLE



CODE: SPPV48971
ROUND BRUSH INSERT
(TO BE USED WITH
SPPV46531)



CODE: SPPV45763
SPRAYER (TO BE USED
WITH SPPV45764)



CODE: MPVR45765
CURVED STEAM LANCE
(TO BE USED WITH
SPPV45764)



CODE: SPPV87587
TRIANGULAR BRUSH
INSERT (TO BE USED WITH
SPPV46531)



STEAM ONLY - BASIC ACCESSORIES

CODE: IPIP47898
HANDGRIP + HOSE
STEAM 2,5 m
(OPTIONAL FOR SG-20)



CODE: IPIP45815
HANDGRIP + HOSE STEAM
5 m (STANDARD FOR SG-45
OPTIONAL FOR SG-30 SG-50)



CODE: IPIP40003
HANDGRIP + HOSE STEAM
8 m (OPTIONAL FOR
SG-45/SG-50)



CODE: KTRI40275
STEAM ONLY ACCESSORIES
KIT (STANDARD FOR SG-45
OPTIONAL FOR
SG-20/SG-30/SG-50)



SINGLE COMPONENTS INCLUDED IN KIT KTRI40275

CODE: SPPV89000
RECTANGULAR MULTI-USE
BRUSH



CODE: MPVR45785
EXTENSION HOSES 2PCS



CODE: SPPV45789
WINDOW CLEANER
STEAM BRUSH



CODE: SPPV45793
120° CURVED STEAM
LANCE



CODE: SPPV89931
Ø30 mm NYLON BRISTLES
BRUSH (3PCS)



CODE: SPPV87589
Ø50 mm NYLON BRISTLES
BRUSH (3PCS)



CODE: KTRI89902
O-RINGS FOR HOSE
EXTENSION



STEAM ONLY - SPECIAL APPLICATIONS ACCESSORIES

CODE: KTRI89215
STEAM MOP



CODE: SPPV40039
MICROFIBER SLEEVE
FOR DELICATE SURFACES
(10PCS)



CODE: SPPV40034
Ø50 mm STAINLESS STEEL
BRUSH (1 PC)



CODE: SPPV40035
Ø50 mm BRASS BRUSH
(1 PC)



CODE: SPPV45791
STEAM WINDOW
CLEANER 25/35 cm



CODE: SPPV45787
TRIANGULAR BRUSH



CODE: KTRI45328
PROFESSIONAL FLATIRON
KIT (OPTIONAL FOR SG-50)



OTHER ACCESSORIES

CODE: MPVR88900
TANK 5 l (STANDARD FOR
SG-40/SG-45/SG-50)



CODE: KTRI40269
DESCALING KIT
(10 PHIALS)



CODE: KTRI89496
TROLLEY (FOR SG-20 / SG-30)



CODE: KTRI89495
TROLLEY (FOR SG-45)



CODE: KTRI40271
TROLLEY (FOR SG-50)





PURE WATER CLEANING SYSTEM

SUGGESTED SECTORS	162
EXCLUSIVE TECHNOLOGIES	164
HPB HIGH PURE	165
HPE HIGH PURE	166
HPG HIGH PURE	167
ACCESSORIES	168

BUILDING



RENOVATION

- WINDOW CLEANING

BUILDINGS

- WINDOW CLEANING
- SHOP WINDOW CLEANING

CONCRETE INDUSTRY

GREEN ENERGIES



PHOTOVOLTAIC PANELS

- SOLAR PANEL WASHING AND RINSING

WIND TURBINES

- STRUCTURE WASHING AND RINSING

NAUTICAL - AUTOMOTIVE - TRANSPORT



CAR WASHING

- ▶ EXTERNAL RINSING

BOATS AND SHIPS

- ▶ WINDOW CLEANING
- ▶ EXTERNAL SURFACE WASHING AND RINSING

BUSES & TRAINS

- ▶ WINDOW CLEANING
- ▶ EXTERNAL SURFACE WASHING AND RINSING

GREENHOUSES - GLASSHOUSES - TENSILE STRUCTURES



GREENHOUSES

- ▶ EXTERNAL AND INTERNAL ROOF/
WALL WASHING AND RINSING
- ▶ WINDOW CLEANING

GLASSHOUSES

- ▶ EXTERNAL AND INTERNAL ROOF/
WALL WASHING AND RINSING
- ▶ WINDOW CLEANING

TENSILE STRUCTURES

- ▶ TENSILE STRUCTURE WASHING
AND RINSING



IPC

BY TENNANT COMPANY

EXCLUSIVE TECHNOLOGIES

HPB
HPE
HPG

POWER FILTER	A 4-stage filtration system for complete water purification	•
POWER PUMP	High-quality rotary blade pumps with a brass structure to prevent possible contamination of treated water	•
ERGONOMICS	Extreme ease of movement, thanks to a structure with handles and puncture-proof solid wheels	•
MANOMETER	Efficiency is always under control thanks to a flow meter that regulates the amount of water that passes through the filters. The manometer also controls membrane pressure	•
LONG LIFE	All components are designed to ensure long durability and reliability. The brass connectors control thanks possible contamination of treated water	•



IPC

BY TENNANT COMPANY

PURE WATER CLEANING SYSTEM

HPB HIGH PURE

PRESSURE

~5 bar

FLOW RATE

~5 l/min



BATTERY NOT INCLUDED

EXCLUSIVE CHARACTERISTICS

- ▶ POWER FILTER
- ▶ ERGONOMICS
- ▶ DURABILITY
- ▶ POWER PUMP
- ▶ MANOMETER

TECHNICAL DATA

Code

HPB
APTA40016

PERFORMANCE

Operating pressure	bar	~5
Pure water flow	l/min	~5
Water in/out connections	gas	3/4"
Maximum working height	m	16 (also with 2 poles)
Productivity	m ² /h	up to 200
Power supply		Gel battery
Dimension (LxWxH)	cm	53x50x127
Weight	kg	50

MOST FREQUENTLY USE

CONSTRUCTION INDUSTRY



GREEN ENERGIES



NAUTICAL/AUTO/TRANSPORTS



GREENHOUSES/GLASSHOUSES/
TENSILE STRUCTURES



STANDARD EQUIPMENT

CODE: FTAC40002
REVERSE OSMOSIS
MEMBRANE



CODE: PRCH40034
POWDER FOR
OSMOTIC MEMBRANE
FILTER MAINTENANCE



CODE: KTRI40106
FILTER KIT: - 1 pcs
sediment filter - 1 pcs
active carbon filter - 1 pcs
deionizing resin cartridge



CODE: TBFX40010
DRAINAGE TUBE



CODE: TBFX40009
30 m FLEXIBLE HOSE
WITH FITTINGS



CODE: VVSF40018
FLOW REGULATION
VALVE



CODE: AZMC40006
HAND-HELD TDS
METER



CODE: CNPR40007
GASKET LUBRICANT





IPC

BY TENNANT COMPANY

PURE WATER CLEANING SYSTEM

HPE HIGH PURE

PRESSURE

~8 bar

FLOW RATE

~ 7 l/min



THIS MODEL
CAN BE COMBINED WITH:
IDAF40884 -
PW-C40 D1005P4 M
PAG. 50

EXCLUSIVE CHARACTERISTICS

- POWER FILTER
- ERGONOMICS
- DURABILITY
- POWER PUMP
- MANOMETER

MOST FREQUENTLY USE

CONSTRUCTION INDUSTRY



GREEN ENERGIES



NAUTICAL/AUTO/TRANSPORTS



GREENHOUSES/GLASSHOUSES/ TENSILE STRUCTURES



TECHNICAL DATA

Code

HPE
APTA40015

PERFORMANCE

Operating pressure	bar	~8
Pure water flow	l/min	~7
Water in/out connections	gas	3/4"
Maximum working height	m	16 (also with 2 poles)
Productivity	m ² /h	up to 200
Power supply	Ph-V-Hz	1-230-50
Absorbed power	kW	0,6
Dimension (LxWxH)	cm	53x50x127
Weight	kg	55

STANDARD EQUIPMENT

CODE: FTAC40002
REVERSE OSMOSIS
MEMBRANE



CODE: PRCH40034
POWDER FOR
OSMOTIC MEMBRANE
FILTER MAINTENANCE



CODE: KTRI40106
FILTER KIT: - 1 pcs
sediment filter - 1 pcs
active carbon filter - 1 pcs
deionizing resin cartridge



CODE: VVSF40018
FLOW REGULATION
VALVE



CODE: TBFX40009
30 m FLEXIBLE HOSE
WITH FITTINGS



CODE: CNPR40007
GASKET LUBRICANT



CODE: AZMC40006
HAND-HELD TDS
METER



CODE: TBFX40010
DRAINAGE TUBE



Specifications, descriptions and pictures are indicative: rights to technical modifications reserved without prior notice.



IPC

BY TENNANT COMPANY

PURE WATER CLEANING SYSTEM

HPG HIGH PURE

PRESSURE

~9 bar

FLOW RATE

~6,5 l/min



PETROL ENGINE

EXCLUSIVE CHARACTERISTICS

- ▶ POWER FILTER
- ▶ ERGONOMICS
- ▶ DURABILITY
- ▶ POWER PUMP
- ▶ MANOMETER

MOST FREQUENTLY USE

CONSTRUCTION INDUSTRY



GREEN ENERGIES



NAUTICAL/AUTO/TRANSPORTS



GREENHOUSES/GLASSHOUSES/
TENSILE STRUCTURES



TECHNICAL DATA

Code

HPG
APTA40012

PERFORMANCE

Operating pressure	bar	~9
Pure water flow	l/min	~6,5
Water in/out connections	gas	3/4"
Maximum working height	m	16 (also with 2 poles)
Productivity	m ² /h	up to 200
Engine type		Honda GX120 (gasoline)
Engine power	Hp	4
Dimension (LxWxH)	cm	53x67x127
Weight	kg	60

STANDARD EQUIPMENT

CODE: FTAC40002
REVERSE OSMOSIS
MEMBRANE



CODE: PRCH40034
POWDER FOR
OSMOTIC MEMBRANE
FILTER MAINTENANCE



CODE: KTRI40106
FILTER KIT: - 1 pcs
sediment filter - 1 pcs
active carbon filter - 1 pcs
deionizing resin cartridge



CODE: VVSF40018
FLOW REGULATION
VALVE



CODE: TBFX40009
30 m FLEXIBLE HOSE
WITH FITTINGS



CODE: CNPR40007
GASKET LUBRICANT



CODE: AZMC40006
HAND-HELD TDS
METER



CODE: TBFX40010
DRAINAGE TUBE



MODULAR POLES

CODE: KTRI40280
10 m CARBON FIBRE
MODULAR POLES KIT (8 Kg)



CODE: KTRI40281
16 m CARBON FIBRE
MODULAR POLES KIT (10 Kg)



KTRI40280 - SINGLE COMPONENTS INCLUDED IN KIT

CODE: LCPR40022
1,5 m CARBON FIBRE
SECTION (700g) - (6 PCS)



CODE: LCPR40083
0,75 m CARBON FIBRE
SECTION (484g) - (1 PCS)



CODE: KTRI40508
BAG FOR TRANSPORT
MODULAR POLES



CODE: TBFX40003
20 m FLEXIBLE HOSE WITH
FITTINGS



CODE: RCVR40107
5 cm DIRECT MOUNT
BRUSH ADAPTER



CODE: RCVR40053
FITTING WITH GASKET



KTRI40281 - SINGLE COMPONENTS INCLUDED IN KIT

CODE: LCPR40022
1,5 m CARBON FIBRE
SECTION (700g) - (10 PCS)



CODE: LCPR40083
0,75 m CARBON FIBRE
SECTION (484g) - (1 PCS)



CODE: KTRI40508
BAG FOR TRANSPORT
MODULAR POLES



CODE: TBFX40003
20 m FLEXIBLE HOSE WITH
FITTINGS



CODE: RCVR40107
5 cm DIRECT MOUNT
BRUSH ADAPTER



CODE: RCVR40053
FITTING WITH GASKET



TELESCOPIC POLES

CODE: LCPR40097
5,2 m GLASS FIBER
TELESCOPIC POLE KIT



CODE: LCPR40098
8,8 m FUSION TELESCOPIC
POLE KIT



CODE: LCPR40099
15,2 m CARBON FIBER
TELESCOPIC POLE KIT



LCPR40097 - LCPR40098 - LCPR40099 - SINGLE COMPONENTS INCLUDED IN KIT

CODE: TBBP40040
FLEXIBLE HOSE FOR
TELESCOPIC POLES AND
SPEED BRUSH (SOLD BY
METER)



CODE: RCVR40107
5 cm DIRECT MOUNT
BRUSH ADAPTER



CODE: RCVR40053
FITTING WITH GASKET



PLASTIC GOOSENECKS

CODE: RCVR40048
5 cm ADJUSTABLE
GOOSENECK



CODE: RCVR40070
25 cm ADJUSTABLE
GOOSENECK



ALUMINIUM GOOSENECKS

CODE: RCVR40104
10 cm ADJUSTABLE
GOOSENECK (192g)



CODE: RCVR40105
20 cm ADJUSTABLE
GOOSENECK (224g)



CODE: RCVR40106
40 cm ADJUSTABLE
GOOSENECK (269g)



ALUMINIUM GOOSENECKS FOR DOUBLE BRUSH

CODE: RCVR40108
10 cm ADJUSTABLE
GOOSENECK FOR DOUBLE
BRUSH (342 g)



CODE: RCVR40109
20 cm ADJUSTABLE
GOOSENECK FOR DOUBLE
BRUSH (364g)



CODE: RCVR40110
40 cm ADJUSTABLE
GOOSENECK FOR DOUBLE
BRUSH(464g)




SOFT SPEED BRUSH (FOR ORDINARY CLEANING)

CODE: SPID40020
35 cm NYLON BRUSH
WITH 0° NOZZLES




CODE: SPID40022
35 cm NYLON BRUSH WITH
0°/25° NOZZLES



CODE: SPID40021
35 cm BRUSH WITH
NATURAL BRISTLES, 0° /
25° NOZZLES



CODE: SPID40023
45 cm NYLON BRUSH WITH
0°/25° NOZZLES



BACK SCRUB (REAR WASHING FLEECE SUPPORT)

CODE: SPPV40029
25 cm WASHING
FLEECE SUPPORT
TECHNOLITE (TO BE
USED WITH ALUMINIUM
GOOSENECKS)



CODE: SPPV40030
25 cm MICROTIGER
REPLACEMENT SLEEVE



CODE: SPPV40031
25 cm FT12 REPLACEMENT
SLEEVE WITH ABRASIVE
STRIP



BATTERIES AND BATTERY CHARGERS

CODE: BAAC00134
12V 45A BATTERY
(RUNNING TIME UP TO 2
HOURS)



CODE: BACA00176
12V 5A CBHD1 "STAND
ALONE" BATTERY CHARGER
(FOR BAAC00134)



CODE: BAAC00117
12V 74A/C5 BATTERY
(RUNNING TIME UP TO 4
HOURS)



CODE: BACA00177
12V 10A CBHD2 "STAND
ALONE" BATTERY CHARGER
(FOR BAAC00117)



OTHER ACCESSORIES

CODE: KTRI40112
Y VALVE FOR 2 POLES
INSTALLATION



CODE: RCVR40111
PLASTIC T VALVE
(STANDARD WITH SPEED
BRUSH, OPT. WITH
DOUBLE BRUSH)



CODE: PRCH40034
1 Kg POWDER FOR
OSMOTIC MEMBRANE
FILTER MAINTENANCE



CODE: TBBP40040
FLEXIBLE HOSE FOR
TELESCOPIC POLES AND
SPEED BRUSH (SOLD BY
METER)





ELECTRIC VEHICLES

TIGER 250/TIGER 250 BC	172
-------------------------------	-----

TIGER 500	173
------------------	-----



ELECTRIC VEHICLE

TIGER 250/TIGER 250 BC

MOTOR

2/300
n°/W

BATTERY

2/12
n°/V

AUTONOMY

~3
h

TECHNICAL DATA

		TIGER 250G II *	TIGER 250 BC **
Code		ELVC42020	ELVC40000
PERFORMANCE			
Motor	N°/W	2/300	2/300
Battery	N°/V	2x12V	2x12V
Recharging voltage	V	24	100/240v
Autonomy	h	~3	~3
Battery rec. time	h	~8	~8
Max capacity on flat surface	kg	140	140
Max capacity on flat surface + haulage	kg	150	150
Max negotiable gradient with driven only	% max	~5%	~5%
Speed forward gear	km/h	0-12	0-12
Speed reverse gear	km/h	0-12	0-12
Dimension (LxWxH)	cm	120x65x115	120x65x115
Weight	kg	110	110

OPTIONAL ACCESSORY

CODE: BAAC29876
BATTERY 12V-38A
(197X165X170 mm - 14 Kg)
(2PCS)

PICTURE
NOT
AVAILABLE

CODE: BACA43835
ELECTRONIC BATTERY CHARGER
(260X205X145 mm - 7,5 Kg)

PICTURE
NOT
AVAILABLE

CODE: KTRI30043
BASIC FLAT TRAILER FOR
TRANSPORTING MATERIAL
(80X60 cm - 22 Kg)
(MAX CAPACITY: 60 Kg)



CODE: KTRI30044
BASKET TO BE USED WITH THE
FLAT TRAILER WITH KTRI30043
(78X59X80 cm - 11 Kg)
(MAX CAPACITY: 55 Kg)



CODE: KTRI30040
FRONT CARRIER BASKET
(DIM:40X30X18 cm - 1,5 Kg)



CODE: KTRI30041
KIT OF N°2 REAR SIDE CARRIER
BASKET (40X30X18 cm - 1,5 Kg)



CODE: KTRI30042
LARGE-VOLUME REAR BASKET
"MARKET" (60X50X54 cm -
9,5 Kg) (MAX CAPACITY: 65 Kg)



CODE: KTRI45151
BASIC FLAT TRAILER FOR
TRANSPORTING MATERIALS
(135X70X25 cm - 40 Kg)
(MAX CAPACITY: 100 Kg)



CODE: KTRI43036
MOP MODULE (WEIGHT: 13 Kg)



CODE: KTRI41464
ROTATING HEADLIGHT KIT
(46X26X173 - 4 Kg)



CODE: KTRI01755
TOOLS EQUIPMENT CLEANING
TROLLEY



CODE: KTRI01756
TROLLEY TRANSFER
EQUIPMENT



CODE: KTRI40041
FRONT AND REAR TROLLEY
CONNECTIONS
(TO BE USED WITH TROLLEY
KTRI01755-KTRI01756)

PICTURE
NOT
AVAILABLE

* Battery and battery charger not included.

** Battery charger is included (battery non included).



ELECTRIC VEHICLE

TIGER 500

MOTOR

2/600
n°/W

BATTERY

2/12
n°/V

AUTONOMY

~4
h

TECHNICAL DATA

		TIGER 500S II *
Code		ELVC42022
PERFORMANCE		
Motor	N°/W	2/600
Battery	N°/V	2x12V
Recharging voltage	V	24
Autonomy	h	~4
Battery rec. time	h	~8
Max capacity on flat surface	kg	170
Max capacity on flat surface + haulage	kg	270
Max negotiable gradient with driven only	% max	~12%
Speed forward gear	km/h	0-12
Speed reverse gear	km/h	0-12
Dimension (LxWxH)	cm	140x80x122
Weight	kg	150

OPTIONAL ACCESSORY

CODE: BAAC39925
BATTERY 12V-75A
(265X175X210 mm - 20 Kg)
(2PCS)

PICTURE
NOT
AVAILABLE

CODE: BACA00133
ELECTRONIC BATTERY
CHARGER

PICTURE
NOT
AVAILABLE

CODE: KTRI43848
ROTATING HEADLIGHT KIT
(46X16X140 cm - 5 Kg)



CODE: KTRI43160
MOP MODULE (13 Kg)



CODE: KTRI31323
ROTATING HEADLIGHT KIT
(71X68X106 cm - 30 Kg)



CODE: KTRI30052
KIT OF N°2 REAR SIDE CARRIER
BASKET (36X21X21 cm - 1,5 Kg)



CODE: KTRI30053
LARGE-VOLUME REAR BASKET
"MARKET" (70X95X45 cm -
9,5 Kg)(MAX CAPACITY: 90 Kg)



CODE: KTRI40041
TROLLEY FRONT AND REAR
CONNECTIONS (TO BE USED
WITH TROLLEY KTRI01755/
KTRI01756)

PICTURE
NOT
AVAILABLE

CODE: KTRI30055
BASKET TO BE USED WITH
THE FLAT TRAILER WITH
KTRI30054 (88X74X80 cm -
12 Kg)
(MAX CAPACITY: 70 Kg)



CODE: KTRI30054
BASIC FLAT TRAILER FOR
TRANSPORTING MATERIAL
(95X75cm - 27 Kg)
(MAX CAPACITY: 120Kg)



CODE: KTRI45231
BASIC FLAT TRAILER FOR
TRANSPORTING MATERIALS
(136X80X55 cm - 70Kg)
(MAX CAPACITY: 200 Kg)



CODE: KTRI01755
TROLLEY CLEANING TOOLS
EQUIPMENT



CODE: KTRI01756
TROLLEY TRANSFER
EQUIPMENT



CODE: KTRI30051
FRONT CARRIER BASKET
(40X30X18 cm - 1,5 Kg)



* Battery and battery charger not included.



PACKAGING

HIGH PRESSURE WASHERS - COLD WATER	176
HIGH PRESSURE WASHERS - HOT WATER	178
HIGH PRESSURE WASHERS - STATIONARY	180
ELECTRICALLY HEATED BOILER	180
HOT WATER WEED REMOVAL SYSTEM	180
STEAM GENERATORS	181
PURE WATER CLEANING SYSTEM	181
ELECTRIC VEHICLES	181

HIGH PRESSURE WASHERS - COLD WATER

Code	Model	Carton	Pallet + carton	N°/ pallet	Dimension			Volume	Weight
					L mm	W mm	H mm	m³	kg
IDAF94300	PW-C09 I1207A M	•		48	340	290	410	0,04	8,40
IDAF94301	PW-C22 I1207A M	•		15	940	415	538	0,20	18,00
IDAF94303	PW-C22P I1307A M	•		15	940	415	538	0,20	23,00
IDAF94304	PW-C22P I1508A M	•		15	940	415	538	0,20	25,00
IDAF94339	PW-C22P I1609AO M	•		15	940	415	538	0,20	28,50
IDAF94223	PW-C23P I1408A M	•		12	400	350	850	0,12	22,80
IDAF94227	PW-C23P I1610A M	•		12	400	350	850	0,12	25,50
IDAF94229	PW-C23P I1508AO M	•		12	400	350	850	0,12	27,00
IDAF94231	PW-C23P I1610AO M	•		12	400	350	850	0,12	28,00
IDAF94359	PW-C21 I1508P M	•		24	500	300	420	0,06	21,00
IDAF94360	PW-C21 I1609P M	•		24	500	300	420	0,06	22,60
IDAF94361	PW-C21 I1310P M	•		24	500	300	420	0,06	22,60
IDAF94166	PW-C25 I1509P M	•		6	480	370	950	0,17	33,80
IDAF94169	PW-C25 I1813P T	•		6	480	370	950	0,17	35,00
IDAF94187	PW-C25P I1310P4 M	•		6	480	370	950	0,17	35,00
IDAF94170	PW-C25P I1509P M	•		6	480	370	950	0,17	36,20
IDAF94174	PW-C25P I1813P T	•		6	480	370	950	0,17	41,60
IDAF40237	PW-C40 1813P T	•		6	870	580	580	0,29	47,60
IDAF40245	PW-C40 1310P4 M	•		6	870	580	580	0,29	46,80
IDAF40246	PW-C40 D1310P4 M	•		6	870	580	580	0,29	46,80
IDAF40254	PW-C40 D1915P4 T	•		6	870	580	580	0,29	53,80
IDAF40884	PW-C40 D1005P4 M	•		6	900	600	700	0,38	48,00
IDAF40901	PW-C45 D1112P4 M	•		6	700	500	660	0,23	45,00
IDAF40902	PW-C45 D1310P4 M	•		6	700	500	660	0,23	45,00
IDAF40903	PW-C45 D1708P4 M	•		6	700	500	660	0,23	45,00
IDAF40904	PW-C45 D1813P T	•		6	700	500	660	0,23	45,50
IDAF40905	PW-C45 D1814P4 T	•		6	700	500	660	0,23	48,00
IDAF40906	PW-C45 D1915P4 T	•		6	700	500	660	0,23	50,50
IDAF409013	PW-C45 DP1310P4 M	•		6	700	500	660	0,23	45,00
IDAF409014	PW-C45 DP1708P4 M	•		6	700	500	660	0,23	45,00
IDAF409016	PW-C45 DP1813P4 T	•		6	700	500	660	0,23	48,00
IDAF409017	PW-C45 DP1915P4 T	•		6	700	500	660	0,23	50,50
IDAF41104	PW-C45 D1310P4m M (painted cover)	•		6	700	500	660	0,23	62
IDAF41105	PW-C45 D1915P4m T (painted cover)	•		6	700	500	660	0,23	73
IDAF40261	PW-C50 D2117P T	•		4	920	570	800	0,42	73,20
IDAF40270	PW-C50 D1622P T	•		4	920	570	800	0,42	67,00
IDAF40922	PW-C55 D2117P4 T	•		6	820	550	660	0,27	65,50
IDAF40923	PW-C55 D1721P4 T	•		6	820	550	660	0,27	67,30
IDAF40924	PW-C55 D2021P4 T	•		6	820	550	660	0,27	73,20
IDAF40925	PW-C55 D2515P4 T	•		6	820	550	660	0,27	73,20
IDAF40926	PW-C55 DP2117P4 T	•		6	820	550	660	0,27	65,50
IDAF40927	PW-C55 DP1721P4 T	•		6	820	550	660	0,27	67,30
IDAF40928	PW-C55 DP2021P4 T	•		6	820	550	660	0,27	73,20
IDAF40929	PW-C55 DP2515P4 T	•		6	820	550	660	0,27	73,20
IDAF41106	PW-C55 D2117P4m T	•		6	820	550	660	0,27	91,5
IDAF41108	PW-C55 D1721P4m T	•		6	820	550	660	0,27	83,5
IDAF41109	PW-C55 D2021P4m T	•		6	820	550	660	0,27	91,5

HIGH PRESSURE WASHERS - COLD WATER

Code	Model	Carton	Pallet + carton	N°/ pallet	Dimension			Volume	Weight
					L mm	W mm	H mm	m³	kg
IDAF40832	PW-C85 D2030P T		•	1	900	680	970	0,59	124,00
IDAF40827	PW-C85 D3515P T		•	1	1160	760	1100	0,97	121,00
IDAF40349	ABSOLUTE-C S2041P T		•	1	1260	800	1170	1,14	211,00
IDAF40350	ABSOLUTE-C S3521P T		•	1	1260	800	1170	1,14	205,00
IDAF40351	ABSOLUTE-C S5015P T		•	1	1260	800	1170	1,14	211,00
IDAF40932	ABSOLUTE-C S5022P T		•	1	1260	800	1170	1,14	250,00
IDAF40794	DIESEL-C L2017P D		•	1	1160	760	1100	0,97	135,00
CDVE49715	FIRE BOX 30 M		•	1	850	790	1090	0,73	119,50
CDVE49716	FIRE BOX 40 M		•	1	850	790	1090	0,73	129,00

HIGH PRESSURE WASHERS - HOT WATER

Code	Model	Carton	Pallet + carton	N°/ pallet	Dimension			Volume	Weight
					L mm	W mm	H mm	m³	kg
IDAC40572	PW-H10 I1207AA M		•	6	650	500	700	0,22	49,20
IDAC40572	PW-H10 I1207AA M	•		6	650	500	700	0,22	49,20
IDAC40573	PW-H10 I1408AA M	•		6	650	500	700	0,22	52,00
IDAC40574	PW-H10P I1408AO M		•	1	770	560	940	0,40	58,50
IDAC40680	PW-H28 I1308A M		•	1	910	730	1010	0,67	86,50
IDAC40683	PW-H28/4 I1308A M		•	1	910	730	1010	0,67	106,60
IDAC41124	PW-H28/4 D1310P4 M (stainless steel)		•	1	1130	810	1140	0,94	98,00
IDAC41125	PW-H28/4 D1713P T (stainless steel)		•	1	1130	810	1140	0,94	100,00
IDAC41351	PW-H31 D1309P M		•	1	910	730	1010	0,67	93,40
IDAC41352	PW-H31 D1310P4 M		•	1	910	730	1010	0,67	93,4
IDAC41353	PW-H31 D1509P4 M		•	1	910	730	1010	0,67	93,40
IDAC41354	PW-H31 D1708P4 M		•	1	910	730	1010	0,67	93,40
IDAC41355	PW-H31 D1713P T		•	1	910	730	1010	0,67	104,20
IDAC41356	PW-H31/4 D1309P M		•	1	910	730	1010	0,67	98,00
IDAC41357	PW-H31/4 D1310P4 M		•	1	910	730	1010	0,67	98,00
IDAC41358	PW-H31/4 D1509P4 M		•	1	910	730	1010	0,67	98,00
IDAC41359	PW-H31/4 D1708P4 M		•	1	910	730	1010	0,67	98,00
IDAC41360	PW-H31/4 D1713P T		•	1	910	730	1010	0,67	100,00
IDAC41361	PW-H61 D1813P4 T		•	1	1130	750	1110	1,06	143,50
IDAC41362	PW-H61 D1915P4 T		•	1	1130	750	1110	1,06	145,4
IDAC41377	PW-H61 D1517P4r T		•	1	1130	750	1110	1,06	147,4
IDAC41364	PW-H61 D1719P4 T		•	1	1130	750	1110	1,06	157,60
IDAC41363	PW-H61 D2017P4 T		•	1	1130	750	1110	1,06	157,60
IDAC41365	PW-H61/4 D1813P4 T		•	1	1130	750	1110	1,06	143,50
IDAC41366	PW-H61/4 D1915P4 T		•	1	1130	750	1110	1,06	145,4
IDAC41381	PW-H61/4 D1517P4r T		•	1	1130	750	1110	1,06	147,4
IDAC41368	PW-H61/4 D1719P4 T		•	1	1130	750	1110	1,06	157,60
IDAC41367	PW-H61/4 D2017P4 T		•	1	1130	750	1110	1,06	157,60
IDAC41369	PW-H61 D1813P4 T		•	1	1130	750	1110	1,06	143,50
IDAC41370	PW-H61 D1915P4 T		•	1	1130	750	1110	1,06	145,4
IDAC41385	PW-H61 D1517P4r T		•	1	1130	750	1110	1,06	147,4
IDAC41372	PW-H61 D1719P4 T		•	1	1130	750	1110	1,06	157,60
IDAC41371	PW-H61 D2017P4 T		•	1	1130	750	1110	1,06	157,60
IDAC41373	PW-H61/4 D1813P4 T		•	1	1130	750	1110	1,06	143,50
IDAC41374	PW-H61/4 D1915P4 T		•	1	1130	750	1110	1,06	145,4
IDAC41389	PW-H61/4 D1517P4r T		•	1	1130	750	1110	1,06	147,4
IDAC41376	PW-H61/4 D1719P4 T		•	1	1130	750	1110	1,06	157,60
IDAC41375	PW-H61/4 D2017P4 T		•	1	1130	750	1110	1,06	157,60
IDAC40361	PW-H90 D1521P T		•	1	1430	850	1070	1,30	195,00
IDAC40362	PW-H90 D2021P T		•	1	1430	850	1070	1,30	202,00
IDAC41379	PW-H101 D2021P T		•	1	1120	740	1100	0,91	184,40
IDAC41380	PW-H101 D2515P T		•	1	1120	740	1100	0,91	178,60
IDAC41383	PW-H101/4 D2021P T		•	1	1120	740	1100	0,91	184,40
IDAC41384	PW-H101/4 D2515P T		•	1	1120	740	1100	0,91	178,60
IDAC41387	PW-H101P D2021P T		•	1	1120	740	1100	0,91	183,80
IDAC41388	PW-H101P D2515P T		•	1	1120	740	1100	0,91	179,60
IDAC41391	PW-H101/4P D2021P T		•	1	1120	740	1100	0,91	183,80
IDAC41392	PW-H101/4P D2515P T		•	1	1120	740	1100	0,91	179,60

HIGH PRESSURE WASHERS - HOT WATER

Code	Model	Carton	Pallet + carton	N°/ pallet	Dimension			Volume	Weight
					L mm	W mm	H mm	m³	kg
IDAC41394	PW-H101HT D2015P T		•	1	1200	850	1100	1,12	160,00
IDAC41395	PW-H101/4HT D2015P T		•	1	1200	850	1100	1,12	160,00
IDAC41396	PW-H101A D2021P T		•	1	1120	740	1100	0,91	183,80
IDAC41397	PW-H101/4A D2021P T		•	1	1120	740	1100	0,91	183,80
IDAC41126	PW-H100P D1915P T		•	1	1200	850	1100	1,12	190,00
IDAC41127	PW-H100P D2017P T		•	1	1200	850	1100	1,12	190,00
IDAC41128	PW-H100P D1721P T		•	1	1200	850	1100	1,12	200,00
IDAC41129	PW-H100P D2021P T		•	1	1200	850	1100	1,12	210,00
IDAC41130	PW-H100P D2515P T		•	1	1200	850	1100	1,12	205,00
IDAC49710	SKID FUEGO H L1818Pi P		•	1	1200	940	1350	1,52	266,00

HIGH PRESSURE WASHERS - STATIONARY

Code	Model	Carton	Pallet + carton	N°/ pallet	Dimension			Volume	Weight
					L mm	W mm	H mm	m³	kg
PPEL40079	MLC-C D1310P M	•		4	600	550	400	0,13	34,00
PPEL40081	MLC-C D1813P T	•		4	600	550	400	0,13	42,50
PPEL40083	MLC-C D1915P T	•		4	600	550	400	0,13	41,50
PPEL40085	MLC-C D2117P T	•		4	600	550	400	0,13	52,50
IDAF40486	ML CMP D1310P4 M		•	1	740	410	730	0,22	55,60
IDAF40535	ML CMP D1813P T		•	1	740	410	730	0,22	56,50
IDAF40536	ML CMP D1915P4 T		•	1	740	410	730	0,22	63,00
IDAF40537	ML CMP D2117P4 T		•	1	740	410	730	0,22	73,50
IDAF40366	ML - C D1515Pi T		•	1	900	520	720	0,34	93,00
IDAF40367	ML - C D1521Pi T		•	1	900	520	720	0,34	90,50
IDAF40368	ML - C D1618Pi T		•	1	900	520	720	0,34	98,50
IDAF40369	ML - C D2015Pi T		•	1	900	520	720	0,34	98,20
IDAF40370	SML-C D1030Pi T		•	1	1110	750	1070	0,90	80,00
IDAF40372	SML-C D2021Pi T		•	1	1110	750	1070	0,90	136,50
IDAC48037	IWD H D1615Pi T		•	1	1400	650	1030	0,93	207,80
IDAC48038	IWD H D1618Pi T		•	1	1400	650	1030	0,93	209,00
IDAC48039	IWD H D2015Pi T		•	1	1400	650	1030	0,93	207,80
IDAC48040	IWD H D1521Pi T		•	1	1400	650	1030	0,93	207,80
IDAC48041	IWD H D2021Pi T		•	1	1400	650	1030	0,93	230,00

ELECTRICALLY HEATED BOILER

Code	Model	Carton	Pallet + carton	N°/ pallet	Dimension			Volume	Weight
					L mm	W mm	H mm	m³	kg
IDAC41398	PW-E101 D1404P12 T			1	1200	850	1100	1,12	130
IDAC41399	PW-E101 D1404P24 T			1	1200	850	1100	1,12	130
IDAC41400	PW-E101 D1710P12 T		•	1	1200	850	1100	1,12	130,4
IDAC41401	PW-E101 D1712P24 T		•	1	1200	850	1100	1,12	130,4
IDAC41402	PW-E101 D1712P36 T		•	1	1200	850	1100	1,12	130,4
IDAC41131	PW-E100 D1710P12 T		•	1	1200	850	1050	1,12	154,2
IDAC41132	PW-E100 D1712P24 T		•	1	1200	850	1050	1,12	154,2
IDAC41133	PW-E100 D1712P36 T		•	1	1200	850	1050	1,12	154,2
IDAC41134	IWD-E D1710P12 T		•	1	1400	650	1050	0,96	170
IDAC41135	IWD-E D1712P24 T		•	1	1400	650	1050	0,96	171
IDAC41136	IWD-E D1712P36 T		•	1	1400	650	1050	0,96	176

HOT WATER WEED REMOVAL SYSTEM

Code	Model	Carton	Pallet + carton	Dimension			Volume	Weight
				L mm	W mm	H mm	m³	kg
IDAC41539	GREEN JET 7006 M		•	910	730	1010	0,67	93,40
GNVA40051	GREEN JT 1010 M		•	1050	890	1160	1,08	161,20
GNVA40078	GREEN JET 7510 M		•	1050	890	1160	1,08	180

STEAM GENERATORS

Code	Model	Carton	Pallet + carton	N°/ pallet	Dimension			Volume	Weight
					L mm	W mm	H mm	m³	kg
GNVA40037	SG-10 S 5007 M	•		16	540	360	430	0,08	10,00
GNVA40038	SG-10 S 6008 M	•		16	540	360	430	0,08	12,00
GNVA40016	SG-20 S 5008 M	•		12	570	400	650	0,15	18,20
GNVA40017	SG-30 S 5510 M	•		12	570	400	650	0,15	18,94
GNVA40020	SG-45 5008 M	•		4	560	390	850	0,19	23,77
GNVA40043	SG-48 S 8010M		•	1	800	600	710	0,34	42
GNVA40067	SG-50 S 5008 M		•	1	890	540	1020	0,49	58
GNVA40068	SG-50 S 5010 M		•	1	890	540	1020	0,49	58
GNVA40069	SG-50 S 5014 T		•	1	890	540	1020	0,49	62
GNVA40047	SG-55 8025 T		•	1	855	615	1150	0,60	64,50

PURE WATER CLEANING SYSTEM

Code	Model	Carton	Pallet + carton	N°/ pallet	Dimension			Volume	Weight
					L mm	W mm	H mm	m³	kg
APTA40000	HPO		•	1	1300	590	660	0,51	44,60
APTA40016	HPB		•	1	1300	590	660	0,51	70,60
APTA40015	HPE		•	1	1300	590	660	0,51	66,00
APTA40012	HPG		•	1	1300	590	1220	0,94	67,20

ELECTRIC VEHICLES

Code	Model	Carton	Pallet + carton	N°/ pallet	Dimension			Volume	Weight
					L mm	W mm	H mm	m³	kg
ELVC42020	TIGER 250G II		•	1	1250	700	880	0,77	122,80
ELVC40000	TIGER 250 BC		•	1	1250	700	880	0,77	122,80
ELVC42022	TIGER 500S II		•	1	1450	830	970	1,17	172,00

[illegible]

[illegible]

[illegible]

Ip Cleaning Srl
Viale Treviso 63 - 30026 Summaga di Portogruaro (VE) - Italy

Tel. +39 0421 205511 - Fax +39 0421 204227
info@ipcworldwide.com - www.ipcworldwide.com



IPC

BY TENNANT COMPANY